

TABLE OF CONTENTS

ARTICLE 2.0000 AIR POLLUTION CONTROL REGULATIONS AND PROCEDURES

Section 2.0500 Emission Control Standards

2.0501	Compliance with Emission Control Standards	205-01
2.0502	Purpose.....	205-03
2.0503	Particulates from Fuel Burning Indirect Heat Exchangers.	205-04
2.0504	Particulates from Wood Burning Indirect Heat Exchangers.....	205-05
2.0505	<i>Control of Particulates from Incinerators (Repealed)</i>	205-07
2.0506	Particulates from Hot Mix Asphalt Plants.	205-07
2.0507	Particulates from Chemical Fertilizer Manufacturing Plants.....	205-08
2.0508	Particulates from Pulp and Paper Mills	205-08
2.0509	Particulates from Mica or Feldspar Processing Plants.....	205-09
2.0510	Particulates from Sand, Gravel, or Crushed Stone Operations	205-10
2.0511	Particulates from Lightweight Aggregate Processes	205-10
2.0512	Particulates from Wood Products Finishing Plants	205-11
2.0513	Particulates from Portland Cement Plants	205-11
2.0514	Particulates from Ferrous Jobbing Foundries	205-12
2.0515	Particulates from Miscellaneous Industrial Processes	205-13
2.0516	Sulfur Dioxide Emissions from Combustion Sources	205-14
2.0517	Emissions from Plants Producing Sulfuric Acid	205-14
2.0518	<i>Miscellaneous Volatile Organic Compound Emissions (Repealed)</i>	205-14
2.0519	Control of Nitrogen Dioxide and Nitrogen Oxides Emissions	205-15
2.0523	<i>Control of Conical Incinerators (Repealed)</i>	205-15
2.0524	New Source Performance Standards.....	205-16
2.0525	National Emission Standards for Hazardous Air Pollutants (Repealed) ..	205-17
2.0526	<i>Sulfur Dioxide Emissions from Fuel Burning Installations (Repealed by State Prior to Local Adoption)</i>	205-17
2.0527	Emissions from Spodumene Ore Roasting	205-17
2.0528	Total Reduced Sulfur from Kraft Pulp Mills	205-18
2.0529	Fluoride Emissions from Primary Aluminum Reduction Plants.	205-20
2.0530	Prevention of Significant Deterioration	205-21
2.0531	Sources in Nonattainment Areas.....	205-26
2.0532	Sources Contributing to an Ambient Violation.	205-32
2.0533	Stack Height.....	205-34
2.0535	Excess Emissions Reporting and Malfunctions.....	205-38
2.0537	Control of Mercury Emissions.....	205-41
2.0538	Control of Ethylene Oxide Emissions.....	205-42
2.0539	Odor Control of Feed Ingredient Manufacturing Plants	205-43
2.0540	Particulates from Fugitive Dust Emission Sources.....	205-46
2.0541	Control of Emissions from Abrasive Blasting	205-48
2.0543	Best Available Retrofit Technology	205-49
2.0544	Prevention of Significant Deterioration Requirements for Green House Gases.....	205-50

SECTION 2.0500 EMISSION CONTROL STANDARDS

2.0501 COMPLIANCE WITH EMISSION CONTROL STANDARDS

(a) Purpose and Scope. The purpose of this Regulation is to assure orderly compliance with emission control standards found in this Section. This Regulation shall apply to all air pollution sources, both combustion and non-combustion.

(b) All new sources shall be in compliance prior to beginning operations.

(c) In addition to any control or manner of operation necessary to meet emission standards in this Section, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards of MCAPCO Section 2.0400 - "Ambient Air Quality Standards" to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this Section are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

(d) The Bubble Concept. A facility with multiple emission sources or multiple facilities within the same area may choose to meet the total emission limitation for a given pollutant through a different mix of controls than that required by the Regulations in this Section or MCAPCO Section 2.0900 - "Volatile Organic Compounds".

(1) In order for this mix of alternative controls to be permitted the Director shall determine that the following conditions are met:

- (A) Sources to which MCAPCO Regulations 2.0524 - "New Source Performance Standards", 2.0530 - "Prevention of Significant Deterioration", 2.0531 - "Sources in Nonattainment Areas", 2.1110 - "National Emission Standards for Hazardous Air Pollutants" or 2.1111 - "Maximum Achievable Control Technology", the federal New Source Performance Standards (NSPS), the federal National Emission Standards for Hazardous Air Pollutants (NESHAPS), regulations established pursuant to Section 111(d) of the federal Clean Air Act, or state or federal Prevention of Significant Deterioration (PSD) requirements apply, shall have emissions no larger than if there were not an alternative mix of controls;
- (B) The facility (or facilities) is located in an attainment area or an unclassified area or in an area that has been demonstrated to be attainment by the statutory deadlines (with reasonable further progress toward attainment) for those pollutants being considered;
- (C) All of the emission sources affected by the alternative mix are in compliance with applicable regulations or are in compliance with established compliance agreements; and
- (D) The review of an application for the proposed mix of alternative controls and the enforcement of any resulting permit will not require expenditures on the part of Mecklenburg County in excess of five times that which would otherwise be required.

- (2) The owner(s) or operator(s) of the facility (facilities) shall demonstrate to the satisfaction of the Director that the alternative mix of controls is equivalent in total allowed emissions, reliability, enforceability, and environmental impact to the aggregate of the otherwise applicable individual emission standards; and
 - (A) that the alternative mix approach does not interfere with attainment and maintenance of ambient air quality standards and does not interfere with the PSD program; this demonstration shall include modeled calculations of the amount, if any, of PSD increment consumed or created;
 - (B) that the alternative mix approach conforms with reasonable further progress requirements in any nonattainment area;
 - (C) that the actual emissions under the alternate mix approach are in fact quantifiable, and trades among them are even;
 - (D) that the pollutants controlled under the alternative mix approach are of the same criteria pollutant categories, except that emissions of some criteria pollutants used in alternative emission control strategies are subject to the limitations as defined in 44 FR 71784 (December 11, 1979), Subdivision D.1.c.ii. The Federal Register referenced in this Part is hereby incorporated by reference and does not include subsequent amendments or editions.

The demonstrations of equivalence shall be performed with at least the same level of detail as The North Carolina State Implementation Plan for Air Quality (SIP) demonstration of attainment for the area in question. Moreover, if the facility involves another facility in the alternative strategy, it shall complete a modeling demonstration to ensure that air quality is protected. Demonstrations of equivalency shall also take into account differences in the level of reliability of the control measures or other uncertainties.

- (3) The emission rate limitations or control techniques of each source within the facility (facilities) subjected to the alternative mix of controls shall be specified in the facility's (facilities') permits(s).
- (4) Compliance schedules and enforcement actions shall not be affected because an application for an alternative mix of controls is being prepared or is being reviewed.
- (5) The Director may waive or reduce requirements in this Paragraph up to the extent allowed by the Emissions Trading Policy Statement published in the Federal Register of April 7, 1982, pages 15076-15086, provided that the analysis required by Paragraph (e) of this Regulation supports any waiver or reduction of requirements. The Federal Register referenced in this Paragraph is hereby incorporated by reference and does not include subsequent amendments or editions.

(e) In a permit application for an alternative mix of controls under Paragraph (d) of this Regulation, the owner or operator of the facility shall demonstrate to the satisfaction of the Director that the proposal is equivalent to the existing requirements of the North Carolina State Implementation Plan for Air Quality (SIP) in total allowed emissions, enforceability, reliability, and environmental impact. The Director shall provide for public notice with an opportunity for a request for public hearing following the procedures under MCAPCO Sections 1.5300 - "Enforcement; Variances; Judicial Review" or 1.5500 - "Title V Procedures", as applicable.

- (1) If and when a permit containing these conditions is issued under MCAPCO Section 1.5200 - "Air Quality Permits" (non-Title V permits), it shall become a part of the state implementation plan (SIP) as an appendix available for inspection at MCAQ. Until the U.S. Environmental Protection Agency (EPA) approves the SIP revision embodying the permit containing an alternative mix of controls, the facility shall continue to meet the otherwise applicable existing SIP requirements.
- (2) If and when a permit containing these conditions is issued under MCAPCO Section 1.5500 - "Title V Procedures", it shall be available for inspection at the Department. Until the EPA approves the Title V permit containing an alternative mix of controls, the facility shall continue to meet the otherwise applicable existing SIP requirements.

The revision shall be approved by EPA on the basis of the revision's consistency with EPA's "Policy for Alternative Emission Reduction Options Within State Implementation Plans" as promulgated in the Federal Register of December 11, 1989, pages 71780-71788, and subsequent rulings.

If owner or operator of any combustion and non-combustion source or control equipment subject to the requirements of this Section is required to demonstrate compliance with a rule in this Section the source testing procedures of Section 2.2600 - "Source Testing" of this Article shall be used.

*History Note: Temporary Amendment Eff. March 8, 1994 for a period of 180 days or until the permanent rule is effective, whichever is sooner;
Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. June 1, 2008; April 1, 2001; April 1, 1999; July 1, 1996; February 1, 1995; July 1, 1994; August 1, 1991; October 1, 1989.*

2.0502 PURPOSE

The purpose of the emission control standards set out in this Section is to establish maximum limits on the rate of emission of air contaminants into the atmosphere. All sources shall be provided with the maximum feasible control.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. June 1, 1981.*

2.0503 PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS

(a) Emissions of particulate matter from the combustion of a fuel that are discharged from any stack or chimney into the atmosphere shall not exceed:

Maximum Heat Input In Million Btu/Hour	For Particulate Matter	Allowable Emission Limit In Lb/Million Btu
Up to and Including 10		0.60
100		0.33
1,000		0.18
10,000 and Greater		0.10

For a heat input between any two consecutive heat inputs stated in the preceding table, the allowable emissions of particulate matter shall be calculated by the equation:

$$E = 1.090(Q)^{-0.2594}$$

E = allowable emission limit for particulate matter in lb/million Btu,

Q = maximum heat input in million Btu/hour.

(b) This Regulation applies to installations in which fuel is burned for the purpose of producing heat or power by indirect heat transfer. Fuels include those such as coal, coke, lignite, peat, natural gas, and fuel oils, but exclude wood and refuse not burned as a fuel. When any refuse, products, or by-products of a manufacturing process are burned as a fuel rather than refuse, or in conjunction with any fuel, this allowable emission limit shall apply.

(c) For the purpose of this Regulation, the maximum heat input shall be the total heat content of all fuels which are burned in a fuel burning indirect heat exchanger, the combustion products of which are emitted through a stack or stacks. The sum of maximum heat input of all fuel burning indirect heat exchangers at a plant site which are in operation, under construction, or permitted pursuant to MCAPCO Section 1.5200 - "Air Quality Permits" shall be considered as the total heat input for the purpose of determining the allowable emission limit for particulate matter for each fuel burning indirect heat exchanger. Fuel burning indirect heat exchangers constructed or permitted after February 1, 1983, shall not change the allowable emission limit of any fuel burning indirect heat exchanger whose allowable emission limit has previously been set. The removal of a fuel burning indirect heat exchanger shall not change the allowable emission limit of any fuel burning indirect heat exchanger whose allowable emission limit has previously been established. However, for any fuel burning indirect heat exchanger constructed after, or in conjunction with, the removal of another fuel burning indirect heat exchanger at the plant site, the maximum heat input of the removed fuel burning indirect heat exchanger shall no longer be considered in the determination of the allowable emission limit of any fuel burning indirect heat exchanger constructed after or in conjunction with the removal. For the purposes of this Paragraph, refuse not burned as a fuel and wood shall not be considered a fuel. For residential facilities or institutions (such as military and educational whose primary fuel burning capacity is

for comfort heat, only those fuel burning indirect heat exchangers located in the same power plant or building or otherwise physically interconnected (such as common flues, steam, or power distribution line) shall be used to determine the total heat input.

(d) The emission limit for fuel burning equipment that burns both wood and other fuels in combination, or for wood and other fuel burning equipment that is operated such that emissions are measured on a combined basis, shall be calculated by the equation:

$$E_c = [(E_w) (Q_w) + (E_o) (Q_o)] / Q_t.$$

E_c = the emission limit for combination or combined emission source(s) in lb/million Btu.

E_w = plant site emission limit for wood only as determined by MCAPCO Regulation 2.0504 - "Particulates from Wood Burning Indirect Heat Exchangers" in lb/million Btu.

E_o = the plant site emission limit for other fuels only as determined by Paragraphs (a), (b) and (c) of this Regulation in lb/million Btu.

Q_w = the actual wood heat input to the combination or combined emission source(s) in Btu/hr.

Q_o = the actual other fuels heat input to the combination or combined emission source(s) in Btu/hr.

Q_t = $Q_w + Q_o$ and is the actual total heat input to combination or combined emission source(s) in Btu/hr.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); Eff. February 1, 1976; Amended Eff. August 1, 1991; June 1, 1985; February 1, 1983.

2.0504 PARTICULATES FROM WOOD BURNING INDIRECT HEAT EXCHANGERS

(a) For the purpose of this Regulation the following definitions shall apply:

- (1) "**Functionally dependent**" means that structures, buildings or equipment are interconnected through common process streams, supply lines, flues, or stacks.
- (2) "**Indirect heat exchanger**" means any equipment used for the alteration of the temperature of one fluid by the use of another fluid in which the two fluids are separated by an impervious surface such that there is no mixing of the two fluids.
- (3) "**Plant site**" means any single or collection of structures, buildings, facilities, equipment, installations, or operations which:
 - (A) are located on one or more adjacent properties,
 - (B) are under common legal control, and
 - (C) are functionally dependent in their operations.

(b) The definition contained in Subparagraph (a)(3) of this Regulation does not affect the calculation of the allowable emission rate of any indirect heat exchanger permitted prior to April 1, 1999.

(c) Emissions of particulate matter from the combustion of wood shall not exceed:

Maximum Heat Input In Million Btu/Hour	Allowable Emission Limit For Particulate Matter In Lb/Million Btu
Up to and Including 10	0.70
100	0.41
1,000	0.25
10,000 and Greater	0.15

For a heat input between any two consecutive heat inputs stated in the preceding table, the allowable emissions of particulate matter shall be calculated by the equation:

$$E = 1.1698(Q)^{-0.2230}$$

E = allowable emission limit for particulate matter in lb/million Btu.

Q = Maximum heat input in million Btu/hour.

(d) This Regulation applies to installations in which wood is burned for the primary purpose of producing heat or power by indirect heat transfer.

(e) For the purpose of this Regulation, the heat content of wood shall be 8,000 Btu per pound (dry-weight basis). The total of maximum heat inputs of all wood burning indirect heat exchangers at a plant site in operation, under construction, or with a permit shall be used to determine the allowable emission limit of a wood burning indirect heat exchanger. Wood burning indirect heat exchangers constructed or permitted after February 1, 1983, shall not change the allowable emission limit of any wood burning indirect heat exchanger whose allowable emission limit has previously been set.

(f) The emission limit for fuel burning equipment that burns both wood and other fuels in combination or for wood and other fuel burning equipment that is operated such that emissions are measured on a combination basis shall be calculated by the procedure described in Paragraph (f) of MCAPCO Regulation 2.0503 - "Particulates from Fuel Burning Indirect Heat Exchangers".

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. August 1, 2002; April 1, 1999; June 1, 1985;
February 1, 1983.*

2.0505 CONTROL OF PARTICULATES FROM INCINERATORS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1);
143-215.107(a)(5); Eff. February 1, 1976;
Amended Eff. July 1, 1987; June 1, 1985;
February 1, 1983; Repealed Eff. October 1, 1991.

2.0506 PARTICULATES FROM HOT MIX ASPHALT PLANTS

(a) The allowable emission rate for particulate matter resulting from the operation of a hot mix asphalt plant that are discharged from any stack or chimney into the atmosphere shall not exceed the level calculated with the equation:

$$E = 4.9445(P)^{0.4376}$$

Calculated to three significant figures, for process rates less than 300 tons per hour, where:

E = the maximum allowable emission rate for particulate matter in pounds per hour;

P = the process rate in tons per hour.

The allowable emission rate shall be 60.0 pounds per hour for process rates equal to or greater than 300 tons per hour.

(b) Visible emissions from stacks or vents at a hot mix asphalt plant shall be less than 20 percent opacity when averaged over a six-minute period.

(c) All hot mix asphalt batch plants shall be equipped with a scavenger process dust control system for the drying, conveying, classifying, and mixing equipment. The scavenger process dust control system shall exhaust through a stack or vent and shall be operated and maintained in such a manner as to comply with Paragraph (a) and (b) of this Regulation.

(d) Fugitive non-process dust emissions shall be controlled by MCAPCO Regulation 2.0540 - "Particulates From Fugitive Dust Emission Sources".

(e) Fugitive emissions for sources at a hot mix asphalt plant not covered elsewhere under this Regulation shall not exceed 20 percent opacity averaged over six minutes.

(f) Paragraph not adopted as not applicable to any facilities in Mecklenburg County. All facilities in Mecklenburg County are required to comply with 20 percent standard.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. August 1, 2004; July 1, 1998; January 1, 1985.

2.0507 PARTICULATES FROM CHEMICAL FERTILIZER MANUFACTURING PLANTS

The allowable emissions rate for particulate matter resulting from the manufacture, mixing, handling, or other operations in the production of chemical fertilizer materials that are discharged from any stack or chimney into the atmosphere shall not exceed the level calculated with the equation:

$$E = 9.377(P)^{0.3067}$$

calculated to three significant figures, where:

- E = the maximum allowable emission rate for particulate matter in pounds per hour;
- P = the process rate (the sum of the production rate and the recycle rate) in tons per hour.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. April 1, 2003; July 1, 1998; January 1, 1985.*

2.0508 PARTICULATES FROM PULP AND PAPER MILLS

(a) Emissions of particulate matter from the production of pulp and paper that are discharged from any stack or chimney into the atmosphere shall not exceed:

- (1) 3.0 pounds per equivalent ton of air dried pulp from a recovery furnace stack;
- (2) 0.6 pounds per equivalent ton of air dried pulp from a dissolving tank vent; and
- (3) 0.5 pounds per equivalent ton of air dried pulp from a lime kiln stack.

(b) Emissions from any kraft pulp recovery boiler established after July 1, 1971, shall not exceed an opacity of 35 percent when averaged over a six-minute period. However, six-minute averaging periods may exceed 35 percent opacity if:

- (1) no six-minute period exceeds 89 percent opacity;
- (2) no more than one six-minute period exceeds 35 percent opacity in any one hour; and
- (3) no more than four six-minute periods exceed 35 percent opacity in any 24-hour period.

Where the presence of uncombined water vapor is the only reason for failure to meet this opacity limitation, this opacity limitation shall not apply.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 1998; August 1, 1987; April 1, 1986,
January 1, 1985; May 30, 1978.*

2.0509 PARTICULATES FROM MICA OR FELDSPAR PROCESSING PLANTS

(a) The allowable emission rate for particulate matter resulting from the processing of mica or feldspar that are discharged from any chimney, stack, vent, or outlet into the atmosphere shall not exceed the level calculated with the equation:

$$E = 4(P)^{0.677}$$

calculated to three significant figures for process rates less than or equal to 30 tons per hour.

For process rates greater than 30 tons per hour but less than 1,000 tons per hour, the allowable emission rate for particulate matter shall not exceed the level calculated with the equation:

$$E = 20.421(P)^{0.1977}$$

calculated to three significant figures.

For process rates greater than or equal to 1,000 tons per hour but less than 3,000 tons per hour, the allowable emission rate for particulate matter shall not exceed the level calculated with the equation:

$$E = 38.147(P)^{0.1072}$$

calculated to three significant figures.

The allowable emission rate shall be 90.0 pounds per hour for process weight rates equal to or greater than 3,000 tons per hour.

For the purpose of these equations:

E = maximum allowable emission rate for particulate matter in pounds per hour,

P = process weight rate in tons per hour.

(b) Fugitive non-process dust emissions shall be controlled by MCAPCO Regulation 2.0540 - "Particulates From Fugitive Dust Emission Sources".

(c) The owner or operator of any mica or feldspar plant shall control process-generated emissions:

(1) from crushers with wet suppression, and

(2) from conveyors, screens, and transfer points,

such that the applicable opacity standards in MCAPCO Regulation 1.5107 - "Control and Prohibition of Visible Emissions" or MCAPCO Regulation 2.0524 - "New Source Performance Standards" are not exceeded.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);

Eff. February 1, 1976;

Amended Eff. April 1, 2003; July 1, 1998; April 1, 1986; January 1, 1985.

2.0510 PARTICULATES FROM SAND, GRAVEL, OR CRUSHED STONE OPERATIONS

(a) The owner or operator of a sand, gravel, or crushed stone operation shall not cause, allow, or permit any material to be produced, handled, transported or stockpiled without taking measures to reduce to a minimum any particulate matter from becoming airborne to prevent exceeding the ambient air quality standards beyond the property line for particulate matter, both PM-10 and total suspended particulates.

(b) Fugitive non-process dust emissions from sand, gravel, or crushed stone operations shall be controlled by MCAPCO Regulation 2.0540 - "Particulates From Fugitive Dust Emission Sources".

(c) The owner or operator of any sand, gravel, or crushed stone operation shall control process-generated emissions:

- (1) from crushers with wet suppression, and
- (2) from conveyors, screens, and transfer points,

such that the applicable opacity standards in MCAPCO Regulation 1.5107 - "Control and Prohibition of Visible Emissions" or MCAPCO Regulation 2.0524 - "New Source Performance Standards" are not exceeded.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 1998; January 1, 1985.*

2.0511 PARTICULATES FROM LIGHTWEIGHT AGGREGATE PROCESSES

(a) The owner or operator of a lightweight aggregate process shall not cause, allow, or permit any material to be produced, handled, transported or stockpiled without taking measures to reduce to a minimum any particulate matter from becoming airborne to prevent the ambient air quality standards for particulate matter, both PM-10 and total suspended particulates, from being exceeded beyond the property line.

(b) Fugitive non-process dust emissions from lightweight aggregate processes subject to this Regulation shall be controlled by MCAPCO Regulation 2.0540 - "Particulates From Fugitive Non-Process Dust Emission Sources".

(c) The owner or operator of any lightweight aggregate process shall control process-generated emissions:

- (1) from crushers with wet suppression, and
- (2) from conveyors, screens, and transfer points,

such that the applicable opacity standards in MCAPCO Regulation 1.5107 - "Control and Prohibition of Visible Emissions" or MCAPCO Regulation 2.0524 - "New Source Performance Standards".

(d) Particulate matter from any stack serving any lightweight aggregate kiln or lightweight aggregate dryer shall be reduced by at least 95 percent by weight before being discharged to the atmosphere. The 95-percent reduction shall be by air pollution control devices.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 1998; October 1, 1989; January 1,
1985; April 1, 1977.*

2.0512 PARTICULATES FROM WOOD PRODUCTS FINISHING PLANTS

A person shall not cause, allow, or permit particulate matter caused by the working, sanding, or finishing of wood to be discharged from any stack, vent, or building into the atmosphere without providing, as a minimum for its collection, adequate duct work and properly designed collectors, or such other devices as approved by the Director, and in no case shall the ambient air quality standards be exceeded beyond the property line. Collection efficiency shall be determined on the basis of weight.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-
215.107(a)(5);
Eff. February 1, 1976; Amended Eff. January 1, 1985.*

2.0513 PARTICULATES FROM PORTLAND CEMENT PLANTS

(a) Particulate matter from any Portland cement kiln shall:

- (1) be reduced by at least 99.7 percent by weight before being discharged to the atmosphere; the 99.7-percent reduction shall be by air pollution control devices; and
- (2) not exceed 0.327 pounds per barrel.

(b) The emissions of particulate matter from any stacks, vent or outlets from all processes except Portland cement kilns shall be controlled by MCAPCO Regulation 2.0515 - "Particulates From Miscellaneous Industrial Processes".

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 1998; January 1, 1985.*

2.0514 PARTICULATES FROM FERROUS JOBBING FOUNDRIES

Particulate emissions from any ferrous jobbing foundry cupola existing before January 2, 1972 shall not exceed:

Maximum Allowable Process Weight Lb/Hr	Emission Rate For Particulate Lb/Hr
1,000	3.05
2,000	4.70
3,000	6.35
4,000	8.00
5,000	9.65
6,000	11.30
7,000	12.90
8,000	14.30
9,000	15.50
10,000	16.65
12,000	18.70
16,000	21.60
18,000	23.40
20,000	25.10

Any foundry existing before January 2, 1972, having a capacity greater than shown in the table and any new foundry, regardless of size, shall comply with the particulate emission limits specified in MCAPCO Regulation 2.0515 - "Particulates From Miscellaneous Industrial Processes" Paragraph (a).

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 1998; April 1, 1986; January 1, 1985.

2.0515 PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

(a) The allowable emission rates for particulate matter from any stack, vent, or outlet of any industrial process for which no other emission control standards are applicable shall not exceed the level calculated with the equation:

$$E = 4.10(P)^{0.67}$$

calculated to three significant figures for process rates less than or equal to 30 tons per hour.

For process weight rates greater than 30 tons per hour, the allowable emission rates for particulate matter shall not exceed the level calculated with the equation:

$$E = 55.0(P)^{0.11} - 40$$

calculated to three significant figures.

For the purpose of these equations:

E = maximum allowable emission rate for particulate matter in pounds per hour,

P = process rate in tons per hour.

(b) Process rate means the total weight of all materials introduced into any specific process that may cause any emission of particulate matter. Solid fuels charged are considered as part of the process weight, but liquid and gaseous fuels and combustion air are not. For a cyclical or batch operation, the process rate is derived by dividing the total process weight by the number of hours in one complete operation from the beginning of any given process to the completion thereof, excluding any time during which the equipment is idle. For a continuous operation, the process rate is derived by dividing the process weight for a typical period of time by the number of hours in that typical period of time.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. April 1, 2003, July 1, 1998; January 1, 1985.

2.0516 SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

(a) Emission of sulfur dioxide from any source of combustion that is discharged from any vent, stack, or chimney shall not exceed 2.3 pounds of sulfur dioxide per million Btu input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard. Sulfur dioxide formed or reduced as a result of treating flue gases with sulfur trioxide or other materials shall also be accounted for when determining compliance with this standard.

(b) A source subject to an emission standard for sulfur dioxide in MCAPCO Regulations 2.0524 - "New Source Performance Standards", 2.0527 - "Emissions from Spodumene Ore Roasting", 2.1110 - "National Emission Standards for Hazardous Air Pollutants", 2.1111 - "Maximum Achievable Control Technology", 2.1205 - "Municipal Waste Combustors", 2.1206 - "Hospital, Medical, and Infectious Waste Incinerators", 2.1210 - "Commercial and Industrial Solid Waste Incinerator Units", or 2.1211 - "Other Solid Waste Incinerator Units" shall meet the standard in that particular rule instead of the standard in Paragraph (a) of this Regulation.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a) (5);
Eff. February 1, 1976;
Amended Eff. July 1, 2007; April 1, 2003; July 1, 1996, October 1, 1989; January 1, 1985.*

2.0517 EMISSIONS FROM PLANTS PRODUCING SULFURIC ACID

Emissions of sulfur dioxide or sulfuric acid mist from the manufacture of sulfuric acid shall not exceed:

- (1) 27 pounds of sulfur dioxide per ton of sulfuric acid produced;
- (2) 0.5 pounds of acid mist (expressed as sulfuric acid) per ton of sulfuric acid produced.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. January 1, 1985.*

2.0518 MISCELLANEOUS VOLATILE ORGANIC COMPOUND EMISSIONS (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. April 1, 1997; July 1, 1996; September 1, 1994; December 1, 1993; February 1, 1983;
Repealed Eff. July 1, 2000.*

2.0519 CONTROL OF NITROGEN DIOXIDE AND NITROGEN OXIDES EMISSIONS

(a) The emissions of nitrogen dioxide shall not exceed 5.8 pounds per ton of acid produced from any sulfuric acid manufacturing plant.

(b) The emissions of nitrogen oxides shall not exceed:

- (1) 0.8 pounds per million Btu of heat input from any oil or gas-fired boiler with a capacity of 250 million Btu per hour or more;
- (2) 1.8 pounds per million Btu of heat input from any coal-fired boiler with a capacity of 250 million Btu per hour or more.

(c) The emission limit for a boiler that burns both coal and oil or gas in combination shall be calculated by the equation:

$$E = [(E_c) (Q_c) + (E_o) (Q_o)] / Q_t.$$

- E = the emission limit for combination in pounds per million Btu.
E_c = emission limit for coal only as determined by Paragraph (b) of this Regulation in pounds per million Btu.
E_o = emission limit for oil or gas as determined by Paragraph (b) of this Regulation in pounds per million Btu.
Q_c = the actual coal heat input to the combination in Btu per hour.
Q_o = the actual oil and gas heat input to the combination in Btu per hour.
Q_t = Q_c + Q_o and is the actual total heat input to the combination in Btu per hour.

(d) A boiler subject to an emission standard for nitrogen oxides under MCAPCO Regulation 2.0524 – “New Source Performance Standards or 2.1418 – “New Generating Units, Large Boilers, and Large I/C Engines of this Article shall meet the standard in that particular rule instead of the standard in Paragraph (a) of this Regulation.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 2007; January 1, 2005; July 1, 1996; October 1, 1989;
January 1, 1985.*

2.0523 CONTROL OF CONICAL INCINERATORS (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. January 1, 1985;
Repealed Eff. July 1, 2000.*

2.0524 NEW SOURCE PERFORMANCE STANDARDS

(a) With the exception of Paragraph (b) and (c) of this Regulation, sources subject to new source performance standards promulgated in 40 CFR Part 60 shall comply with emission standards, monitoring and reporting requirements, maintenance requirements, notification and record keeping requirements, performance test requirements, test method and procedural provisions, and any other provisions, as required therein, rather than with any otherwise-applicable Regulation in this Section which would be in conflict therewith.

(b) The following is not included under this Regulation:

- (1) 40 CFR Part 60, Subpart AAA (new residential wood heaters);
- (2) 40 CFR Part 60, Subpart B (adoption and submittal of state plans for designated facilities);
- (3) 40 CFR Part 60, Subpart C (emission guidelines and compliance times);
- (4) 40 CFR Part 60, Subpart Cb (guidelines for municipal waste combustors constructed on or before September 20, 1994);
- (5) 40 CFR Part 60, Subpart Cc (guidelines for municipal solid waste landfills);
- (6) 40 CFR Part 60, Subpart Cd (guidelines for sulfuric acid production units);
- (7) 40 CFR Part 60, Subpart Ce (guidelines for hospital, medical, infectious waste incinerators);
- (8) 40 CFR Part 60, Subpart BBBB (guidelines for small municipal waste combustion units constructed on or before August 30, 1999);
- (9) 40 CFR Part 60, Subpart DDDD (guidelines for commercial and industrial solid waste incinerators constructed on or before November 30, 1999);
- (10) 40 CFR Part 60, Subpart FFFF (guidelines for other solid waste incinerators constructed on or before December 9, 2004); or
- (11) 40 CFR Part 60, Subpart HHHH (guidelines for coal-fired electric steam generating units).

(c) Along with the notice appearing in the North Carolina Register for a public hearing to amend this Regulation to exclude a standard from this Regulation, the Director of the Department of Environment and Natural Resources - Division of Air Quality shall state whether or not the new source performance standards promulgated under 40 CFR Part 60, or part thereof, shall be enforced. If the North Carolina Environmental Management Commission does not adopt the amendment to this Regulation to exclude or amend the standard within 12 months after the close of the comment period on the proposed amendment, the Director of Mecklenburg County Air Quality shall begin enforcing that standard when 12 months has elapsed after the end of the comment period on the proposed amendment.

(d) New sources of volatile organic compounds that are located in an area designated in 40 CFR 81.334 as nonattainment for ozone or an area identified in accordance with MCAPCO Regulation 2.0902 - "Applicability" as being in violation of the ambient air quality standard for ozone shall comply with the requirements of 40 CFR Part 60 that are not excluded by this Regulation, as well as with any applicable requirements in MCAPCO Section 2.0900 - "Volatile Organic Compounds".

(e) All requests, reports, applications, submittals, and other communications to the administrator required under Paragraph (a) of this Regulation shall be submitted to the Director, Mecklenburg County Air Quality rather than to the Environmental Protection Agency.

(f) In the application of this Regulation, definitions contained in 40 CFR Part 60 shall apply rather than those of MCAPCO Section 2.0100 - "Definitions and References".

(g) With the exceptions allowed under MCAPCO 1.5211 - "Applicability", the owner or operator of the source shall apply for and receive a permit as required in MCAPCO Section 1.5200 - "Air Quality Permits" or 1.5500 - "Title V Procedures".

History Note: Filed as a Temporary Amendment Eff. March 8, 1994, for a period of 180 days or until the permanent rule is effective, whichever is sooner;
Filed as a Temporary Amendment Eff. January 3, 1988, for a period of 180 days to expire on June 30, 1988;
Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 150B-21.6;
Eff. June 18, 1976;
Amended Eff. July 1, 2007; July 1, 2000; April 1, 1997; July 1, 1996; July 1, 1994; December 1, 1992; July 1, 1992.

2.0525 NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (REPEALED)

History Note: Filed as a Temporary Amendment Eff. March 8, 1994 for a period of 180 days or until the permanent rule is effective, whichever is sooner;
Authority G.S. 143-215.3(a)(1); 143-215.107 (a)(5); 150B-21.6;
Eff. June 18, 1976;
Amended Eff. July 1, 1994; December 1, 1992; July 1, 1992; August 1, 1991;
Repeal Eff. July 1, 1996.

2.0526 SULFUR DIOXIDE EMISSIONS FROM FUEL BURNING INSTALLATIONS (REPEALED BY STATE PRIOR TO LOCAL ADOPTION)

2.0527 EMISSIONS FROM SPODUMENE ORE ROASTING

Emission of sulfur dioxide and sulfuric acid mist from any one kiln used for the roasting of spodumene ore shall not exceed:

- (1) 9.7 pounds of sulfur dioxide per ton of ore roasted; and

- (2) 1.0 pound of sulfuric acid mist, expressed as H₂SO₄, per ton of ore roasted.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. March 15, 1978;
Amended Eff. January 1, 1985.*

2.0528 TOTAL REDUCED SULFUR FROM KRAFT PULP MILLS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Black liquor solids”** means the dry weight of the solids which enter the recovery furnace in the black liquor.
- (2) **“Condensate stripper system”** means a column, and associated condensers, used to strip, with air or steam, total reduced sulfur compounds from condensate streams from various processes within a kraft pulp mill.
- (3) **“Cross recovery furnace”** means a furnace used to recover chemicals consisting primarily of sodium and sulfur compounds by burning black liquor which on a quarterly basis contains more than seven percent by weight of the total pulp solids from the neutral sulfite semichemical process and has a green liquor sulfidity of more than 28 percent.
- (4) **“Digester system”** means each continuous digester or each batch digester used for the cooking of wood in white liquor, and associated flash tanks, blow tanks, chip steamers and condensers.
- (5) **“Green liquor sulfidity”** means the sulfidity of the liquor which leaves the smelt dissolving tank.
- (6) **“Kraft pulp mill”** means any facility that produces pulp from wood by cooking (digesting) wood chips in a water solution of sodium hydroxide and sodium sulfide (white liquor) at high temperature and pressure. Regeneration of cooking chemicals through a recovery process is also considered part of the kraft pulp mill.
- (7) **“Lime kiln”** means a unit used to calcine lime mud, which consists primarily of calcium carbonate, into quicklime, which is calcium oxide.
- (8) **“Multiple-effect evaporator system”** means the multiple-effect evaporators and associated condensers and hot wells used to concentrate the spent cooking liquid that is separated from the pulp (black liquor).
- (9) **“Neutral sulfite semichemical pulping operation”** means any operation in which pulp is produced from wood by cooking (digestion) wood chips in a solution of sodium sulfite and sodium bicarbonate, followed by mechanical defibrating (grinding).
- (10) **“New design recovery furnace”** means a straight kraft recovery furnace that has both membrane wall or welded wall construction and emission control designed air systems.
- (11) **“Old design recovery furnace”** means a straight kraft recovery furnace that does not have membrane wall or welded wall construction or emission control designed air systems.
- (12) **“Recovery furnace”** means either a straight kraft recovery furnace or a cross recovery

- furnace and includes the direct-contact evaporator for a direct-contact furnace.
- (13) **“Smelt dissolving tank”** means a vessel used for dissolving the smelt collected from the recovery furnace.
 - (14) **“Straight kraft recovery furnace”** means a furnace used to recover chemicals consisting primarily of sodium and sulfur compounds by burning black liquor which on a quarterly basis contains seven percent by weight or less of the total pulp solids from the neutral sulfite semichemical process or has green liquor sulfidity of 28 percent or less.
 - (15) **“Total reduced sulfur (TRS)”** means the sum of the sulfur compounds hydrogen sulfide, methyl mercaptan, dimethyl sulfide, and dimethyl disulfide, that are released during the kraft pulping operation.

(b) This Regulation shall apply to recovery furnaces, digester systems, multiple-effect evaporator systems, lime kilns, smelt dissolving tanks, and condensate stripping systems of kraft pulp mills not subject to MCAPCO Regulation 2.0524 - “New Source Performance Standards”.

(c) Emissions of total reduced sulfur from any kraft pulp mill subject to this Regulation shall not exceed:

- (1) 20 parts per million from any old design recovery furnace,
- (2) five parts per million from any new design recovery furnace,
- (3) 25 parts per million from any cross recovery furnace,
- (4) five parts per million from any digester system,
- (5) five parts per million from any multiple-effect evaporator system,
- (6) 20 parts per million from any lime kiln,
- (7) five parts per million from any condensate stripping system,
and
- (8) 0.032 pounds per ton of black liquor solids (dry weight) from any smelt dissolving tank.

(d) The emission limitations given in Subparagraphs (c)(1) through (c)(7) of this Regulation are measured as hydrogen sulfide on a dry gas basis and are averages of discrete contiguous 12-hour time periods. The emission limitations given in Subparagraphs (c)(1) through (c)(3) of this Regulation are corrected to eight percent oxygen by volume. The emission limitations given in Subparagraph (c)(6) of this Regulation is corrected to 10 percent oxygen by volume.

(e) One percent of all 12-hour total reduced sulfur averages per quarter year in excess of the limitations given in Subparagraphs (c)(1) through (c)(3) of this Regulation, in the absence of start-ups, shut-downs and malfunctions, shall not be considered in violation.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. June 1, 1980;
Amended Eff. July 1, 1988; July 1, 1987, January 1, 1985;
November 1, 1982.*

2.0529 FLUORIDE EMISSIONS FROM PRIMARY ALUMINUM REDUCTION PLANTS

- (a) For the purpose of this Regulation, the following definitions apply:
- (1) **“Fluoride”** means elemental fluorine and all fluoride compounds as measured by the methods specified in MCAPCO Regulation 2.2616 – “Fluorides“ or by equivalent or alternative methods approved by the Director or his delegate. The Director may approve equivalent or alternative methods on an individual basis for sources or pollutants if equivalent or alternative methods can be demonstrated to determine compliance of permitted emission sources or pollutants.
 - (2) **“Prebake cell”** is an aluminum reduction pot which uses carbon anodes that are formed, pressed, and baked prior to their placement in the pot.
 - (3) **“Primary aluminum reduction plant”** means any facility manufacturing aluminum by electrolytic reduction.
- (b) This Regulation shall apply to prebake cells at all primary aluminum reduction plants not subject to MCAPCO Regulation 2.0524 - “New Source Performance Standards”.
- (c) An owner or operator of a primary aluminum reduction plant subject to this Regulation shall not cause, allow, or permit the use of the prebake cells unless:
- (1) 95 percent of the fluoride emissions are captured, and
 - (2) 98.5 percent of the captured fluoride emissions are removed before the exhaust gas is discharged into the atmosphere.
- (d) The owner or operator of a primary aluminum reduction plant subject to this Regulation shall:
- (1) ensure that hood covers are in good repair and positioned over the prebake cells;
 - (2) minimize the amount of time that hood covers are removed during pot working operations;
 - (3) if the hooding system is equipped with a dual low and high hood exhaust rate, use the high rate whenever hood covers are removed and return to the normal exhaust rate when the hood covers are replaced;
 - (4) minimize the occurrence of fuming pots and correct the cause of a fuming pot as soon as practical;
and
 - (5) if the tapping crucibles are equipped with hoses which return aspirator air under the hood, ensure that the hoses are in good repair and that the air return system is functioning properly.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. June 1, 2008; Amended Eff. July 1, 1988; January 1, 1985.*

2.0530 PREVENTION OF SIGNIFICANT DETERIORATION

(a) The purpose of the Regulation is to implement a program for the prevention of significant deterioration of air quality as required by 40 CFR 51.166.

(b) For the purposes of this Regulation, the definitions contained in 40 CFR 51.166(b) and 40 CFR 51.301 apply, except the definition of “baseline actual emissions.” For the purposes of this Regulation:

(1) **“Baseline actual emissions”** means the rate of emissions, in tons per year, of a regulated new source review (NSR) pollutant, as determined in accordance with Parts (A) through (C) of this Subparagraph:

- (A) For an existing emissions unit, baseline actual emissions means the average rate, in tons per year, at which the emissions unit actually emitted the pollutant during any consecutive 24-month period selected by the owner or operator within the five year period immediately preceding the date that a complete permit application is received by the Department for a permit required under this Regulation. The Director shall allow a different time period, not to exceed 10 years immediately preceding the date that a complete permit application is received by the Department, if the owner or operator demonstrates that it is more representative of normal source operation. For the purpose of determining baseline actual emissions, the following apply:
- (i) The average rate shall include fugitive emissions to the extent quantifiable and emissions associated with startups, shutdowns, and malfunctions;
 - (ii) The average rate shall be adjusted downward to exclude any non-compliant emissions that occurred while the source was operating above any emission limitation that was legally enforceable during the consecutive 24-month period;
 - (iii) For an existing emission unit (other than an electric utility steam generating unit), the average rate shall be adjusted downward to exclude any emissions that would have exceeded an emission limitation with which the major stationary source must currently comply. However, if the State has taken credit in an attainment demonstration or maintenance plan consistent with the requirements of 40 CFR 51.165(a)(3)(ii)(G) for an emission limitation that is part of a maximum achievable control technology standard that the Administrator of Environmental Protection Agency (EPA) proposed or promulgated under Part 63 in Title 40 of the Code of Federal Regulations, the baseline actual emissions shall be adjusted to account for such emission reductions;
 - (iv) For an electric utility steam generating unit, the average rate shall be adjusted downward to reflect any emissions reductions under G. S. 143-215.107D and for which cost recovery is sought pursuant to G. S. 62-133.6;
 - (v) For a regulated NSR pollutant, if a project involves multiple emissions units, only one consecutive 24-month period shall be used to determine the baseline actual emissions for all the emissions units being changed. A different consecutive 24-month period for each regulated NSR pollutant may be used for each regulated NSR pollutant; and
 - (vi) The average rate shall not be based on any consecutive 24-month period for

which there is inadequate information for determining annual emissions, in tons per year, and for adjusting this amount if required by Subparts (ii) and (iii) of this Part;

- (B) For a new emissions unit, the baseline actual emissions for purposes of determining the emissions increase that will result from the initial construction and operation of such unit shall equal zero and thereafter, for all other purposes, shall equal the unit's potential to emit; and
 - (C) For a plantwide applicability limit (PAL) for a stationary source, the baseline actual emissions shall be calculated for existing emissions units in accordance with the procedures contained in Part (A) of this Subparagraph and, for a new emissions unit, in accordance with the procedures contained in Part (B) of this Subparagraph;
- (2) In the definition of "net emissions increase," the reasonable period specified in 40 CFR 51.166(b)(3)(ii) shall be seven years;
 - (3) The limitation specified in 40 CFR 51.166(b)(15)(ii) shall not apply; and
 - (4) Particulate matter PM_{2.5} significant levels set forth in 40 CFR 51.166(b)(23)(i) are incorporated by reference except as otherwise provided in this Regulation. Sulfur dioxide (SO₂) and nitrogen oxides (NO_x) are precursors to PM_{2.5} in all attainment and unclassifiable areas. Volatile organic compounds and ammonia are not significant precursors to PM_{2.5}.
- (c) All areas of the State are classified as Class II, except the following areas, which are designated as Class I:
- (1) Great Smoky Mountains National Park;
 - (2) Joyce Kilmer Slickrock National Wilderness Area;
 - (3) Linville Gorge National Wilderness Area;
 - (4) Shining Rock National Wilderness Area; and
 - (5) Swanquarter National Wilderness Area.
- (d) Redesignations of areas to Class I or II may be submitted as state proposals to the Administrator of the Environmental Protection Agency (EPA) if the requirements of 40 CFR 51.166(g)(2) are met. Areas may be proposed to be redesignated as Class III if the requirements of 40 CFR 51.166(g)(3) are met. Redesignations may not, however, be proposed which would violate the restrictions of 40 CFR 51.166(e). Lands within the boundaries of Indian Reservations may be redesignated only by the appropriate Indian Governing Body.
- (e) In areas designated as Class I, II, or III, increases in pollutant concentration over the baseline concentration shall be limited to the values set forth in 40 CFR 51.166(c). However, concentration of the pollutant shall not exceed standards set forth in 40 CFR 51.166(d).
- (f) Concentrations attributable to the conditions described in 40 CFR 51.166(f)(1) shall be excluded in determining compliance with a maximum allowable increase. However, the exclusions referred to in 40 CFR 51.166(f)(1)(i) or (ii) shall be limited to five years as described in 40 CFR 51.166(f)(2).

(g) Major stationary sources and major modifications shall comply with the requirements contained in 40 CFR 51.166(a)(7) and (i) and in 40 CFR 51.166(j) through (o) and (w). The transition provisions allowed by 40 CFR 52.21(i)(11)(i) and (ii) and (m)(1)(vii) and (viii) are hereby adopted under this Regulation. The minimum requirements described in the portions of 40 CFR 51.166 referenced in this Paragraph are hereby adopted as the requirements under this Regulation, except as otherwise provided in this Regulation. Wherever the language of the portions of 40 CFR 51.166 referenced in this Paragraph speaks of the "plan," the requirements described therein shall apply to the source to which they pertain, except as otherwise provided in this Regulation. Whenever the portions of 40 CFR 51.166 referenced in this Paragraph provide that the State plan may exempt or not apply certain requirements in certain circumstances, those exemptions and provisions of nonapplicability are also hereby adopted under this Regulation. However, this provision shall not be interpreted so as to limit information that may be requested from the owner or operator by the Director as specified in 40 CFR 51.166(n)(2).

(h) New natural gas-fired electrical utility generating units for which cost recovery is sought pursuant to G.S. 62-133.6 shall install best available control technology for NO_x and SO₂, regardless of the applicability of the rest of this regulation.

(i) For the purpose of this Regulation, 40 CFR 51.166(w)(10)(iv)(a) shall read: "If the emissions level calculated in accordance with Paragraph (w)(6) of this Section is equal to or greater than 80 percent of the PAL level, the Director shall renew the PAL at the same level." 40 CFR 51.166(w)(10)(iv)(b) is not incorporated by reference.

(j) MCAPCO Regulation 1.5211 - "Applicability" Paragraphs (f) and (g) shall not be applicable to any source to which this Regulation applies. The owner or operator of the sources to which this Regulation applies shall apply for and receive a permit as required in MCAPCO Section 1.5200 - "Air Quality Permits" or MCAPCO Section 1.5500 - "Title V Procedures".

(k) When a particular source or modification becomes a major stationary source or major modification solely by virtue of a relaxation in any enforceable limitation which was established after August 7, 1980, on the capacity of the source or modification to emit a pollutant, such as a restriction on hours of operation, then the provisions of this Regulation shall apply to the source or modification as though construction had not yet begun on the source or modification.

(l) For the purpose of this Regulation, the provisions of 40 CFR 52.21(r)(2) regarding the period of validity of approval to construct are incorporated by reference except that the term "Administrator" shall be replaced with "Director".

(m) Volatile organic compounds exempted from coverage in 40 CFR 51.100(s) shall be exempted when calculating source applicability and control requirements under this Regulation.

(n) The degree of emission limitation required for control of any air pollutant under this Regulation shall not be affected by:

- (1) that amount of a stack height, not in existence before December 31, 1970, that exceeds

- good engineering practice; or
- (2) any other dispersion technique not implemented before December 31, 1970.

(o) A substitution or modification of a model as provided in 40 CFR 51.166(l) is subject to public comment procedures in accordance with the requirements of 40 CFR 51.102.

(p) Permits may be issued on the basis of innovative control technology as set forth in 40 CFR 51.166(s)(1) if the requirements of 40 CFR 51.166(s)(2) have been met, subject to the condition of 40 CFR 51.166(s)(3), and with the allowance set forth in 40 CFR 51.166(s)(4).

(q) If a source to which this Regulation applies impacts an area designated Class I by requirements of 40 CFR 51.166(e), notice to EPA shall be provided as set forth in 40 CFR 51.166(p)(1). If the Federal Land Manager presents a demonstration described in 40 CFR 51.166(p)(3) during the public comment period or public hearing to the Director and if the Director concurs with this demonstration, the permit application shall be denied. Permits may be issued on the basis that the requirements for variances as set forth in 40 CFR 51.166(p)(4), (p)(5) and (p)(7), or (p)(6) and (p)(7) have been satisfied.

(r) A permit application subject to this Regulation shall be processed in accordance with the procedures and requirements of 40 CFR 51.166(q). Within 30 days of receipt of the application, applicants shall be notified if the application is complete as to the initial information submitted. Commencement of construction before full prevention of significant deterioration approval is obtained shall constitute a violation of this Regulation.

(s) Approval of an application with regard to the requirements of this Regulation shall not relieve the owner or operator of the responsibility to comply with applicable provisions of other Regulations of this Ordinance or any other requirements under local, state, or federal law.

- (t) When a source or modification is subject to this Regulation the following procedures apply:
- (1) Notwithstanding any other provisions of this paragraph, the Director shall, no later than 60 days after receipt of an application, notify the Federal Land Manager with the U.S. Department of Interior and U.S. Department of Agriculture of an application from a source or modification subject to this Regulation;
 - (2) If a source or modification may affect visibility of a Class I area, the Director shall provide written notification to all affected Federal Land Managers within 30 days of receiving the permit application or within 30 days of receiving advance notification of an application. The notification shall be given at least 30 days prior to the publication of notice for public comment on the application. The notification shall include a copy of all information relevant to the permit application, including an analysis provided by the source of the potential impact of the proposed source on visibility;
 - (3) The Director shall consider any analysis concerning visibility impairment performed by the Federal Land Manager if the analysis is received within 30 days of notification. If the Director finds that the analysis of the Federal Land Manager fails to demonstrate that an adverse impact on visibility will result in the Class I area, the Director shall follow

the public hearing process described in 40 CFR 51.307(a)(3) on the application and include an explanation of the Director's decision or notice as to where the explanation can be obtained; and

- (4) The Director may require monitoring of visibility in or around any Class I area by the proposed new source or modification if the visibility impact analysis indicates possible visibility impairment, pursuant to 40 CFR 51.307.

(u) If the owner or operator of a source is using projected actual emissions to avoid applicability of prevention of significant deterioration requirements, the owner or operator shall notify the Director of the modification before beginning actual construction. The notification shall include:

- (1) a description of the project;
- (2) identification of sources whose emissions could be affected by the project;
- (3) the calculated projected actual emissions and an explanation of how the projected actual emissions were calculated, including identification of emissions excluded by 40 CFR 51.166(b)(40)(ii)(c);
- (4) the calculated baseline actual emissions and an explanation of how the baseline actual emissions were calculated; and
- (5) any netting calculations, if applicable.

If, upon reviewing the notification, the Director finds that the project will require a prevention of significant deterioration evaluation, the Director shall notify the owner or operator of his or her findings. The owner or operator shall not make the modification until a permit has been issued pursuant to this Regulation. If a permit revision is not required pursuant to this Regulation, the owner or operator shall maintain records of annual emissions in tons per year, on a calendar year basis related to the modifications, for 10 years following resumption of regular operations after the change if the project involves increasing the emissions unit's design capacity or its potential to emit the regulated NSR pollutant; otherwise, these records shall be maintained for five years following resumption of regular operations after the change. The owner or operator shall submit a report to the Director within 60 days after the end of each year during which these records must be generated. The report shall contain the items listed in 40 CFR 51.166(r)(6)(v)(a) through (c). The owner or operator shall make the information documented and maintained under this Paragraph available to the Director and the general public, pursuant to the requirements in 40 CFR 70.4(b)(3)(vii).

(v) Portions of the regulations in the Code of Federal Regulations (CFR) that are referred to in this Regulation are incorporated by reference unless a specific reference states otherwise. The version of the CFR incorporated in this Regulation, with respect to 40 CFR 51.166, is that as of July 1, 2014 at <https://www.gpo.gov/fdsys/pkg/CFR-2014-title40-vol2/pdf/CFR-2014-title40-vol2-sec51-166.pdf> and does not include any subsequent amendments or editions to the referenced material. The publication may be accessed free of charge.

State History Note:

Filed as a Temporary Amendment Eff. March 8, 1994, for a period of 180 days or until the permanent Regulation is effective, whichever is sooner;
Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3); 143-215.107(a)(5); 143-

215.107(a)(7); 143-215.108(b);

Eff. June 1, 1981;

Amended Eff. September 1, 2017; September 1, 2013, January 2, 2011; September 1, 2010
May 1, 2008; July 28, 2006; July 1, 1997; February 1, 1995; July 1, 1994; December 1,
1992; August 1, 1991.

MCAQ History Note:

Amended Eff. October 17, 2017; June 17, 2014

2.0531 SOURCES IN NONATTAINMENT AREAS

(a) The purpose of this Regulation, is to implement a program for the For the purpose of this Regulation the definitions contained in 40 CFR 51.165(a)(1) and 40 CFR 51.301 apply, except the definition of “baseline actual emissions.” For the purposes of this Regulation:

(1) **“Baseline actual emissions”** means the rate of emissions, in tons per year, of a regulated new source review (NSR) pollutant, as determined in accordance with Parts (A) through (C) of this Subparagraph:

(A) For an existing emissions unit, baseline actual emissions means the average rate, in tons per year, at which the emissions unit actually emitted the pollutant during any consecutive 24-month period selected by the owner or operator within the five year period immediately preceding the date that a complete permit application is received by the Department for a permit required under this Regulation. The Director of Mecklenburg County Air Quality (MCAQ) shall allow a different time period, not to exceed 10 years immediately preceding the date that a complete permit application is received by the Department, if the owner or operator demonstrates that it is more representative of normal source operation. For the purposes of determining baseline actual emissions, the following apply:

- (i) The average rate shall include fugitive emissions to the extent quantifiable, and emissions associated with startups, shutdowns, and malfunctions;
- (ii) The average rate shall be adjusted downward to exclude any non-compliant emissions that occurred while the source was operating above any emission limitation that was legally enforceable during the consecutive 24-month period;
- (iii) For an existing emission unit (other than an electric utility steam generating unit), the average rate shall be adjusted downward to exclude any emissions that would have exceeded an emission limitation with which the major stationary source must currently comply. However, if the State has taken credit in an attainment demonstration or maintenance plan consistent with the requirements of 40 CFR 51.165(a)(3)(ii)(G) for an emission limitation that is part of a maximum achievable control technology standard that the Administrator proposed or promulgated under Part 63 in Title 40 of the Code of Federal Regulations, the baseline

- actual emissions shall be adjusted to account for such emission reductions;
- (iv) For an electric utility steam generating unit, the average rate shall be adjusted downward to reflect any emissions reductions under G. S. 143-215.107D and for which cost recovery is sought pursuant to G. S. 62-133.6;
 - (v) For a regulated NSR pollutant, when a project involves multiple emissions units, only one consecutive 24-month period shall be used to determine the baseline actual emissions for all the emissions units being changed. A different consecutive 24-month period can be used for each regulated NSR pollutant; and
 - (vi) The average rate shall not be based on any consecutive 24-month period for which there is inadequate information for determining annual emissions, in tons per year, and for adjusting this amount if required by Subparts (ii) and (iii) of this Part;
- (B) For a new emissions unit, the baseline actual emissions for purposes of determining the emissions increase that will result from the initial construction and operation of such unit shall equal zero; and thereafter, for all other purposes, shall equal the unit's potential to emit; and
 - (C) For a plantwide applicability limit (PAL) for a stationary source, the baseline actual emissions shall be calculated for existing emissions units in accordance with the procedures contained in Part (A) of this Subparagraph, and for a new emissions unit in accordance with the procedures contained in Part (B) of this Subparagraph;
- (2) In the definition of “**net emissions increase**”, the reasonable period specified in 40 CFR 51.165(a)(1)(vi)(C)(1) is seven years; and
 - (3) Particulate matter PM_{2.5} significant levels in 40 CFR 51.165(a)(1)(x)(A) are incorporated by reference except as otherwise provided in this Regulation. Sulfur dioxide (SO₂) and nitrogen oxides (NO_x) are precursors to PM_{2.5} in all nonattainment areas. Volatile organic compounds and ammonia are not significant precursors to PM_{2.5}.
- (b) Redesignation to Attainment. If Mecklenburg County or any part of Mecklenburg County to which this Regulation applies is later designated in 40 CFR 81.334 as attainment all sources in that county subject to this Regulation before the redesignation date shall continue to comply with this Regulation.
- (c) Applicability. 40 CFR 51.165(a)(2) is incorporated by reference. This Regulation applies to areas designated as nonattainment in 40 CFR 81.334, including any subsequent amendments or editions
- (d) This Regulation is not applicable to:
- (1) Transportation Facilities regulated only under Section 2.0800 -“Transportation Facilities” and not under any other Regulation in this Article;
 - (2) emission of pollutants at the new major stationary source or major modification

located in the nonattainment area that are pollutants other than the pollutant or pollutants for which the area is nonattainment. (A major stationary source or major modification that is major for volatile organic compounds or nitrogen oxides is also major for ozone.);

- (3) emission of pollutants for which the source or modification is not major;
 - (4) a new source or modification that qualifies for exemption under the provision of 40 CFR 51.165(a)(4); and
 - (5) emission of compounds listed under 40 CFR 51.100(s) as having been determined to have negligible photochemical reactivity except carbon monoxide.
- (e) MCAPCO 1.5211 - “Applicability” Paragraphs (f) and (g) are not applicable to any source to which this Regulation applies. The owner or operator of the source shall apply for and receive a permit as required in MCAPCO Sections 1.5200 - “Air Quality Permits” or 1.5500 - “Title V Procedures”.
- (f) To issue a permit to a source to which this Regulation applies, the Director of MCAQ shall determine that the source will meet the following requirements:
- (1) The new major stationary source or major modification will emit the nonattainment pollutant at a rate no more than the lowest achievable emission rate;
 - (2) The owner or operator of the proposed new major stationary source or major modification has demonstrated that all major stationary sources in the State that are owned or operated by this person (or any entity controlling, controlled by, or under common control with this person) are subject to emission limitations and are in compliance, or on a schedule for compliance that is federally enforceable or contained in a court decree, with all applicable emission limitations and standards of this Article that EPA has authority to approve as elements of the North Carolina State Implementation Plan for Air Quality;
 - (3) The owner or operator of the proposed new major stationary source or major modification will obtain sufficient emission reductions of the nonattainment pollutant from other sources in the nonattainment area so that the emissions from the new major source and any associated new minor sources will be less than the emissions reductions by a ratio of at least 1.00 to 1.15 for volatile organic compounds and nitrogen oxides and by a ratio of lesser than one to one for carbon monoxide. The baseline for this emission offset shall be the actual emissions of the source from which offset credit is obtained. Emission reductions shall not include any reductions resulting from compliance (or scheduled compliance) with applicable Regulations in effect before the application. The difference between the emissions from the new major source and associated new minor sources of carbon monoxide and the emission reductions shall be sufficient to represent reasonable further progress toward attaining the National Ambient Air Quality Standards. The emissions reduction credits shall also conform to the provisions of 40 CFR 51.165(a)(3)(ii)(A) through (J); and
 - (4) The Mecklenburg County Portion of the North Carolina State Implementation Plan for Air Quality is being carried out for the nonattainment area in which the proposed

source is located.

- (g) New natural gas-fired electrical utility generating units for which cost recovery is sought pursuant to G.S. 62-133.6 shall install lowest achievable emission rate technology for NO_x and SO₂, regardless of the applicability of the rest of this Rule.
- (h) For the purpose of this Regulation, 40 CFR 51.165(f) is incorporated by reference except that 40 CFR 51.165(f)(10)(iv)(A) reads: “If the emissions level calculated in accordance with Paragraph (f)(6) of 40 CFR 51.165 is equal to or greater than 80 percent of the PAL level, the Director of MCAQ shall renew the PAL at the same level.” 40 CFR 51.165(f)(10)(iv)(B) is not incorporated by reference.
- (i) When a particular source or modification becomes a major stationary source or major modification solely by virtue of a relaxation in any enforceable limitation established after August 7, 1980, on the capacity of the source or modification to emit a pollutant, such as a restriction on hours of operation, then the provisions of this Regulation shall apply to the source or modification as though construction had not yet begun on the source or modification.
- (j) To issue a permit to a source of a nonattainment pollutant, the Director of MCAQ shall determine, in accordance with Section 173(a)(5) of the Clean Air Act and in addition to the other requirements of this Regulation, that an analysis (produced by the permit applicant) of alternative sites, sizes, production processes, and environmental control techniques for source demonstrates that the benefits of the source significantly outweigh the environmental and social costs imposed as a result of its location, construction, or modification.
- (k) For the purpose of this rule, the provisions of 40 CFR 52.21(r)(2) regarding the period of validity of approval to construct are incorporated by reference except the term “Administrator” is replaced with “Director.”
- (l) Approval of an application regarding the requirements of this Regulation does not relieve the owner or operator of the responsibility to comply with applicable provisions of other Regulations of this Ordinance and any other requirements under local, state, or federal law.
- (m) Except as provided in 40 CFR 52.28(c)(6), for a source or modification subject to this Regulation the following procedures shall be followed:
 - (1) Notwithstanding any other provisions of this paragraph, the Director shall, no later than 60 days after receipt of an application, notify the Federal Land Manager with the U.S. Department of Interior and U.S. Department of Agriculture of an application from a source or modification subject to this Regulation.
 - (2) The owner or operator of the source shall provide an analysis of the impairment to visibility that would occur because of the source or modification and general commercial, industrial and other growth associated with the source or modification;

- (3) When a source or modification may affect the visibility of a Class I area, the Director of MCAQ shall provide written notification to all affected Federal Land Managers within 30 days of receiving the permit application or within 30 days of receiving advance notification of an application. The notification shall be given at least 30 days before the publication of the notice for public comment on the application. The notification shall include a copy of all information relevant to the permit application, including an analysis provided by the source of the potential impact of the proposed source on visibility;
- (4) The Director of MCAQ shall consider any analysis concerning visibility impairment performed by the Federal Land Manager if the analysis is received within 30 days of notification. If the Director of MCAQ finds that the analysis of the Federal Land Manager fails to demonstrate to the Director's satisfaction that an adverse impact on visibility will result in the Class I area, the Director shall follow the public hearing process described in 40 CFR 51.307(a)(3) on the application and include an explanation of his the Director's decision or notice where the explanation can be obtained;;
- (5) The Director of MCAQ shall only issue permits to those sources whose emissions will be consistent with making reasonable progress, as defined in Section 169A of the Clean Air Act, toward the national goal of preventing any future, and remedying any existing, impairment of visibility in mandatory Class I areas when the impairment results from manmade air pollution. In making the decision to issue a permit, the Director of MCAQ shall consider the cost of compliance, the time necessary for compliance, the energy and nonair quality environmental impacts of compliance, and the useful life of the source; and
- (6) The Director of MCAQ may require monitoring of visibility in or around any Class I area by the proposed new source or modification when the visibility impact analysis indicates possible visibility impairment.

The requirements of this Paragraph do not apply to nonprofit health or nonprofit educational institutions.

- (n) If the owner or operator of a source is using projected actual emissions to avoid nonattainment new source review, the owner or operator shall notify the Director of MCAQ of the modification before beginning actual construction. The notification shall include:
 - (1) a description of project;
 - (2) identification of sources whose emissions could be affected by the project;
 - (3) the calculated projected actual emissions and an explanation of how the projected actual emissions were calculated, including identification of emissions excluded by 40 CFR 51.165(a)(1)(xxviii)(B)(3);
 - (4) the calculated baseline actual emissions and an explanation of how the baseline actual emissions were calculated, and
 - (5) any netting calculations, if applicable.

If upon reviewing the notification, the Director of MCAQ finds that the project will cause a nonattainment new source review evaluation, the Director of MCAQ shall notify the owner or operator of his or her findings. The owner or operator shall not make the modification until it

has received a permit issued pursuant to this Regulation. If a permit revision is not required pursuant to this Regulation, the owner or operator shall maintain records of annual emissions in tons per year, on a calendar year basis related to the modifications for 10 years, following resumption of regular operations after the change if the project involves increasing the emissions unit's design capacity or its potential to emit the regulated NSR pollutant; otherwise these records shall be maintained for five years following resumption of regular operations after the change. The owner or operator shall submit a report to the Director within 60 days after the end of each year during which these records must be generated. The report shall contain the items listed in 40 CFR 51.165(a)(6)(v)(A) through (C). The owner or operator shall make the information documented and maintained under this Paragraph available to the Director and the general public pursuant to the requirements in 40 CFR 70.4(b)(3)(viii).

- (o) The reference to the Code of Federal Regulations (CFR) in this Rule are incorporated by reference unless a specific reference states otherwise. Except for 40 CFR 81.334, the version of the CFR incorporated in this Regulation is that as of May 16, 2008 at <http://www.gpo.gov/fdsys/pkg/FR-2008-05-16/pdf/E8-10768.pdf> and does not include any subsequent amendments or editions to the referenced material. The publication may be accessed free of charge.

State History Note:

Filed as a Temporary Amendment Eff. March 8, 1994 for a period of 180 days or until the permanent Regulation is effective, whichever is sooner;

Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 143-215.108(b);

Eff. June 1, 1981;

Amended Eff. September 1, 2013, January 2, 2011; September 1, 2010; May 1, 2008; May 1, 2005; July 1, 1998; July 1, 1996; July 1, 1995; July 1, 1994; December 1, 1993; December 1, 1992.

MCAQ History Note:

Eff. June 17, 2014

2.0532 SOURCES CONTRIBUTING TO AN AMBIENT VIOLATION

(a) This Regulation applies to certain new major stationary sources and major modifications to which MCAPCO Regulation 2.0531 - "Sources in Non-Attainment Areas" does not apply and which would contribute to a violation of a national ambient air quality standard but which would not cause a new violation.

(b) For the purpose of this Regulation the definitions contained in Section II.A. of Appendix S of 40 CFR Part 51 shall apply.

(c) The Regulation is not applicable to:

- (1) Transportation Facilities regulated only under MCAPCO Section 2.0800 - "Transportation Facilities" and not under any other Regulation of this Article;
- (2) emission of pollutants for which the area in which the new or modified source is located is designated as nonattainment;
- (3) emission of pollutants for which the source or modification is not major;
- (4) emission of pollutants other than sulfur dioxide, total suspended particulates, nitrogen oxides, and carbon monoxide;
and
- (5) a new or modified source whose impact will increase not more than:
 - (A) 1.0 ug/m³ of SO₂ on an annual basis,
 - (B) 5 ug/m³ of SO₂ on a 24-hour basis,
 - (C) 25 ug/m³ of SO₂ on a 3-hour basis,
 - (D) 1.0 ug/m³ of total suspended particulates on an annual basis,
 - (E) 5 ug/m³ of total suspended particulates on a 24-hour basis,
 - (F) 1.0 ug/m³ of NO₂ on an annual basis,
 - (G) 0.5 mg/m³ of carbon monoxide on an 8-hour basis,
 - (H) 2 mg/m³ of carbon monoxide on a one-hour basis, at any locality that does not meet a national ambient air quality standard;
 - (I) 1.0 ug/m³ of PM-10 on an annual basis, or
 - (J) 5 ug/m³ of PM-10 on a 24-hour basis, at any locality that does not meet a national ambient air quality standard;
- (6) sources which are not major unless secondary emissions are included in calculating the potential to emit;
- (7) sources which are exempted by the provision in Section II.F. of Appendix S of 40 CFR Part 51;
- (8) temporary emission sources which will be relocated within two years; and
- (9) emissions resulting from the construction phase of the source.

(d) MCAPCO Regulation 1.5211 - "Applicability" Paragraphs (f) and (g) are not applicable to any source to which this Regulation applies. The owner or operator of the source shall apply for and receive a permit as required in MCAPCO Section 1.5200 - "Air Quality Permits" or 1.5500 - "Title V Procedures".

(e) To issue a permit to a new or modified source to which this Regulation applies, the Director

shall determine that the source will meet the following conditions:

- (1) The sources will emit the nonattainment pollutant at a rate no more than the lowest achievable emission rate.
- (2) The owner or operator of the proposed new or modified source has demonstrated that all major stationary sources in the State which are owned or operated by this person (or any entity controlling, controlled by, or under common control with this person) are subject to emission limitations and are in compliance, or on a schedule for compliance which is federally enforceable or contained in a court decree, with all applicable emission limitations and standards of this Article which EPA has authority to approve as elements of the Mecklenburg County Portion of the North Carolina State Implementation Plan for Air Quality.
- (3) The source will satisfy one of the following conditions:
 - (A) The source will comply with Subparagraph (e)(3) of MCAPCO Regulation 2.0531 - "Sources in Non-Attainment Areas" when the source is evaluated as if it were in the nonattainment area;
or
 - (B) The source will have an air quality offset, i.e., the applicant will have caused an air quality improvement in the locality where the national ambient air quality standard is not met by causing reductions in impacts of other sources greater than any additional impact caused by the source for which the application is being made. The emissions reductions creating the air quality offset shall be placed as a condition in the permit for the source reducing emissions. The requirements of this Part may be partially waived if the source is a resource recovery facility burning municipal solid waste, the source must switch fuels due to lack of adequate fuel supplies, or the source is required to be modified as a result of EPA regulations and no exemption from such regulations is available and if:
 - (i) the permit applicant demonstrates that it made its best efforts to obtain sufficient air quality offsets to comply with this Part;
 - (ii) the applicant has secured all available air quality offsets;
and
 - (iii) the applicant will continue to seek the necessary air quality offsets and apply them when they become available.

(f) At such time that a particular source or modification becomes a major stationary source or major modification solely by virtue of a relaxation in any enforceable limitation established after August 7, 1980, on the capacity of the source or modification to emit a pollutant, such as a restriction on hours of operation, then the provisions of this Regulation shall apply to the source or modification as though construction had not yet begun on the source or modification.

(g) The version of the Code of Federal Regulations incorporated in this Regulation is that as of January 1, 1989, and does not include any subsequent amendments or editions to the referenced material.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 143-215.108(b); 150B-21.6; Eff. June 1, 1981; Amended Eff. July 4, 1994; August 1, 1991; October 1, 1989; July 1, 1988; October 1, 1987; January 1, 1985; February 1, 1983.

2.0533 STACK HEIGHT

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“A stack in existence”** means that the owner or operator had:
 - (A) begun, or caused to begin, a continuous program of physical on-site construction of the stack;
 - or
 - (B) entered into binding agreements or contractual obligations, which could not be canceled or modified without substantial loss to the owner or operator, to undertake a program of construction of the stack to be completed in the time that is normally required to construct such a stack.
- (2) **“Dispersion technique”**
 - (A) **“Dispersion technique”** means any technique which attempts to affect the concentration of a pollutant in the ambient air by:
 - (i) using that portion of a stack which exceeds good engineering practice stack height,
 - (ii) varying the rate of emission of a pollutant according to atmospheric conditions or ambient concentrations of that pollutant,
 - or
 - (iii) increasing final exhaust gas plume rise by manipulating source process parameters, exhaust gas parameters, stack parameters, or combining exhaust gases from several existing stacks into one stack; or other selective handling of exhaust gas streams so as to increase the exhaust gas plume rise.
 - (B) **“Dispersion technique”** does not include:
 - (i) the reheating of a gas stream, following use of a pollution control system, for the purpose of returning the gas to the temperature at which it was originally discharged from the facility generating the gas stream;
 - (ii) the using of smoke management in agricultural or silvicultural prescribed burning programs;
 - (iii) the merging of exhaust gas streams where:
 - (I) The facility owner or operator demonstrates that the source was originally designed and constructed with such merged gas streams;
 - (II) After July 8, 1985, such merging is part of a change in operation at the facility that includes the installation of pollution controls and is accompanied by a net reduction in the allowable emissions of a pollutant. This exclusion from the definition of “dispersion

- techniques” shall apply only to the emission limitation for the pollutant affected by such change in operation; or
- (III) Before July 8, 1985, such merging was part of a change in operation at the source that included the installation of emissions control equipment or was carried out for sound economic or engineering reasons. Where there was an increase in the emission limitation or in the event that no emission limitation was in existence prior to the merging, an increase in the quantity of pollutants actually emitted prior to the merging, the Director shall presume that merging was significantly motivated by an intent to gain emissions credit for greater dispersion. Absent a demonstration by the source owner or operator that merging was not significantly motivated by such intent, the Director shall deny credit for the effects of such merging in calculating the allowable emissions for the source;
 - (iv) Episodic restrictions on residential woodburning and open burning or;
 - (v) Techniques under Subpart (A)(iii) of this Subparagraph which increase final exhaust gas plume rise where the resulting allowable emissions of sulfur dioxide from the facility do not exceed 5,000 tons per year.
- (3) **“Emission limitation”** means a requirement established by this Article that limits the quantity, rate, or concentration of emissions of air pollutants on a continuous basis, including any requirements that limit the level of opacity, prescribe equipment, set fuel specifications, or prescribe operation or maintenance procedures for a source to assure continuous emission reduction.
- (4) **“Excessive concentrations”** means, for the purpose of determining good engineering practice stack height under Part (4)(D) of this Paragraph:
- (A) for sources seeking credit for stack height exceeding that established under Part (4)(B) or (C) of this Paragraph, a maximum ground-level concentration due to emissions from a stack due in whole or part to downwash, wakes, and eddy effects produced by nearby structures or nearby terrain features which individually is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes, or eddy effects and which contributes to a total concentration due to emissions from all sources that is greater than an ambient air quality standard. For sources subject to MCAPCO Regulation 2.0530 - “Prevention of Significant Deterioration”, an excessive concentration alternatively means a maximum ground-level concentration due to emissions from a stack due in whole or part to downwash, wakes, or eddy effects produced by nearby structures or nearby terrain features which individually is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes, or eddy effects and greater than a prevention of significant deterioration increment. The allowable emission rate to be used in making demonstrations under this part shall be prescribed by the new source performance standard that is applicable to the source category unless the owner or operator demonstrates

that this emission rate is infeasible. Where such demonstrations are approved by the Director, an alternative emission rate shall be established in consultation with the source owner or operator;

- (B) for sources seeking credit after October 11, 1983, for increases in existing stack heights up to the heights established under Part (4)(B) or (C) of this Paragraph:
 - (i) a maximum ground-level concentration due in whole or part to downwash, wakes or eddy effects as provided in Part (A) of this Subparagraph, except that the emission rate specified by any applicable Regulation in this Article (or, in the absence of such a limit, the actual emission rate) shall be used,
 - or
 - (ii) the actual presence of a local nuisance (odor, visibility impairment, or pollutant concentration) caused by the existing stack, as determined by the Director; and
 - (C) for sources seeking credit after January 12, 1979, for a stack height determined under Part (4)(B) or (C) of this Paragraph where the Director requires the use of a field study or fluid model to verify GEP stack height, for sources seeking stack height credit after November 9, 1984 based on the aerodynamic influence of cooling towers, and for sources seeking stack height credit after December 31, 1970 based on the aerodynamic influence of structures not adequately represented by Part (4)(B) or (C) of this Paragraph, a maximum ground-level concentration due in whole or part to downwash, wakes, or eddy effects that is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes, or eddy effects.
- (5) **“Good engineering practice (GEP) stack height”** means the greater of:
- (A) 65 meters measured from the ground-level elevation at the base of the stack;
 - (B) 2.5 times the height of nearby structure(s) measured from the ground-level elevation at the base of the stack for stacks in existence on January 12, 1979 and for which the owner or operator had obtained all applicable permit or approvals required under the Mecklenburg County Air Pollution Control Ordinance, provided the owner or operator produces evidence that this equation was actually relied on in establishing an emission limitation;
 - (C) for stacks not covered under Part (B) of this Subparagraph, the height of nearby structure(s) measured from the ground-level elevation at the base of the stack plus 1.5 times the lesser dimension (height or projected width) of nearby structure(s) provided that the Director may require the use of a field study or fluid model to verify GEP stack height for the source;
 - or
 - (D) the height demonstrated by a fluid model or a field study approved by the Director, which ensures that the emissions from a stack do not result in excessive concentrations of any air pollutant as a result of atmospheric downwash, wakes, or eddy effects created by the source itself, nearby structures or nearby terrain features.

- (6) **“Nearby”** means, for a specific structure or terrain feature:
- (A) under Parts (4)(B) and (C) of this Paragraph, that distance up to five times the lesser of the height or the width dimension of a structure but not greater than one-half mile. The height of the structure is measured from the ground-level elevation at the base of the stack.
 - (B) under Part (4)(D) of this Paragraph, not greater than one-half mile, except that the portion of a terrain feature may be considered to be nearby which falls within a distance of up to 10 times the maximum height [H_t] of the feature, not to exceed two miles if such feature achieves a height [h_t] one-half mile from the stack that is at least 40 percent of the GEP stack height determined by Part (4)(C) of this Paragraph or 26 meters, whichever is greater, as measured from the ground-level elevation at the base of the stack. The height of the structure or terrain feature is measured from the ground-level elevation at the base of the stack.
- (7) **“Stack”** means any point in a source designed to emit solids, liquids, or gases into the air, including a pipe or duct but not including flares.

(b) With the exceptions stated in Paragraphs (c) and (d) of this Regulation, the degree of emission limitations required by any Regulation in this Article shall not be affected by:

- (1) that amount of a stack height that exceeds good engineering practice, or
- (2) any other dispersion technique.

(c) Paragraph (b) shall not apply to:

- (1) stack heights in existence or dispersion techniques implemented before December 31, 1970, except where pollutants are being emitted from such stacks or using such dispersion techniques by sources, as defined in Section 111(a)(3) of the Clean Air Act, which were constructed, or reconstructed, or for which major modifications, as defined in MCAPCO Regulations 2.0530 - “Prevention of Significant Deterioration” Paragraph (b) and 2.0531 - “Sources in Non-Attainment Areas” Paragraph (b) were carried out after December 31, 1970;
or
- (2) coal-fired steam electric generating units, subject to provisions of Section 118 of the federal Clean Air Act, which began operation before July 1, 1957, and whose stacks were constructed under a construction contract awarded before February 8, 1974. However, these exemptions shall not apply to a new stack that replaces a stack that is exempted by Subparagraphs (1) and (2) of this Paragraph. These exemptions shall not apply to a new source using a stack that is exempted by Subparagraphs (1) and (2) of this Paragraph.

(d) This Regulation shall not restrict the actual stack height of any source.

History Note: Statutory Authority G.S. 143-215.3(a)(1); Eff. November 1, 1982;
Amended Eff. July 1, 1994; July 1, 1987; April 1, 1986.

2.0535 EXCESS EMISSIONS REPORTING AND MALFUNCTIONS

(a) For this Regulation the following definitions apply:

- (1) **“Excess Emissions”** means an emission rate that exceeds any applicable emission limitation or standard allowed by any Regulation in MCAPCO Sections 1.5500 - “Title V Procedures”, 2.0900 - “Volatile Organic Compounds”, 2.1200 - “Control of Emissions from Incinerators”, or 2.1400 - “Nitrogen Oxides”; or by a permit condition; or that exceeds an emission limit established in a permit issued under MCAPCO Section 1.5700 - “Toxic Air Pollutant Procedures”.
- (2) **“Malfunction”** means any unavoidable failure of air pollution control equipment, process equipment, or process to operate in a normal and usual manner that results in excess emissions. Excess emissions during periods of routine start-up and shut-down of process equipment are not considered a malfunction. Failures caused entirely or in part by poor maintenance, careless operations or any other upset condition within the control of the emission source are not considered a malfunction.
- (3) **“Shut-down”** means the cessation of the operation of any source for any purpose.
- (4) **“Start-up”** means the commencement of operation of any source that has shut-down or ceased operation for a period sufficient to cause temperature, pressure, process, chemical, or a pollution control device imbalance that would result in excess emissions.

(b) This Regulation does not apply to sources to which MCAPCO Regulations 2.0524 - “New Source Performance Standards”, 2.1110 - “National Emission Standards for Hazardous Air Pollutants”, or 2.1111 - “Maximum Achievable Control Technology” applies unless excess emissions exceed an emission limit established in a permit issued under MCAPCO Section 1.5700 - “Toxic Air Pollutant Procedures” that is more stringent than the emission limit set by MCAPCO Regulations 2.0524 - “New Source Performance Standards”, 2.1110 - “National Emission Standards for Hazardous Air Pollutants”, or 2.1111 - “Maximum Achievable Control Technology”.

(c) Any excess emissions that do not occur during start-up or shut-down are considered a violation of the appropriate Regulation unless the owner or operator of the source of excess emissions demonstrates to the Director, that the excess emissions are the result of a malfunction. To determine if the excess emissions are the result of a malfunction, the Director shall consider, along with any other pertinent information, the following:

- (1) The air cleaning device, process equipment, or process has been maintained and operated, to the maximum extent practicable, consistent with good practice for minimizing emissions;
- (2) Repairs have been made expeditiously when the emission limits have been exceeded;
- (3) The amount and duration of the excess emissions, including any bypass, have been minimized to the maximum extent practicable;
- (4) All practical steps have been taken to minimize the impact of the excess emissions on ambient air quality;

- (5) The excess emissions are not part of a recurring pattern indicative of inadequate design, operation, or maintenance;
- (6) The requirements of Paragraph (f) of this Regulation have been met; and
- (7) If the source is required to have a malfunction abatement plan, it has followed that plan.

All malfunctions shall be repaired as expeditiously as practicable. However, the Director shall not excuse excess emissions caused by malfunctions from a source for more than 15 percent of the operating time during each calendar year. The Director may require the owner or operator of a facility to maintain records of the time that a source operates when it or its air pollution control equipment is malfunctioning or otherwise has excess emissions.

(d) All electric utility boiler units shall have a malfunction abatement plan approved by the Director as satisfying the requirements of Subparagraphs (1) through (3) of this Paragraph. In addition, the Director may require any other source to have a malfunction abatement plan approved by the Director as satisfying the requirements of Subparagraphs (1) through (3) of this Paragraph. If the Director requires a malfunction abatement plan for a source other than an electric utility boiler, the owner or operator of that source shall submit a malfunction abatement plan within 60 days after receipt of the Director's request. The malfunction plans of electric utility boiler units and of other sources required to have them shall be implemented when a malfunction or other breakdown occurs. The purpose of the malfunction abatement plan is to prevent, detect, and correct malfunctions or equipment failures that could result in excess emissions. A malfunction abatement plan shall contain:

- (1) a complete preventive maintenance program including:
 - (A) the identification of individuals or positions responsible for inspecting, maintaining and repairing air cleaning devices;
 - (B) a description of the items or conditions that will be inspected and maintained;
 - (C) the frequency of the inspection, maintenance services, and repairs; and
 - (D) an identification and quantities of the replacement parts that shall be maintained in inventory for quick replacement;
- (2) an identification of the source and air cleaning operating variables and outlet variables, such as opacity, grain loading, and pollutant concentration, that may be monitored to detect a malfunction or failure; the normal operating range of these variables and a description of the method of monitoring or surveillance procedures and of informing operating personnel of any malfunctions, including alarm systems, lights or other indicators; and
- (3) a description of the corrective procedures that the owner or operator will take in case of a malfunction or failure to achieve compliance with the applicable Regulation as expeditiously as practicable but no longer than the next boiler or process outage that would provide for an orderly repair or correction of the malfunction or 15 days, whichever is shorter. If the owner or operator anticipates that the malfunction would continue for more than 15 days, a case-by-case repair schedule shall be established by the Director with the source.

The owner or operator shall maintain logs to show that the operation and maintenance parts of the malfunction abatement plan are implemented. These logs are subject to inspection by the

Director or his designee upon request during business hours.

(e) The owner or operator of any source required by the Director to have a malfunction abatement plan shall submit a malfunction abatement plan to the Director within six months after it has been required by the Director. The malfunction abatement plan and any amendment to it shall be reviewed by the Director or his designee. If the plan carries out the objectives described by Paragraph (d) of this Regulation, the Director shall approve it. If the plan does not carry out the objectives described by Paragraph (d) of this Regulation, the Director shall disapprove the plan. The Director shall state his reasons for his disapproval. The person who submits the plan shall submit an amendment to the plan to satisfy the reasons for the Director's disapproval within 30 days of receipt of the Director's notification of disapproval. Any person having an approved malfunction abatement plan shall submit to the Director for his approval amendments reflecting changes in any element of the plan required by Paragraph (d) of this Regulation or amendments when requested by the Director. The malfunction abatement plan and amendments to it shall be implemented within 90 days upon receipt of written notice of approval.

(f) The owner or operator of a source of excess emissions that last for more than four hours and that results from a malfunction, a breakdown of process or control equipment or any other abnormal conditions, shall:

- (1) notify the Director or his designee of any such occurrence by 9:00 a.m. Eastern time of the Department's next business day after becoming aware of the occurrence and describe:
 - (A) name and location of the facility,
 - (B) the nature and cause of the malfunction or breakdown,
 - (C) the time when the malfunction or breakdown is first observed,
 - (D) the expected duration, and
 - (E) an estimated rate of emissions;
- (2) notify the Director or his designee immediately when the corrective measures have been accomplished;
- (3) submit to the Director within 15 days after the request a written report that includes:
 - (A) name and location of the facility,
 - (B) identification or description of the processes and control devices involved in the malfunction or breakdown,
 - (C) the cause and nature of the event,
 - (D) time and duration of the violation or the expected duration of the excess emission if the malfunction or breakdown has not been fixed,
 - (E) estimated quantity of pollutant emitted,
 - (F) steps taken to control the emissions and to prevent recurrences and if the malfunction or breakdown has not been fixed, steps planned to be taken, and
 - (G) any other pertinent information requested by the Director. After the malfunction or breakdown has been corrected, the Director may require the owner or operator of the source to test the source in accordance with Section 2.2600 of this Article to demonstrate compliance.

(g) Start-up and shut-down. Excess emissions during start-up and shut-down shall be considered a violation of the appropriate Regulation if the owner or operator cannot demonstrate that the excess emissions are unavoidable. To determine if excess emissions are unavoidable during startup or shutdown, the Director shall consider the items listed in Paragraphs (c)(1), (c)(3), (c)(4), (c)(5), and (c)(7) of this Regulation along with any other pertinent information. The Director may specify for a particular source the amount, time, and duration of emissions allowed during start-up or shut-down. The owner or operator shall, to the extent practicable, operate the source and any associated air pollution control equipment or monitoring equipment in a manner consistent with best practicable air pollution control practices to minimize emissions during start-up and shut-down.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(4); 143-215.107(a)(5);
Eff. March 1, 1983;
Amended Eff. June 1, 2008; April 1, 2001; July 1, 1998;
July 1, 1996; October 1, 1991; May 1, 1990; April 1, 1986.

2.0537 CONTROL OF MERCURY EMISSIONS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Mercury”** means the element mercury, excluding any associated elements, and includes mercury in particulates, vapors, aerosols, and compounds.
- (2) **“Stationary source”** means the total plant site. This includes all emissions (stacks, ducts, vents, openings, fugitives, etc.) to the atmosphere within the property boundary.

(b) This Regulation shall apply to all new and existing stationary sources engaged in the handling and/or processing of mercury and not subject to standards on emissions for mercury in MCAPCO Regulations 2.0530 - “Prevention of Significant Deterioration”, 2.1110 - “National Emission Standards for Hazardous Air Pollutants” or 2.1111 - “Maximum Achievable Control Technology”.

(c) An owner or operator of a stationary source engaged in the handling and/or processing of mercury shall not cause, allow, or permit particulate and/or gaseous mercury emissions in excess of 2300 grams per day into the outdoor atmosphere.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. June 1, 1985.

2.0538 CONTROL OF ETHYLENE OXIDE EMISSIONS

(a) For purposes of this Regulation, "medical devices" means instruments, apparatus, implements, machines, implants, in vitro reagents, contrivances, or other similar or related articles including their components, parts, and accessories, intended for use in the diagnosis, cure, mitigation, treatment, or prevention of disease in man or other animals; or intended to affect the structure or any function of the body of man or other animals.

(b) This Regulation applies to emissions of ethylene oxide resulting from use as a sterilant in:

- (1) the production and subsequent storage of medical devices; or
- (2) the packaging and subsequent storage of medical devices for sale;

from the processes described in Paragraph (d) of this Regulation for which construction of facilities began after August 31, 1992.

(c) This Regulation does not apply to hospital or medical facilities.

(d) Facilities subject to this Regulation shall comply with the following standards:

- (1) For sterilization chamber evacuation, a closed loop liquid ring vacuum pump, or equipment demonstrated to be as effective at reducing emissions of ethylene oxide shall be used;
- (2) For sterilizer exhaust, a reduction in the weight of uncontrolled emissions of ethylene oxide of at least 99.8 percent by weight shall be achieved;
- (3) For sterilizer unload and backdraft valve exhaust, a reduction:
 - (A) in uncontrolled emissions of ethylene oxide of at least 99 percent by weight shall be achieved;
 - or
 - (B) to no more than one part per million by volume of ethylene oxide shall be achieved.
- (4) Sterilized product ethylene oxide residual shall be reduced by:
 - (A) a heated degassing room to aerate the products after removal from the sterilization chamber; the temperature of the degassing room shall be maintained at a minimum of 95E Fahrenheit during the degassing cycle, and product hold time in the aeration room shall be at least 24 hours; or
 - (B) a process demonstrated to be as effective as Part (d)(4)(A) of this Regulation.
- (5) Emissions of ethylene oxide from the degassing area (or equivalent process) shall be vented to a control device capable of reducing uncontrolled ethylene oxide emissions by at least 99 percent by weight or to no more than one part per million by volume of ethylene oxide. The product aeration room and the product transfer area shall be maintained under a negative pressure.

(e) Before installation of the controls required by Paragraph (d) of this Regulation, and annually thereafter, a written description of waste reduction, elimination, or recycling plan shall be submitted [as specified in G.S. 143-215.108(g)] to determine if ethylene oxide use can be reduced or eliminated through alternative sterilization methods or process modifications.

(f) The owner or operator of the facility shall conduct a performance test to verify initial efficiency of the control devices. The owner or operator shall maintain temperature records to demonstrate proper operation of the degassing room. Such records shall be retained for a period of at least two calendar years and shall be made available for inspection by Department personnel.

(g) If the owner or operator of a facility subject to the Regulation demonstrates, using the procedures in MCPCO Regulation 2.1106 - "Determination of Ambient Air Concentrations", that the emissions of ethylene oxide from all sources at the facility do not cause the acceptable ambient level of ethylene oxide in MCAPCO Regulation 2.1104 - "Toxic Air Pollutant Guidelines" to be exceeded, then the requirements of Paragraphs (d) through (e) of this Regulation shall not apply. This demonstration shall be at the option of the owner or operator of the facility. If this option is chosen, the Director shall write the facility's permit to satisfy the requirements of MCAPCO Regulation 2.1104 - "Toxic Air Pollutant Guidelines" Paragraph (a).

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(4),(5); 143-215.108(c);
Eff. September 1, 1992;
Amended Eff. April 1, 2004; August 1, 2002.*

2.0539 ODOR CONTROL OF FEED INGREDIENT MANUFACTURING PLANTS

(a) Applicability. The requirements of this Regulation apply to any facility that produces feed-grade animal proteins or feed-grade animal fats and oils, but do not apply to any portions of such facilities that are engaged exclusively in the processing of food for human consumption.

(b) This Regulation does not apply to those facilities solely engaged in the processing of marine byproducts. Those facilities, however, shall continue to control their odorous emissions in accordance with MCAPCO Regulation 1.5110 - "Control and Prohibition of Odorous Emissions".

(c) A person shall not allow, cause, or permit the operation or use of any device, machine, equipment, or other contrivance to process material to be used in the production of feed-grade animal proteins or feed-grade animal fats and oils unless all gases, vapors, and gas-entrained effluents from these processes are passed through condensers to remove all steam and other condensable materials. All noncondensibles passing through the condensers shall then be incinerated at 1200 degrees Fahrenheit for a period of not less than 0.3 seconds, or treated in an equally effective manner.

(d) Measurement and Recording Requirements. Any person processing or incinerating gases, vapors, or gas-entrained matter as required by Paragraph (c) of this Regulation shall install, operate, and maintain in good working order and calibration continuous measuring and recording devices for equipment operational parameters to document equipment operation in accordance with this Regulation. In addition, the owner or operator of the facility shall:

- (1) demonstrate that the measuring and recording devices are capable of verifying the compliance status of the equipment on a continuous basis;
- (2) describe the parameters to be used to determine the compliance status and how these

parameters:

- (A) are to be measured,
 - (B) are to be used to determine compliance status; and
- (3) provide a quality assurance program approved by the Director for all monitoring devices and systems that includes:
- (A) procedures and frequencies for calibration,
 - (B) standards traceability,
 - (C) operational checks,
 - (D) maintenance schedules and procedures,
 - (E) auditing schedules and procedures,
 - (F) data validation,
 - and
 - (G) schedule for implementing the quality assurance program.

These data shall be available to the Director upon request.

(e) A person shall not allow, cause, or permit the installation or operation of expeller units unless they are properly hooded and all exhaust gases are collected or ducted to odor control equipment.

(f) A person subject to this Regulation shall not cause or permit any raw material to be handled, transported, or stored, or to undertake the preparation of any raw material without taking reasonable precautions to prevent odors from being discharged. For the purpose of this Regulation, such raw material is in "storage" after it has been unloaded at a facility or after it has been located at the facility for at least 24 hours. Reasonable precautions shall include the following:

- (1) storage of all raw material before or in the process of preparation, in properly enclosed and vented equipment or areas, together with the use of effective devices and methods to prevent the discharge of odor bearing gases;
- (2) use of covered vehicles or containers of watertight construction for the handling and transporting of any raw material; and
- (3) use of hoods and fans to enclose and vent the storage, handling, preparation, and conveying of any odorous materials together with effective devices or methods, or both, to prevent emissions of odors or odor bearing gases.

(g) The owner or operator shall notify MCAQ within two business days after conditions are encountered that cause or may cause release of excessive and malodorous gases or vapors.

(h) Compliance Schedule. The owner or operator of a facility subject to this Regulation that begins construction or is in operation before July 1, 1996, shall adhere to the following increments of progress and schedules:

- (1) documentation that the facility complies with this Regulation or an air permit application containing plans to bring the facility into compliance and a schedule shall be submitted by January 1, 1997;
- (2) the compliance schedule shall contain the following increments of progress:
 - (A) a date by which contracts for the emission control system and process

equipment shall be awarded or orders shall be issued for purchase of component parts;

- (B) a date by which on-site construction or installation of the emission control and process equipment shall begin;
 - (C) a date by which on-site construction or installation of the emission control and process equipment shall be completed;
and
 - (D) a date by which final compliance shall be achieved.
- (3) The final compliance date under Subparagraph (2)(D) of this Paragraph shall be no later than July 1, 2001.

The owner or operator shall certify to the Director within five days after the deadline, for each increment of progress, whether the required increment of progress has been met.

(i) The owner or operator of a facility that begins construction after June 30, 1996, shall be in compliance with this Regulation before beginning operation.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.66; 143-215.107
(a)(5);
Eff. July 1, 1996.

2.0540 PARTICULATES FROM FUGITIVE DUST EMISSION SOURCES

(a) For the purpose of this Regulation the following definitions apply:

- (1) **“Excess fugitive dust emissions”** means:
 - (A) Fugitive dust is visible extending beyond the facility’s property line, or
 - (B) Upon inspection of settled dust on adjacent property, the Division finds that the dust came from the adjacent facility.
- (2) **“Fugitive dust emission”** means particulate matter that does not pass through a process stack or vent and that is generated within plant property boundaries from activities such as as unloading and loading areas, process areas, stockpiles, stock pile working, plant parking lots, and plant roads (including access roads and haul roads).
- (3) **“Production of crops”** means:
 - (A) cultivation of land for crop planting;
 - (B) crop irrigation;
 - (C) harvesting;
 - (D) on site curing, storage, or preparation of crops; or
 - (E) protecting them from damage or disease conducted in according to practices acceptable to the North Carolina Department of Agriculture and Consumer Services.
- (4) **“Public parking”** means an area dedicated to or maintained for the parking of vehicles by the general public.
- (5) **“Public road”** means any road that is part of the State highway system or any road, street, or right-of-way dedicated or maintained for public use.
- (6) **“Substantive complaints”** means complaints that are verified with physical evidence.

(b) This Rule does not apply to:

- (1) abrasive blasting covered under MCAPCO Regulation 2.0541 – “Control of Emissions from Abrasive Blasting”,
- (2) non-production military base operations,
- (3) land disturbing activities, such as clearing, grading, or digging, and related activities such as hauling fill and cut material, building material, or equipment, or
- (4) public roads, public parking, timber harvesting, or production of crops.

(c) The owner or operator of a facility required to have a permit under Article I of this Ordinance or of a source subject to a requirement under Article II of this Ordinance shall not cause or allow fugitive dust emissions to cause or contribute to substantive complaints, or visible emissions in excess of that allowed under Paragraph (e) of this Regulation.

(d) If fugitive dust emissions from a facility required to comply with this Regulation cause or contribute to substantive complaints, the owner or operator of the facility shall:

- (1) within 30 days upon receipt of written notification from the Director of a second substantive complaint in a 12-month period, submit to the Director a written report that includes the identification of the probable source(s) of the fugitive dust emissions causing complaints and what measures can be made to abate the fugitive emissions.
- (2) within 60 days of the initial report submitted under Subparagraph (1) of this

Paragraph, submit to the Director a control plan as described in Paragraph (f) of this Regulation; and

- (3) within 30 days after the Director approves the plan, be in compliance with the plan.

(e) If there is sufficient environmental benefit to justify a fugitive dust control plan, the Director shall require that the owner or operator of a facility covered by Paragraph (c) of this Regulation, develop and submit a fugitive dust control plan as described in Paragraph (f) of this Regulation if:

- (1) ambient air quality measurements or dispersion modeling as provided in Paragraph (e) of MCAPCO Regulation 2.1106 – “Determination of Ambient Air Concentrations” show violation or a potential for a violation of an ambient air quality standard for particulates in MCAPCO Section 2.0400 - “Ambient Air Quality Standards”, or
- (2) the Department observes excessive fugitive dust emissions from the facility beyond the property boundaries for six minutes in any one hour using Reference Method 22 in 40 CFR 60, Appendix A.

(f) The fugitive dust control plan shall:

- (1) identify the sources of fugitive dust emissions within the facility;
- (2) describe how fugitive dust will be controlled from each identified source;
- (3) contain a schedule by which the plan will be implemented;
- (4) describe how the plan will be implemented, including training of facility personnel; and
- (5) describe methods to verify compliance with the plan.

(g) The Director shall approve the plan if he finds that:

- (1) the plan contains all required elements in Paragraph (f) of this Regulation;
- (2) the proposed schedule contained in the plan will reduce fugitive dust emissions in a timely manner;
- (3) the methods used to control fugitive dust emissions are sufficient to prevent fugitive dust emissions from causing or contributing to a violation of the ambient air quality standards for particulates; and
- (4) the described compliance verification methods are sufficient to verify compliance with the plan.

If the Director finds that the proposed plan does not meet the requirements of this Paragraph he shall notify the owner or operator of the facility of any deficiencies in the proposed plan. The owner or operator shall have 30 days after receiving written notification from the Director to correct the deficiencies or submit a schedule describing actions to be taken and the time by which they will be implemented.

(h) If after a plan has been implemented, the Director finds that the plan inadequately controls fugitive dust emissions, he shall require the owner or operator of the facility to correct the deficiencies in the plan. Within 90 days after receiving written notification from the Director identifying the deficiency, the owner or operator of the facility shall submit a revision to his plan to correct the deficiencies.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 143-215.108(c)(7);
Eff. July 1, 1998;
Amended Eff. January 1, 2010; September 1, 2007*

2.0541 CONTROL OF EMISSIONS FROM ABRASIVE BLASTING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Abrasives”** means any material used in abrasive blasting operations.
- (2) **“Abrasive blasting”** means the operation of cleaning or preparing a surface by forcibly propelling a stream of abrasive material against the surface. Sandblasting is one form of abrasive blasting.
- (3) **“Abrasive blasting equipment”** means any equipment used in abrasive blasting operations.
- (4) **“Fugitive dust emissions”** means emissions of particulate matter into the outdoor atmosphere that is not vented or captured by a stack or chimney.
- (5) **“Building”** means a structure with four or more sides and a roof that is used, in whole or in part, to house or contain abrasive blasting.

(b) The owner or operator shall ensure that any abrasive blasting operation conducted outside a building or conducted indoors and vented to the atmosphere is performed in accordance with the requirements set forth in MCAPCO Regulation 1.5107 - “Control and Prohibition of Visible Emissions”. For the purposes of this Regulation, the visible emissions reading for abrasive blasting performed outside a building shall be taken at a spot approximately one meter above the point of abrasive blasting with a viewing distance of approximately five meters.

(c) Except as provided in Paragraph (d) of this Regulation, all abrasive blasting operations shall be conducted within a building.

(d) An abrasive blasting operation conducted under one or more of the following conditions is not required to be conducted within a building:

- (1) when the item to be blasted exceeds eight feet in any dimension,
- (2) when the surface being blasted is situated at its permanent location or not further away from its permanent location than is necessary to allow the surface to be blasted, or
- (3) when the abrasive blasting operation is conducted at a private residence or farm and the visible emissions created by this abrasive blasting operation do not migrate beyond the property boundary of the private residence or farm on which the abrasive blasting operation is being conducted.

(e) The owner or operator of any abrasive blasting operation conducted in accordance with Subparagraphs (d)(1) and (d)(2) of this Regulation, outside a building, shall take appropriate measures to ensure that the fugitive dust emissions created by the abrasive blasting operation do not migrate beyond the property boundaries in which the abrasive blasting operation is being conducted. Appropriate measures include the following:

- (1) the addition of a suppressant to the abrasive blasting material,
- (2) wet abrasive blasting,
- (3) hydroblasting,
- (4) vacuum blasting,
- (5) shrouded blasting, or
- (6) shrouded hydroblasting.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.108(c)(7); 143-215.108(d)(1);
Eff. July 1, 2000.

2.0543 BEST AVAILABLE RETROFIT TECHNOLOGY

- (a) For the purposes of this Regulation, the definitions at 40 CFR 51.301 shall apply.
- (b) Mandatory Class I Federal areas are identified in 40 CFR Part 81, Subpart D.
- (c) The Director shall have the maximum flexibility allowed under 40 CFR 51.308 or 40 CFR Part 51, Appendix Y.
- (d) This Regulation applies to BART-eligible sources as determined using 40 CFR Part 51, Appendix Y that cause or contribute to any visibility impairment in a mandatory Class I Federal area as determined by using 40 CFR Part 51, Subpart P.
- (e) Unless exempted under 40 CFR 51.303, the owner or operator of a BART-eligible emission unit subject to this Regulation shall perform a best available retrofit technology (BART) evaluation for that emission unit. Pursuant to 40 CFR 51.308, the evaluation shall include:
 - (1) the technology available,
 - (2) the cost of compliance,
 - (3) the energy and non-air quality environmental impacts of compliance,
 - (4) any pollution control equipment in use at source,
 - (5) the remaining useful life of the source, and
 - (6) the degree of improvement in visibility that may reasonably be anticipated to result from the use of such technology.
- (f) The owner or operator of a BART-subject emission unit shall install, operate, and maintain BART as approved by the Director after considering the six items listed in Paragraph (e) of this Regulation and incorporated in the unit's permit issued under Article 1 of this Ordinance.
- (g) The owner or operators of a BART-eligible source required to install BART under this Regulation shall submit permit applications for the installation and operation of BART by September 1, 2006. The Director shall extend the deadline for submitting a permit application if additional time is needed to complete the evaluation required under Paragraph (e) of this

Regulation.

(h) BART shall be determined using “Guidelines for Determining Best Available Retrofit Technology for Coal-fired Power Plants and Other Existing Stationary Facilities” (1980), 40 CFR 51.308(e)(1)(ii), and 40 CFR Part 51, Appendix Y. Electric generating units covered under and complying with MCAPCO Section 2.2400 – “Clean Air Interstate Rule”, are considered to be in compliance with the BART requirements for nitrogen oxides and sulfur dioxide under this Regulation.

(i) The owner or operator of a BART-eligible source required to install BART under this Regulation shall have installed and begun operation of the BART controls by December 31, 2012.

(j) “Guidelines for Determining Best Available Retrofit Technology for Coal-fired Power Plants and Other Existing Stationary Facilities” is incorporated by reference, exclusive of appendix E, and shall include any later amendments or editions. This document, which was published in the Federal Register on February 6, 1980 (45 FR 8210), is EPA publication No. 450/3–80–009b and can be obtained from the U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, Virginia 22161 for \$84.00. It is also available for inspection at the National Archives and Records Administration (NARA). Information on the availability of this material at NARA may be found at:

http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

History Note: Authority G.S.143-215.3(a)(1); 143-215.107(a)(5), (10)
Eff. September 1, 2006.
Amended Eff. May 1, 2007.

2.0544 PREVENTION OF SIGNIFICANT DETERIORATION REQUIREMENTS FOR GREENHOUSE GASES

(a) The purpose of this Regulation is to implement a program for the prevention of significant deterioration of air quality for greenhouse gases as required by 40 CFR 51.166. For purposes of greenhouse gases, the provisions of this Regulation shall apply rather than the provisions of MCAPCO Regulation 2.0530 – “Prevention Of Significant Deterioration”. A major stationary source or major modification shall not be required to obtain a prevention of significant deterioration (PSD) permit on the sole basis of its greenhouse gas emissions. For all other regulated NSR pollutants, the provisions of MCAPCO Regulation 2.0530 of this apply.

(b) For the purposes of this Regulation, the definitions contained in 40 CFR 51.166(b) and 40 CFR 51.301 shall apply except the definition of "baseline actual emissions." "Baseline actual emissions" means the rate of emissions, in tons per year, of a regulated new source review (NSR) pollutant, as determined in accordance with Subparagraphs (1) through (3) of this Paragraph:

(1) For an existing emissions unit, baseline actual emissions means the average rate, in tons

per year, at which the emissions unit actually emitted the pollutant during any consecutive 24-month period selected by the owner or operator within the 5-year period preceding the date that a complete permit application is received by the Department for a permit required under this Regulation. The Director shall allow a different time period, not to exceed 10 years preceding the date that a complete permit application is received by the Department, if the owner or operator demonstrates that it is more representative of normal source operation. For the purpose of determining baseline actual emissions, the following shall apply:

- (A) The average rate shall include fugitive emissions to the extent quantifiable, and emissions associated with startups, shutdowns, and malfunctions;
 - (B) The average rate shall be adjusted downward to exclude any non-compliant emissions that occurred while the source was operating above any emission limitation that was legally enforceable during the consecutive 24-month period;
 - (C) For an existing emission unit (other than an electric utility steam generating unit), the average rate shall be adjusted downward to exclude any emissions that would have exceeded an emission limitation with which the major stationary source shall currently comply. However, if the State has taken credit in an attainment demonstration or maintenance plan consistent with the requirements of 40 CFR 51.165(a)(3)(ii)(G) for an emission limitation that is part of a maximum achievable control technology standard that the Administrator proposed or promulgated under part 63 of the Code of Federal Regulations, the baseline actual emissions shall be adjusted to account for such emission reductions;
 - (D) For an electric utility steam generating unit, the average rate shall be adjusted downward to reflect any emissions reductions under G. S. 143-215.107D and for which cost recovery is sought pursuant to G. S. 62-133.6;
 - (E) For a regulated NSR pollutant, when a project involves multiple emissions units, only one consecutive 24-month period shall be used to determine the baseline actual emissions for all the emissions units being changed. A different consecutive 24-month period for each regulated NSR pollutant can be used for each regulated NSR pollutant; and
 - (F) The average rate shall not be based on any consecutive 24-month period for which there is inadequate information for determining annual emissions, in tons per year, and for adjusting this amount if required by Parts (B) and (C) of this Subparagraph.
- (2) For a new emissions unit, the baseline actual emissions for purposes of determining the emissions increase that will result from the initial construction and operation of such unit shall equal zero; and thereafter, for all other purposes, shall equal the unit's potential to emit.
- (3) For a plantwide applicability limit (PAL) for a stationary source, the baseline actual emissions shall be calculated for existing emissions units in accordance with the procedures contained in Subparagraph (1) of this Paragraph and for a new emissions unit in accordance with the procedures contained in Subparagraph (2) of this Paragraph.

(c) In the definition of "net emissions increase," the reasonable period specified in 40 CFR 51.166(b)(3)(ii) shall be seven years.

(d) In the definition of “subject to regulation”, a greenhouse gas’s global warming potential is the global warming potential published at Table A-1 of Subpart A of 40 CFR Part 98 and shall include subsequent amendments and additions.

(e) The limitation specified in 40 CFR 51.166(b)(15)(ii) shall not apply.

(f) Major stationary sources and major modifications shall comply with the requirements contained in 40 CFR 51.166(i) and (a)(7) and by extension in 40 CFR 51.166(j) through (o) and (w). The transition provisions allowed by 40 CFR 52.21 (i)(11)(i) and (ii) and (m)(1)(vii) and (viii) are hereby adopted under this Regulation. The minimum requirements described in the portions of 40 CFR 51.166 referenced in this Paragraph are hereby adopted as the requirements to be used under this Regulation, except as otherwise provided in this Regulation. Wherever the language of the portions of 40 CFR 51.166 referenced in this Paragraph speaks of the "plan," the requirements described therein shall apply to the source to which they pertain, except as otherwise provided in this Regulation. Whenever the portions of 40 CFR 51.166 referenced in this Paragraph provide that the State plan may exempt or not apply certain requirements in certain circumstances, those exemptions and provisions of nonapplicability are also hereby adopted under this Regulation. However, this provision shall not be interpreted so as to limit information that may be requested from the owner or operator by the Director as specified in 40 CFR 26 51.166(n)(2).

(g) 40 CFR 51.166(w)(10)(iv)(a) is changed to read: "If the emissions level calculated in accordance with Paragraph (w)(6) of this Section is equal to or greater than 80 percent of the PAL [plant wide applicability limit] level, the Director shall renew the PAL at the same level." 40 CFR 51.166(w)(10)(iv)(b) is not incorporated by reference.

(h) 15A NCAC 02Q .0102 and .0302 are not applicable to any source to which this Regulation applies. The owner or operator of the sources to which this Regulation applies shall apply for and receive a permit as required in MCAPCO Sections 1.5200 – “Air Quality Permits” or 1.5500 – “Title V Procedures”.

(i) When a particular source or modification becomes a major stationary source or major modification solely by virtue of a relaxation in any enforceable limitation that was established after August 7, 1980, on the capacity of the source or modification to emit a pollutant, such as a restriction on hours of operation, then the provisions of this Regulation shall apply to the source or modification as though construction had not yet begun on the source or modification.

(j) The provisions of 40 CFR 52.21(r)(2) regarding the period of validity of approval to construct are incorporated by reference except that the term "Administrator" is replaced with "Director".

(k) Permits may be issued based on innovative control technology as set forth in 40 CFR 51.166(s)(1) if the requirements of 40 CFR 51.166(s)(2) have been met, subject to the condition

of 40 CFR 51.166(s)(3), and with the allowance set forth in 40 CFR 51.166(s)(4).

(l) A permit application subject to this Regulation shall be processed in accordance with the procedures and requirements of 40 CFR 51.166(q). Within 30 days of receipt of the application, applicants shall be notified if the application is complete as to initial information submitted. Commencement of construction before full prevention of significant deterioration approval is obtained constitutes a violation of this Regulation.

(m) Approval of an application with regard to the requirements of this Regulation shall not relieve the owner or operator of the responsibility to comply fully with applicable provisions of other Regulations of this Ordinance and any other requirements under local, state, or federal law.

(n) If the owner or operator of a source is using projected actual emissions to avoid applicability of prevention of significant deterioration requirements, the owner or operator shall notify the Director of the modification before beginning actual construction. The notification shall include:

- (1) a description of the project;
- (2) identification of sources whose emissions could be affected by the project;
- (3) the calculated projected actual emissions and an explanation of how the projected actual emissions were calculated, including identification of emissions excluded by 40 CFR 51.166(b)(40)(ii)(c);
- (4) the calculated baseline actual emissions and an explanation of how the baseline actual emissions were calculated; and
- (5) any netting calculations, if applicable.

If upon reviewing the notification, the Director finds that the project will cause a prevention of significant deterioration evaluation, then the Director shall notify the owner or operator of his or her findings. The owner or operator shall not make the modification until it has received a permit issued pursuant to this Regulation. If a permit revision is not required pursuant to this Regulation, the owner or operator shall maintain records of annual emissions in tons per year, on a calendar year basis related to the modifications for 10 years following resumption of regular operations after the change if the project involves increasing the emissions unit's design capacity or its potential to emit the regulated NSR pollutant; otherwise these records shall be maintained for five years following resumption of regular operations after the change. The owner or operator shall submit a report to the Director within 60 days after the end of each year during which these records must be generated. The report shall contain the items listed in 40 CFR 51.166(r)(6)(v)(a) through (c). The owner or operator shall make the information documented and maintained under this Paragraph available to the Director or the general public pursuant to the requirements in 40 CFR 70.4(b)(3)(viii).

~~(n)~~(o) The references to the Code of Federal Regulations (CFR) in this Regulation are incorporated by reference unless a specific reference states otherwise. The version of the CFR incorporated in this Regulation is that published in the Federal Register July 20, 2011 as set forth here: <http://www.gpo.gov/fdsys/pkg/CFR-2011-title40-vol2-sec51-166.pdf>, <http://www.gpo.gov/fdsys/pkg/CFR-2011-title40-vol3-sec52-21.pdf>, and with the amendment set forth on 76 FR 43507: <http://www.gpo.gov/fdsys/pkg/FR-2011-07-20/pdf/2011-17256.pdf> and

does not include any subsequent amendments or editions to the referenced material. This Regulation is applicable as of its effective date in accordance with 40 CFR 51.166(b)(48) and (b)(49)(iv) and (v).

State History Note:

*Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3); 143-215.107(a)(5); 143-215.107(a)(7); 143-215.108(b); 150B-21.6;
Eff. January 28, 2011 pursuant to E.O. 81, Beverly E. Perdue
Amended Eff. September 1, 2015, July 1, 2012*

MCAQ History Note:

Amended Eff. December 15, 2015