

TABLE OF CONTENTS

ARTICLE 2.0000 AIR POLLUTION CONTROL REGULATIONS AND PROCEDURES

Section 2.0900 Volatile Organic Compounds

2.0901	Definitions.....	209-01
2.0902	Applicability	209-03
2.0903	Recordkeeping: Reporting: Monitoring.....	209-05
2.0904	<i>Malfunctions: Breakdowns: Upsets (Repealed by State Prior to Local Adoption)</i>	209-07
2.0905	<i>Petition for Alternative Controls (Repealed by State Prior to Local Adoption)</i>	209-07
2.0906	Circumvention.....	209-08
2.0907	<i>Compliance Schedules for Sources in Nonattainment Areas. (Repealed)</i>	209-08
2.0908	<i>Equipment Modification Compliance Schedules (Repealed by State Prior to Local Adoption)</i>	209-08
2.0909	Compliance Schedules For Sources in New Nonattainment Areas	209-08
2.0910	<i>Alternative Compliance Schedules (Repealed)</i>	209-12
2.0911	<i>Exception from Compliance Schedules (Repealed)</i>	209-12
2.0912	General Provisions on Test Methods and Procedures.....	209-12
2.0913	<i>Determination of Volatile Content of Surface Coatings (Repealed)</i>	209-13
2.0914	<i>Determination of VOC Emission Control System Efficiency (Repealed)</i> ..	209-13
2.0915	<i>Determination of Solvent Metal Cleaning VOC Emissions (Repealed)</i>	209-13
2.0916	<i>Determination: VOC Em. from Bulk Gasoline Terminals (Repealed)</i>	209-13
2.0917	<i>Automobile and Light-Duty Truck Manufacturing (Repealed)</i>	209-14
2.0918	Can Coating.	209-14
2.0919	Coil Coating.....	209-15
2.0920	<i>Paper Coating (Repealed)</i>	209-16
2.0921	<i>Fabric and Vinyl Coating (Repealed)</i>	209-16
2.0922	Metal Furniture Coating.....	209-16
2.0923	Surface Coating of Large Appliances	209-17
2.0924	Magnet Wire Coating.....	209-18
2.0925	Petroleum Liquid Storage in Fixed Roof Tanks	209-19
2.0926	Bulk Gasoline Plants.....	209-21
2.0927	Bulk Gasoline Terminals	209-24
2.0928	Gasoline Service Stations Stage I	209-28
2.0929	<i>Petroleum Refinery Sources (Repealed)</i>	209-31
2.0930	Solvent Metal Cleaning.....	209-31
2.0931	Cutback Asphalt.....	209-35
2.0932	Gasoline Truck Tanks and Vapor Collection Systems	209-36
2.0933	Petroleum Liquid Storage in External Floating Roof Tanks	209-39
2.0934	<i>Coating of Miscellaneous Metal Parts and Products (Repealed)</i>	209-41
2.0935	Factory Surface Coating of Flat Wood Paneling	209-41
2.0936	<i>Graphic Arts (Repealed)</i>	209-42
2.0937	Manufacture of Pneumatic Rubber Tires.....	209-43
2.0938	<i>Perchloroethylene Dry Cleaning System (Repealed)</i>	209-44

2.0939	<i>Determination of Volatile Organic Compound Emissions (Repealed)</i>	209-44
2.0940	<i>Determination of Leak Tightness and Vapor Leaks (Repealed)</i>	209-44
2.0941	<i>Alternative Method for Leak Tightness (Repealed)</i>	209-44
2.0942	<i>Determination of Solvent in Filter Waste (Repealed)</i>	209-44
2.0943	Synthetic Organic Chemical and Polymer Manufacturing	209-45
2.0944	Manufacture of Polyethylene, Polypropylene and Polystyrene	209-47
2.0945	Petroleum Dry Cleaning	209-49
2.0946	<i>Compliance Schedule: Gasoline Handling (Repealed)</i>	209-51
2.0947	Manufacture of Synthesized Pharmaceutical Products.....	209-51
2.0948	VOC Emissions from Transfer Operations.....	209-53
2.0949	Storage of Miscellaneous Volatile Organic Compounds.....	209-53
2.0950	<i>Interim Standards for Certain Source Categories (Repealed)</i>	209-54
2.0951	RACT for Sources of Volatile Organic Compounds.....	209-54
2.0952	Petition for Alternative Controls for RACT	209-55
2.0953	<i>Vapor Return Piping for Stage II Vapor Recovery (Repealed)</i>	209-57
2.0954	<i>Stage II Vapor Recovery (Repealed)</i>	209-57
2.0955	Thread Bonding Manufacturing.....	209-57
2.0956	Glass Christmas Ornament Manufacturing.....	209-58
2.0957	Commercial Bakeries.....	209-59
2.0958	Work Practices for Sources of Volatile Organic Compounds	209-60
2.0959	Petition for Superior Alternative Controls	209-61
2.0961	Offset Lithographic Printing and Letterpress Printing.....	209-63
2.0962	Industrial Cleaning Solvents	209-67
2.0963	Fiberglass Boat Manufacturing Materials.....	209-69
2.0964	Miscellaneous Industrial Adhesives	209-75
2.0965	Flexible Package Printing	209-78
2.0966	Paper, Film and Foil Coatings	209-80
2.0967	Miscellaneous Metal and Plastic Parts Coatings	209-81
2.0968	Automobile and Light Duty Truck Assembly Coatings	209-88

SECTION 2.0900 VOLATILE ORGANIC COMPOUNDS

2.0901 DEFINITIONS

For the purpose of this Section, the following definitions apply:

- (1) **“Coating”** means a functional, protective, or decorative film applied in a thin layer to a surface.
- (2) **“Coating applicator”** means an apparatus used to apply a surface coating.
- (3) **“Coating line”** means one or more apparatus or operations in a single line wherein a surface coating is applied, dried, or cured and which include a coating applicator and flashoff area and may include an oven or associated control devices.
- (4) **“Continuous vapor control system”** means a vapor control system which treats vapors displaced from tanks during filling on a demand basis without intermediate accumulation.
- (5) **“Delivered to the applicator”** means the condition of coating after dilution by the user just before application to the substrate.
- (6) **“Flashoff area”** means the space between the application area and the oven.
- (7) **“High solids coating”** means a coating which contains a higher percentage of solids and a lower percentage of volatile organic compounds and water than conventional organic solvent-borne coatings.
- (8) **“Hydrocarbon”** means any organic compound of carbon and hydrogen only.
- (9) **“Incinerator”** means a combustion apparatus designed for high temperature operation in which solid, semisolid, liquid, or gaseous combustible wastes are ignited and burned efficiently and from which the solid and gaseous residues contain little or no combustible material.
- (10) **“Intermittent vapor control system”** means a vapor control system which employs an intermediate vapor holder to accumulate vapors displaced from tanks during filling. The control device treats the accumulated vapors only during automatically controlled cycles.
- (11) **“Loading rack”** means an aggregation or combination of loading equipment arranged so that all loading outlets in the combination can be connected to a tank truck or trailer parked in a specified loading space.
- (12) **“Low solvent coating”** means a coating which contains a substantially lower amount of volatile organic compounds than conventional organic solvent borne coatings; it usually falls into one of three major groups of high solids, waterborne, or powder coatings.
- (13) **“Organic material”** means a chemical compound of carbon excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate.
- (14) **“Oven”** means a chamber within which heat is used to bake, cure, polymerize, or dry a surface coating.
- (15) **“Potential emissions”** means the quantity of a pollutant which would be emitted at the maximum capacity of a stationary source to emit the pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the source to emit a pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is

described or contained as a condition in the federally enforceable permit. Secondary missions do not count in determining potential emissions of a stationary source. Fugitive emissions count, to the extent quantifiable, in determining the potential emissions only in these cases:

- (a) petroleum refineries,
 - (b) chemical process plants, and
 - (c) petroleum storage and transfer units with a total storage capacity exceeding 300,000 barrels.
- (16) **“Prime coat”** means the first film of coating applied to a surface to protect it or to prepare it to receive subsequent coatings.
- (17) **“Reasonably available control technology”** (also denoted as RACT) means the lowest emission limit which a particular source is capable of meeting by the application of control technology that is reasonably available considering technological and economic feasibility. It may require technology which has been applied to similar, but not necessarily identical, source categories.
- (18) **“Reid vapor pressure”** means the absolute vapor pressure of volatile crude oil and volatile nonviscous petroleum liquids except liquefied petroleum gases as determined by American Society for Testing and Materials, Part 17, 1973, D-323-72 (reapproved 1977).
- (19) **“Shutdown”** means the cessation of operation of a source or a part thereof or emission control equipment.
- (20) **“Solvent”** means organic materials which are liquid at standard conditions and which are used as solvers, viscosity reducers, or cleaning agents.
- (21) **“Standard conditions”** means a temperature of 68 degrees Fahrenheit and pressure of 29.92 inches of mercury.
- (22) **“Stage I”** means vapor control systems that minimize, collect, and transfer vapors in a gasoline storage tank, displaced by the incoming gasoline, which are routed through pipes and hoses back to into the tank truck tank to be transported to where the truck is loaded and the vapors are recovered or destroyed. Vent lines on storage tanks with vapor control systems use pressure relief valves or flow restrictors to minimize releases to the atmosphere.
- (23) **“Startup”** means the setting in operation of a source or emission control equipment.
- (24) **“Substrate”** means the surface to which a coating is applied.
- (25) **“Topcoat”** means the final film of coating applied in a multiple or single coat operation.
- (26) **“True vapor pressure”** means the equilibrium partial pressure exerted by a petroleum liquid as determined in accordance with methods described in American Petroleum Institute Bulletin 2517, “Evaporation Loss from Floating Roof Tanks”, 1962.
- (27) **“Vapor collection system”** means a vapor transport system which uses direct displacement by the liquid loaded to force vapors from the tank into a vapor control system.
- (28) **“Vapor control system”** means a system which prevents release to the atmosphere of at least 90 percent by weight of organic compounds in the vapors displaced from a tank during the transfer of gasoline.
- (29) **“Volatile organic compound”** (also denoted as VOC) means any compound of carbon whose volatile content can be determined by the procedure described in Section 2.2600 of this Article excluding any compound that is listed under 40 CFR 51.100(s) as having been determined to have negligible photochemical reactivity.

*History Note: Authority G.S. 143-215.3(a)(1);
Eff July 1, 1979;
Amended Eff. January 1, 2009; June 1, 2008;
July 1, 1996, December 1, 1993; July 1, 1991;
March 1, 1991.*

2.0902 APPLICABILITY

- (a) The Regulations in this Section shall not apply except as specifically set out in this Regulation.
- (b) This Section applies to sources that emit greater than or equal to 15 pounds of volatile organic compounds per day unless specified otherwise in this Section.
- (c) MCAPCO Regulations 2.0925 – “Petroleum Liquid Storage in Fixed Roof Tanks”, 2.0926 – “Bulk Gasoline Plants”, 2.0927 – “Bulk Gasoline Terminals”, 2.0928 – “Gasoline Service Stations Stage I”, 2.0931 – “Cutback Asphalt”, 2.0932 – “Gasoline Truck Tanks and Vapor Collection Systems”, 2.0933 – “Petroleum Liquid Storage in External Floating Roof Tanks”, and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds” apply regardless of the level of emissions of volatile organic compounds unless provisions specified in Paragraph (d)(1) of this Regulation are applied.
- (d) This Section does not apply to:
- (1) sources that emit less than 800 pounds of volatile organic compounds per calendar month and that are:
 - (A) bench-scale, on-site equipment used exclusively for chemical or physical analysis for quality control purposes, staff instruction, water or wastewater analyses, or non-production environmental compliance assessments;
 - (B) bench-scale experimentation, chemical or physical analyses, training or instruction from not-for-profit, non-production educational laboratory
 - (C) bench-scale experimentation, chemical or physical analyses, training or instruction from hospitals or health laboratories pursuant to the determination or diagnoses of illness; or
 - (D) research and development laboratory activities provided the activity produces no commercial product or feedstock material; or
 - (2) emissions of volatile organic compounds during startup or shutdown operations from sources that use incineration or other types of combustion to control emissions of volatile organic compounds whenever the off-gas contains an explosive mixture during the startup or shutdown operation if the exemption is approved by the Director as meeting the requirements of this Subparagraph.
- (e) The following MCAPCO Regulations apply to facilities located in Mecklenburg County:
- (1) 2.0925 - “Petroleum Liquid Storage in Fixed Roof Tanks”, for fixed roof tanks at

- gasoline bulk plants and gasoline bulk terminals;
- (2) 2.0926 - “Bulk Gasoline Plants”;
 - (3) 2.0927 - “Bulk Gasoline Terminals”;
 - (4) 2.0928 - “Gasoline Service Stations Stage I”;
 - (5) 2.0932 - “Gasoline Truck Tanks and Vapor Collection Systems”;
 - (6) 2.0933 - “Petroleum Liquid Storage in External Floating Roof Tanks”, for external floating roof tanks at bulk gasoline plants and bulk gasoline terminal;
 - (7) 2.0948 - “VOC Emissions from Transfer Operations”; and
 - (8) 2.0949 - “Storage of Miscellaneous Volatile Organic Compounds”;

(f) Except as provided in Paragraph (e) of this Regulation, the Regulations in this Section apply to facilities subject to Section 182(b)(2) of the Clean Air Act with potential to emit 100 or more tons per year of VOC and to facilities with potential to emit less than 100 tons per year of volatile organic compounds in categories for which the United States Environmental Protection Agency has issued Control Technique Guidelines that are located in Mecklenburg County which is a part of a moderate nonattainment area for the 1997 8-hour ozone standard as designated in 40 CFR 81.334 prior to January 2, 2014. These facilities are subject to reasonably available control technology under this Section and shall comply in accordance with MCAPCO Regulation 2.0909 – “Compliance Schedules For Sources In Non-attainment Areas” through use of MCAPCO Regulation 2.0951 – “Miscellaneous Volatile Organic Compound Emissions” and with MCAPCO Regulation 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

(g) If Mecklenburg County is later designated in 40 CFR 81.334 as attainment and becomes a maintenance area for the 1997 8-hour ozone standard, all sources that achieved compliance in accordance with MCAPCO Regulation 2.0909 shall continue to comply with this Section. Facilities with potential to emit less than 100 tons of volatile organic compounds per year for that the compliance date in MCAPCO Regulation 2.0909 has not passed before redesignation of the area to attainment for the 1997 ozone standard shall comply in accordance with Paragraph (h) of this Regulation.

(h) If a violation of the 1997 ambient air quality standard for ozone occurs in the Charlotte-Gastonia-Rock Hill ozone area, the Director of the North Carolina Department of Environmental Quality – Division of Air Quality shall initiate technical analysis to determine the control measures needed to attain and maintain the 1997 8-hour ambient air quality standard for ozone. By the following May 1, the Director shall implement the specific stationary source control measures contained in this Section that are required as part of the control strategy necessary to bring the area into compliance and to maintain compliance with the 1997 8-hour ambient air quality standard for ozone. The Director shall implement the Regulations in this Section identified as being necessary by the analysis by notice in the North Carolina Register. The notice shall identify the Regulations that are to be implemented and shall identify whether the Regulation implemented are to apply to the areas listed in Paragraph (f) of the Regulation. At least one week before the scheduled publication date of the North Carolina Register containing the Director’s notice implementing Regulations in this Section, the Director shall send written notification to all permitted facilities within Mecklenburg County that are or may be subject to the requirements of

this Section informing them that they are or may be subject to the requirements of this Section. Compliance shall be according to MCAPCO Regulation 2.0909 – “Compliance Schedules for Sources in Nonattainment Areas”.

(i) Sources whose emissions of volatile organic compounds that are not subject to limitation under this Section may still be subject to emission limits on volatile organic compounds in MCAPCO Regulation 2.0524 - “New Source Performance Standards”, 2.1110 - “National Emission Standards for Hazardous Air Pollutants”, or 2.1111 - “Maximum Achievable Control Technology”.

State History Note:

Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);

Eff. July 1, 1979;

Amended Eff. November 1, 2016; May 1, 2013, September 10, 2010; January 1, 2009; July 1, 2007; March 1, 2007; August 1, 2004; July 1, 2000; April 1, 1997; July 1, 1996; July 1, 1995; May 1, 1995; July 1, 1994.

MCAQ History Note:

Amended Eff. October 17, 2017; June 17, 2014

2.0903 RECORDKEEPING: REPORTING: MONITORING

(a) This Regulation applies to sources subject to Regulations in this Section.

(b) The owner or operator of any volatile organic compound emission source or control equipment shall maintain:

- (1) records detailing all activities relating to any compliance schedule in this Section,
- (2) records detailing all malfunctions under MCAPCO Regulation 2.0535 - “Excess Emissions Reporting and Malfunctions”,
- (3) records of all testing conducted under Regulations in this Section,
- (4) records of all monitoring conducted under Paragraph (d) of this Regulation, and
- (5) records necessary to determine compliance as required by Paragraph (d) of this Regulation.

(c) When requested by the Director, the owner or operator of any volatile organic compound emission source or control equipment shall submit reports detailing the following:

- (1) General information.
 - (A) Type of source and process description.
 - (B) Schedule of operation.
 - (C) Quantity of volatile organic compounds emitted per day from each source.
 - (D) Quantity and type of wash and clean-up solvents used each day for each source.
- (2) Coating line information.

- (A) Method of application.
 - (B) Drying method used and minimum temperature.
 - (C) Substrate type.
 - (D) Substrate form.
 - (E) Type of coatings applied, number of each coating type applied, and quantity of each type of coating applied per day.
 - (F) Percent by weight of volatile organic compounds content of each coating applied.
 - (G) Percent by volume of solids content of each coating applied.
 - (H) Method used to determine volume percent solids content of coatings.
 - (I) Type and quantity of diluents added to each coating and percent by weight of volatile organic content of each diluent.
- (3) Control equipment.
- (A) Thermal incinerator.
 - (i) Combustion temperature.
 - (ii) Residence time.
 - (B) Catalytic incinerator.
 - (i) Exhaust gas temperature.
 - (ii) Change in temperature across catalyst bed.
 - (iii) Residence time.
 - (iv) Date of last change of catalyst bed.
 - (v) Date of last catalyst test and results of test.
 - (C) Condenser.
 - (i) Inlet temperature of cooling medium.
 - (ii) Outlet temperature of cooling medium.
 - (D) Emission test results.
 - (i) Inlet volatile organic compound concentration.
 - (ii) Outlet volatile organic compound concentration.
 - (iii) Explanation of how inlet and outlet concentrations have been determined.
 - (iv) Date when these concentrations were last determined.
 - (E) Capture system.
 - (i) Type of capture system.
 - (ii) Efficiency of capture system.
 - (iii) Explanation of how capture efficiency has been determined.

The owner or operator of the source shall also provide any other pertinent information to the Director when requested.

(d) The owner or operator of any volatile organic compound emission source or control equipment shall:

- (1) install, operate, and maintain process and/or control equipment monitoring instruments or procedures as necessary to comply with Paragraphs (b) and (c) of this Regulation; and

- (2) maintain, in writing, data and/or reports relating to monitoring instruments or procedures which will, upon review, document the compliance status of the volatile organic compound emission source or control equipment to the satisfaction of the Director; such data and reports shall, as a minimum, be maintained daily unless otherwise specified in this section.

(e) Copies of all records and reports under Paragraphs (b), (c), and (d) of this Regulation shall be retained by the owner or operator for a minimum of two years after the date on which the record was made or the report submitted. However, the Director may extend the retention period in particular instances when necessary to comply with other State or federal requirements or when compliance with a particular standard requires documentation for more than two years.

(f) Copies of all records and reports under this Section shall be made available within a reasonable time to the Director upon written request.

State History Note:

*Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. May 1, 2013, July 1, 1993; July 1, 1991; December 1,
1989; January 1, 1985; July 1, 1980; June 1, 1980.*

MCAQ History Note:

Eff. June 17, 2014

**2.0904 MALFUNCTIONS: BREAKDOWNS: UPSETS
(REPEALED BY STATE PRIOR TO LOCAL ADOPTION)**

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-
215.107(a)(5);
Eff. July 1, 1979; Repealed Eff. March 1, 1983.*

**2.0905 PETITION FOR ALTERNATIVE CONTROLS
(REPEALED BY STATE PRIOR TO LOCAL ADOPTION)**

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-
215.107(a)(5);
Eff. July 1, 1979; Amended Eff. January 1, 1985; July 1, 1980.
Repealed Eff. July 1, 1988.*

2.0906 CIRCUMVENTION

(a) An owner or operator subject to this Section shall not build, erect, install, or use any article,

machine, equipment, process, or method, the use of which conceals an emission which would otherwise constitute a violation of an applicable Regulation.

(b) Paragraph (a) of this Regulation includes, but is not limited to, the use of gaseous diluents to achieve compliance and the piecemeal carrying out of an operation to avoid coverage by a Regulation that applies only to operations larger than a specified size.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. January 1, 1985.

2.0907 COMPLIANCE SCHEDULES FOR SOURCES IN NONATTAINMENT AREAS (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. May 1, 1995; July 1, 1994; July 1, 1994;
January 1, 1985;
Repealed Eff. April 1, 1997.

2.0908 EQUIPMENT MODIFICATION COMPLIANCE SCHEDULES (REPEALED BY STATE PRIOR TO LOCAL ADOPTION)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-215.107(a)(5);
Eff. July 1, 1979; Amended Eff. January 1, 1985; July 1, 1980.
Repealed Eff. July 1, 1988.

2.0909 COMPLIANCE SCHEDULES FOR SOURCES IN OZONE NONATTAINMENT AREAS

(a) Applicability. With the exceptions in Paragraph (b) of this Regulation, this Regulation applies to sources located at any facility covered by Paragraphs (f) or (h) of MCAPCO Regulation 2.0902 - “Applicability”.

(b) Exceptions. This Regulation does not apply to facilities subject to the rules listed under paragraph (e) in MCAPCO Regulation 2.0902 - “Applicability”. Facilities subject to Regulations

listed in paragraph (e) of MCAPCO Regulation 2.0902 shall comply in accordance with the provisions defined in those Regulations rather than the schedule listed in Paragraph (c) and (d) of this Regulation.

(c) Maintenance area contingency plan. The owner or operator of any source subject to Paragraph (a) in this Regulation shall adhere to the following increments of progress and schedules:

- (1) if compliance with applicable Regulations in this Section is to be achieved by installing emission control equipment, replacing process equipment, or modifying existing process equipment:
 - (A) The owner or operator shall submit a permit application and a compliance schedule within six months after the Director of the North Carolina Department of Environment and Natural Resources – Division of Air Quality (hereafter identified as NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone;
 - (B) The compliance schedule shall contain the following increments of progress:
 - (i) a date by which contracts for the emission control system and process equipment shall be awarded or orders shall be issued for purchase of component parts;
 - (ii) a date by which on-site construction or installation of the emission control and process equipment shall begin; and
 - (iii) a date by which on-site construction or installation of the emission control and process equipment shall be completed; and
 - (C) Final compliance with applicable Regulations in this Section shall be achieved within three years after the Director (NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone.
- (2) if compliance with applicable Regulations in this Section is to be achieved by using low solvent content coating technology:
 - (A) The owner or operator shall submit a permit application and a compliance schedule to Mecklenburg County Air Quality (MCAQ) within six months after the Director (NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone;
 - (B) The compliance schedule shall contain the following increments of progress:
 - (i) a date by which purchase orders shall be issued for low solvent content coatings and process modifications;
 - (ii) a date by which process modifications shall be initiated; and
 - (iii) a date by which process modifications shall be completed and use of low solvent content coatings shall begin; and
 - (C) Final compliance with applicable Regulations in this Section shall be achieved within two years after the Director (NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone.

- (3) The owner or operator shall certify to the Director (MCAQ) within five days after each increment deadline of progress in this Paragraph, whether the required increment of progress defined has been met.

(d) Moderate nonattainment areas. The owner or operator of any source subject to Paragraph (a) of this Regulation shall adhere to the following increments of progress and schedules:

- (1) if compliance with applicable Regulations in this Section is to be achieved by installing emissions control equipment, replacing process equipment, or modifying existing process equipment:
 - (A) The owner or operator shall submit a permit application and compliance schedule by August 1, 2007.
 - (B) The compliance schedule shall contain the following increments of progress:
 - (i) a date by which contracts for the emission control system and process equipment shall be awarded or orders shall be issued for purchase of component parts;
 - (ii) a date by which on-site construction or installation of the emissions control and process equipment shall begin; and
 - (iii) a date by which on-site construction or installation of the emission control and process equipment shall be completed; and
 - (C) For facilities with potential to emit 100 tons or more of volatile organic compounds per year, final compliance with the applicable Regulations of this Section shall be achieved no later than April 1, 2009.
 - (D) For facilities with potential to emit less than 100 tons of volatile organic compounds per year final compliance with the applicable Regulations of this Section shall be achieved no later than May 1, 2016
- (2) if compliance with the applicable Regulations of this Section is to be achieved by using low solvent content coating technology:
 - (A) The owner or operator shall submit a permit application and a compliance schedule by August 1, 2007.
 - (B) The compliance schedule shall contain the following increments:
 - (i) a date by which purchase orders shall be issued for low solvent content coatings and process modifications;
 - (ii) a date by which process modifications shall be initiated; and
 - (iii) a date by which process modifications shall be completed and use of low solvent content coatings shall begin; and
 - (C) Final compliance with the applicable Regulations of this Section shall be achieved no later than April 1, 2009.
 - (D) For facilities with potential to emit less than 100 tons of volatile organic compounds per year, final compliance with the applicable Regulations of this Section shall be achieved no later than May 1, 2015.
- (3) The owner or operator shall certify to the Director (MCAQ) within five days after the deadline, for each increment of progress defined in this Paragraph, whether the required increment of progress has been met.

(e) If the Director (MCAQ) requires a test to demonstrate that compliance has been achieved, the owner or operator of sources subject to this Regulation shall conduct a test and submit a final test report within six months after the stated date of final compliance.

(f) Sources already in compliance.

- (1) Maintenance area contingency plan. Paragraph (c) of this Regulation shall not apply to any source subject to Paragraph (a) of this Regulation that are in compliance with applicable Regulations of this Section when the Director (NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone and that have determined and certified compliance to the satisfaction of the Director (MCAQ) within six months after the Director (NCDENR-DAQ) notices the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone.
- (2) Moderate nonattainment areas. Paragraph (d) of this Regulation does not apply to facilities subject to Paragraph (a) of this Regulation if they are in compliance with applicable Regulations of this Section on March 1, 2007.

(g) New sources.

- (1) Maintenance area contingency plan. The owner or operator of any source subject to Paragraph (a) of this Regulation not in existence or under construction before the date that the Director (NCDENR-DAQ) notices in the North Carolina Register in accordance with MCAPCO Regulation 2.0902 Paragraph (h) the implementation of rules in the North Carolina Register that resolves a violation of the ambient air quality standard for ozone, shall comply with all applicable Regulations in the Section upon start-up of the source.
- (2) Moderate nonattainment areas. The owner or operator of any new source subject to Paragraph (a) of this Regulation not in existence or under construction before March 1, 2007 in an area identified in MCAPCO Regulation 2.0902 Paragraph (f) shall comply with all applicable Regulations in this Section upon start-up of the source.

State History Note:

Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);

Eff. July 1, 1979;

Amended Eff. May 1, 2013, September 1, 2010; January 1, 2009; July 1, 2007; March 1, 2007; April 1, 1997; July 1, 1995; July 1, 1994; July 1, 1988; January 1, 1985.

MCAQ History Note:

Eff. June 17, 2014

2.0910 ALTERNATIVE COMPLIANCE SCHEDULES (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. May 1, 1995; July 1, 1994; July 1, 1988;
January 1, 1985;
Repealed Eff. April 1, 1997.

2.0911 EXCEPTION FROM COMPLIANCE SCHEDULES (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. May 1, 1995; July 1, 1994; July 1, 1980;
Repealed Eff. April 1, 1997.

2.0912 GENERAL PROVISIONS ON TEST METHODS AND PROCEDURES

(a) The owner or operator of any volatile organic compound source required to comply with Regulations in this Section shall demonstrate compliance by the methods described in Section 2.2600 of this Article. The owner or operator of a volatile organic compound source shall demonstrate compliance when the Director requests such demonstration.

(b) If the volatile organic compound emissions test shows noncompliance, the owner or operator of the volatile organic source shall submit along with the final test report proposed corrective action.

(c) Compliance shall be determined on a line-by-line basis using the more stringent of the following two:

- (1) Compliance shall be determined on a daily basis for each coating line using a weighted average, that is, dividing the sum of the mass (pounds) of volatile organic compounds in coatings consumed on that coating line, as received, and the mass (pounds) of volatile organic compound solvents added to the coatings on that coating line by the volume (gallons) of coating solids consumed during that day on that coating line; or
- (2) Compliance shall be determined as follows:
 - (A) When low solvent or high solids coatings are used to reduce emissions of volatile organic compounds, compliance shall be determined instantaneously.
 - (B) When add on control devices, e.g., solvent recovery systems or incinerators, are used to reduce emissions of volatile organic compounds, compliance shall be determined by averaging emissions over a one-hour period.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;

Amended Eff. June 1, 2008; April 1, 2003; July 1, 1993; July 1, 1991; March 1, 1991; December 1, 1989; January 1, 1985; July 1, 1980.

2.0913 DETERMINATION OF VOLATILE CONTENT OF SURFACE COATINGS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); Eff. July 1, 1979; Amended Eff. March 1, 1991, December 1, 1989; July 1, 1988; January 1, 1985. Repealed Eff. June 1, 2008

2.0914 DETERMINATION OF VOC EMISSION CONTROL SYSTEM EFFICIENCY (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.68; 143-215.107(a)(5); Eff. July 1, 1979; Amended Eff. July 1, 1998; January 1, 1985. Repealed Eff. June 1, 2008

2.0915 DETERMINATION OF SOLVENT METAL CLEANING VOC EMISSIONS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-215.107(a)(5); Eff. July 1, 1979; Amended Eff. January 1, 1985. Repealed Eff. June 1, 2008

2.0916 DETERMINATION: VOC EMISSIONS FROM BULK GASOLINE TERMINALS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a) (5); Eff. July 1, 1979; Amended Eff. July 1, 1988; April 1, 1986; January 1, 1985. Repealed Eff. June 1, 2008

2.0917 AUTOMOBILE AND LIGHT-DUTY TRUCK MANUFACTURING

(REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; April 1, 1986.
Repealed Eff. September 1, 2010*

2.0918 CAN COATING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“End sealing compound”** means a synthetic rubber compound which is coated onto can ends and which functions as a gasket when the end is assembled on the can.
- (2) **“Exterior base coating”** means a coating applied to the exterior of a can to provide exterior protection to the metal and to provide background for the lithographic or printing operation.
- (3) **“Interior base coating”** means a coating applied by roller coater or spray to the interior of a can to provide a protective lining between the can metal and product.
- (4) **“Interior body spray”** means a coating sprayed on the interior of the can body to provide a protective film between the product and the can.
- (5) **“Overvarnish”** means a coating applied directly over ink to reduce the coefficient of friction, to provide gloss, and to protect the finish against abrasion and corrosion.
- (6) **“Three-piece can side-seam spray”** means a coating sprayed on the exterior and interior of a welded, cemented, or soldered seam to protect the exposed metal.
- (7) **“Two-piece can exterior end coating”** means a coating applied by roller coating or spraying to the exterior end of a can to provide protection to the metal.

(b) This Regulation applies to coating applicator(s) and oven(s) of sheet, can, or end coating lines involved in sheet basecoat (exterior and interior) and overvarnish; two-piece can interior body spray; two-piece can exterior end (spray or roll coat); three-piece can side-seam spray and end sealing compound operations.

(c) Emissions of volatile organic compounds from any can coating line subject to this Regulation shall not exceed:

- (1) 4.5 pounds of volatile organic compounds per gallon of solids delivered to the coating applicator from sheet basecoat (exterior and interior) and overvarnish or two-piece can exterior (basecoat and overvarnish) operations,
- (2) 9.8 pounds of volatile organic compounds per gallon of solids delivered to the coating applicator from two and three-piece can interior body spray and two-piece can exterior end (spray or roll coat) operations,
- (3) 21.8 pounds of volatile organic compounds per gallon of solids delivered to the coating applicator from a three-piece applicator from a three-piece can side-seam spray operations,
- (4) 7.4 pounds of volatile organic compounds per gallon of solids delivered to the coating

applicator from end sealing compound operations.

- (d) *PARAGRAPH NOT ADOPTED - Mecklenburg County had no facilities complying with this requirement instead of 2.0518(e) prior to December 1, 1989.*

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; January 1,
1985.*

2.0919 COIL COATING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Coil coating”** means the coating of any flat metal sheet or strip that comes in rolls or coils.
- (2) **“Quench area”** means a chamber where the hot metal exiting the oven is cooled by either a spray of water or a blast of air followed by water cooling.

(b) This Regulation applies to the coating applicator(s) oven(s), and quench area(s) of coil coating lines involved in prime and top coat or single coat operations.

(c) Emissions of volatile organic compounds from any coil coating line subject to this Regulation shall not exceed 4.0 pounds of volatile organic compounds per gallon of solids delivered to the coating application from prime and topcoat or single coat operations.

- (d) *PARAGRAPH NOT ADOPTED - Mecklenburg County had no facilities complying with this requirement instead of 2.0518(e) prior to December 1, 1989.*

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; January 1,
1985.*

2.0920 PAPER COATING (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; January 1, 1985.
Repealed Eff. September 1, 2010*

2.0921 FABRIC AND VINYL COATING (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; January 1, 1985.
Repealed Eff. September 1, 2010*

2.0922 METAL FURNITURE COATING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Application area”** means the area where the coating is applied by spraying, dipping, or flowcoating techniques.
- (2) "Coating unit" means one or more coating areas and any associated drying area or oven wherein a coating is applied, dried, or cured.
- (3) **“Metal furniture coatings”** means paints, sealants, caulks, inks, adhesives, and maskants.

(b) This Regulation applies to each metal furniture surface coating unit source whose emissions of volatile organic compounds exceeds the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability”.

(c) With the exception stated in Paragraph (f) of this Regulation, emissions of all volatile organic compounds from any metal furniture coating line subject to this Regulation shall not exceed:

- (1) 2.3 pounds of volatile organic compounds per gallon of coating excluding water and exempt compounds (3.3 pounds of volatile organic compounds per gallon of solids) delivered from general, one component or general, multi-component types of coating operations; and
- (2) 3.0 pounds of volatile organic compounds per gallon of coating excluding water and exempt compounds (5.1 pounds of volatile organic compounds per gallon of solids) delivered from any other types of coating operations.

(d) EPA Method 24 (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at metal furniture surface coating units unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(e) Emissions limits established in Subparagraph (c)(2) of this Regulation do not apply to stencil

coatings, safety-indicating coatings, solid film lubricants, electric-insulating and thermal-conducting coatings, touch up and repair coatings, coating application utilizing hand-held aerosol cans, or cleaning operations.

(f) Any coating unit which has chosen to use add-on control for coating operations rather than the emission limits established in Paragraph (c) of this Regulation shall install control equipment with an overall control efficiency of 90 percent or use a combination of coating and add-on control equipment on a coating unit to meet limits established in Paragraph (c) of this Regulation.

(g) The owner or operator of any facility subject to this regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. September 1, 2010; July 1, 1996, December 1,
1989; January 1, 1985.*

2.0923 SURFACE COATING OF LARGE APPLIANCE PARTS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Application area”** means the area where the coating is applied by spraying, dipping, or flowcoating techniques.
- (2) **“Coating”** means paints, sealants, caulks, inks, adhesives, and maskants.
- (3) **“Coating unit”** means a unit that consists of a series of one or more coating applicators and any associated drying area or oven where a coating is dried, or cured.
- (4) **“Large appliance part”** means any organic surface-coated metal lid, door, casing, panel, or other interior or exterior metal part or accessory that is assembled to form a large appliance product.
- (5) **“Large appliance product”** means any organic surface-coated metal range, oven, microwave oven, refrigerator, freezer, washer, dryer, dishwasher, water heater, or trash compactor manufactured for household, commercial, or recreational use.

(b) This Regulation applies to each large appliance coating unit source whose volatile organic compounds emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability.”

(c) Emissions of all volatile organic compounds from any large appliance coating ~~the~~ unit subject to this Regulation shall not exceed:

- (1) 2.3 pounds of volatile organic compounds per gallon of coating, excluding water and exempt compounds (3.3 pounds of volatile organic compounds per gallon of solids) delivered from general, one component coating or general, multi-component types of coating operations; and
- (2) 2.8 pounds of volatile organic compounds per gallon of coating, excluding water and

exempt compounds (4.5 pounds of volatile organic compounds per gallon of solids) delivered from any other types of coating operations.

(d) EPA Method 24 (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at surface coating of large appliances parts facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(e) Emissions limits established in Subparagraph (c)(2) of this Regulation do not apply to stencil coatings, safety-indicating coatings, solid film lubricants, electric-insulating and thermal-conducting coatings, touch up and repair coatings, coating applications utilizing hand-held aerosol cans, or any cleaning material.

(f) Any coating unit which has chosen to use add-on controls for coating operations rather than the emission limits established in Paragraph (c) of this Regulation shall install control equipment with an overall control efficiency of 90 percent or use a combination of coating and add-on control equipment on a coating unit to meet limits established in Paragraph (c) of this Regulation.

(g) The owner or operator of any facility subject to this Regulation shall comply with MCAPCO Regulations 2.0903 – “Record Keeping: Reporting: Monitoring” and 2.0958- -“Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. September 1, 2010; July 1, 1996, December 1,
1989; January 1, 1985.*

2.0924 MAGNET WIRE COATING

(a) For the purpose of this Regulation, “**magnet wire coating**” means the process of applying a coating of electrically insulating varnish or enamel to aluminum or copper wire for use in electrical machinery.

(b) This Regulation applies to the oven(s) of magnet wire coating operations.

(c) Emissions of volatile organic compounds from any magnet wire coating oven subject to this Regulation shall not exceed 2.2 pounds of volatile organic compounds per gallon of solids delivered to the coating applicator from magnet wire coating operations.

(d) *PARAGRAPH NOT ADOPTED Mecklenburg had no facilities complying with this requirement instead of 2.0518(e) prior to December 1, 1989.*

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. July 1, 1996, December 1, 1989; January 1,
1985.*

2.0925 PETROLEUM LIQUID STORAGE IN FIXED ROOF TANKS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Condensate”** means hydrocarbon liquid separated from natural gas which condenses due to changes in the temperature and/or pressure and remains liquid at standard conditions.
- (2) **“Crude oil”** means a naturally occurring mixture which consists of hydrocarbons and/or sulfur, nitrogen and/or oxygen derivatives of hydrocarbons and which is a liquid at standard conditions.
- (3) **“Custody transfer”** means the transfer of produced crude oil and/or condensate, after processing and/or treating in the producing operations, from storage tanks or automatic transfer facilities to pipeline or any other forms of transportation.
- (4) **“External floating roof”** means a storage vessel cover in an open top tank consisting of a double deck or pontoon single deck which rests upon and is supported by the petroleum liquid being contained and is equipped with a closure seal or seals to close the space between the roof edge and tank shell.
- (5) **“Internal floating roof”** means a cover or roof in a fixed roof tank which rests upon or is floated upon the petroleum liquid being contained, and is equipped with a closure seal or seals to close the space between the roof edge and tank shell.
- (6) **“Petroleum liquids”** means crude oil, condensate, and any finished or intermediate products manufactured or extracted in a petroleum refinery.
- (7) **“Petroleum refinery”** means any facility engaged in producing gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation of crude oils, or through redistillation, cracking, extraction, or reforming of unfinished petroleum derivatives.

(b) This Regulation applies to all fixed roof storage vessels with capacities greater than 39,000 gallons containing volatile petroleum liquids whose true vapor pressure is greater than 1.52 psia.

(c) This Regulation does not apply to volatile petroleum liquid storage vessels:

- (1) equipped with external floating roofs, or
- (2) having capacities less than 416,000 gallons used to store produced crude oil and condensate prior to lease custody transfer.

(d) With the exceptions stated in Paragraph (c) of this Regulation, the owner or operator of any fixed roof storage vessel subject to this Regulation shall not use the storage vessel unless:

- (1) the storage vessel has been retrofitted with an internal floating roof equipped with a closure seal, or seals, to close the space between the roof edge and tank wall;

- (2) the storage vessel is maintained such that there are no visible holes, tears, or other openings in the seal or any seal fabric or materials;
- (3) all openings, except stub drains are equipped with covers, lids, or seals such that:
 - (A) the cover, lid, or seal is in the closed position at all times except when in actual use;
 - (B) automatic bleeder vents are closed at all times except when the roof is floated off or landed on the roof leg supports;
 - (C) rim vents, if provided, are set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting;
- (4) routine visual inspections are conducted through roof hatches once per month;
- (5) a complete inspection of cover and seal is conducted whenever the tank is emptied for maintenance, shell inspection, cleaning, or for other nonoperational reasons or whenever excessive vapor leakage is observed; and
- (6) records are maintained in accordance with MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring" and shall include:
 - (A) reports of the results of inspections conducted under Subparagraphs (d)(4) and (d)(5) of this Regulation,
 - (B) a record of the average monthly storage temperature, and true vapor pressures of petroleum liquids stored, and
 - (C) records of the throughput quantities and types of petroleum liquids for each storage vessel.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. March 1, 1991; December 1, 1989; January 1, 1985.

2.0926 BULK GASOLINE PLANTS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Average daily throughput”** means annual throughput of gasoline divided by 312 days per year.
- (2) **“Bottom filling”** means the filling of a truck tank or stationary storage tank through an opening that is flush with the tank bottom.
- (3) **“Bulk gasoline plant”** means a gasoline storage and distribution facility which has an average daily throughput of less than 20,000 gallons of gasoline and which usually receives gasoline from bulk terminals by trailer transport, stores it in tanks, and subsequently dispenses it via account trucks to local farms, businesses, and service stations.
- (4) **“Bulk gasoline terminal”** means a gasoline storage facility which usually receives gasoline from refineries primarily by pipeline, ship, or barge; and delivers gasoline to bulk gasoline plants or to commercial or retail accounts primarily by truck tank; and has an average daily throughput of more than 20,000 gallons of gasoline.
- (5) **“Gasoline”** means any petroleum distillate having a Reid vapor pressure of four psia or greater.
- (6) **“Incoming vapor balance system”** means a combination of pipes or hoses which create a closed system between the vapor spaces of an unloading truck tank or trailer and a receiving stationary storage tank such that vapors displaced from the receiving stationary storage tank are transferred to the truck tank or trailer being unloaded.
- (7) **“Outgoing vapor balance system”** means a combination of pipes or hoses which create a closed system between the vapor spaces of an unloading stationary storage tank and a receiving truck tank or trailer such that vapors displaced from the receiving truck tank or trailer are transferred to the stationary storage tank being unloaded.
- (8) **“Splash filling”** means the filling of a truck tank or stationary storage tank through a pipe or hose whose discharge opening is above the surface level of the liquid in the tank being filled.
- (9) **“Submerged filling”** means the filling of a truck tank or stationary tank through a pipe or hose whose discharge opening is entirely submerged when the pipe normally used to withdraw liquid from the tank can no longer withdraw any liquid, or whose discharge opening is entirely submerged when the liquid level is six inches above the bottom of the tank.

(b) This Regulation applies to the unloading, loading, and storage facilities of all bulk gasoline plants and of all truck tanks or trailers delivering or receiving gasoline at bulk gasoline plants except stationary storage tanks with capacities less than 528 gallons.

(c) The owner or operator of a bulk gasoline plant shall not transfer gasoline to any stationary storage tanks after May 1, 1993 unless the unloading truck tank or trailer and the receiving stationary storage tank are equipped with an incoming vapor balance system as described in Paragraph (i) of this Regulation and the receiving stationary storage tank is equipped with a fill line whose discharge opening is flush with the bottom of the tank.

(d) The owner or operator of a bulk gasoline plant with an average daily throughput of 4000 gallons or more shall not load truck tanks or trailers at such plant after May 1, 1993, unless the unloading stationary storage tank and the receiving truck tank or trailer are equipped with an outgoing vapor balance system as described in Paragraph (i) of this Regulation and the receiving truck tank or trailer is equipped for bottom filling.

(e) The owner or operator of a bulk gasoline plant with an average daily throughput of more than 2,500 gallons but less than 4,000 gallons located in an area with a housing density exceeding specified limits as described in this Paragraph shall not load any truck tank or trailer at such bulk gasoline plant after November 1, 1996, unless the unloading stationary storage tank and receiving truck tank or trailer are equipped with an outgoing vapor balance system as described in Paragraph (i) of this Regulation and the receiving truck tank or trailer is equipped for bottom filling. In Mecklenburg County the specified limit on housing density is 50 residences in a square one mile on a side with the square centered on the loading rack at the bulk gasoline plant and with one side oriented in a true North-South direction. In all other counties the specified limit on housing density is 100 residences per square mile. The housing density shall be determined by counting the number of residences using aerial photographs or other methods determined by the Director to provide equivalent accuracy.

(f) The owner or operator of a bulk gasoline plant not subject to the outgoing vapor balance system requirements of Paragraph (d) or (e) of this Regulation shall not load truck tanks or trailers at such plants unless:

- (1) equipment is available at the bulk gasoline plant to provide for submerged filling of each truck tank or trailer; or
- (2) each receiving truck tank or trailer is equipped for bottom filling.

(g) For a gasoline bulk plant located in a nonattainment area for ozone, once the average daily throughput of gasoline at the bulk gasoline plant reaches or exceeds the applicability threshold in Paragraph (d) or (e) of this Regulation or if Paragraph (d) or (e) is currently applicable to the bulk gasoline plant, the bulk gasoline plant shall continue to comply with the outgoing vapor balance system requirements of Paragraph (d) or (e) of this Regulation, as is applicable, even though the average daily gasoline throughput falls below the threshold contained in Paragraph (d) or (e) of this Regulation.

(h) The owner or operator of a bulk gasoline plant, truck tank or trailer that is required to be equipped with a vapor balance system pursuant to Paragraph (c), (d), or (e) of this Regulation shall not transfer gasoline between truck tank or trailer and stationary storage tank unless:

- (1) the vapor balance system is in good working order and is connected and operating,
- (2) truck tank or trailer hatches are closed at all times during loading and unloading operations,
and
- (3) the truck tank's or trailer's pressure/vacuum relief valves and hatch covers and the truck tanks or storage tanks or associated vapor and liquid lines are vapor tight during loading or unloading.

(i) Vapor balance systems required by Paragraphs (c), (d), and (e) of this Regulation shall consist of the following major components:

- (1) a vapor space connection on the stationary storage tank equipped with fittings which are vapor tight and will be automatically and immediately closed upon disconnection so as to prevent release of organic material,
- (2) a connecting pipe or hose equipped with fittings which are vapor tight and will be automatically and immediately closed upon disconnection so as to prevent release of organic material,
and
- (3) a vapor space connection on the truck tank or trailer equipped with fittings which are vapor tight and will be automatically and immediately closed upon disconnection so as to prevent release of organic material.

(j) The owner or operator of a bulk gasoline plant shall paint all tanks used for gasoline storage white or silver at the next scheduled painting or before November 1, 2002, whichever is sooner.

(k) The pressure relief valves on truck tanks or trailers loading or unloading at bulk gasoline plants shall be set to release at the highest possible pressure (in accordance with state or local fire codes or the National Fire Prevention Association guidelines). The pressure relief valves on stationary storage tanks shall be set at 0.5 psi for storage tanks placed in service on or after November 1, 1992, and 0.25 psi for storage tanks existing before November 1, 1992.

(l) No owner or operator of a bulk gasoline plant may permit gasoline to be spilled, discarded in sewers, stored in open containers, or handled in any other manner that would result in evaporation.

(m) The owner or operator of a bulk gasoline plant shall observe loading and unloading operations and shall discontinue the transfer of gasoline:

- (1) if any liquid leaks are observed, or
- (2) if any vapor leaks are observed where a vapor balance system is required under Paragraph (c), (d), or (e) of this Regulation.

(n) The owner or operator of a bulk gasoline plant shall not load, or allow to be loaded, gasoline into any truck tank or trailer unless the truck tank or trailer has been certified leak tight in accordance with MCAPCO Regulation 2.0932 - "Gasoline Truck Tanks and Vapor Collection Systems" within the last 12 months where the bulk gasoline plant is required to use an outgoing vapor balance system.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979; Amended Eff. July 1, 1996, May 1, 1993,
March 1, 1991, December 1, 1989.*

2.0927 BULK GASOLINE TERMINALS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Breakout tank”** means a tank used to:
 - (A) relieve surges in a hazardous liquid pipeline system, or
 - (B) receive and store hazardous liquids transported by pipeline for reinjection and continued transport by pipeline.
- (2) **“Bulk gasoline terminal”** means:
 - (A) breakout tanks of an interstate oil pipeline facility; or
 - (B) a gasoline storage facility that usually receives gasoline from refineries primarily by pipeline, ship, or barge; delivers gasoline to bulk gasoline plants or to commercial or retail accounts primarily by tank truck; and has an average daily throughput of more than 20,000 gallons of gasoline.
- (3) **“Contact deck”** means a deck in an internal floating roof tank that rises and falls with the liquid level and floats in direct contact with the liquid surface.
- (4) **“Gasoline”** means a petroleum distillate having a Reid vapor pressure of four psia or greater.
- (5) **“Degassing”** means the process by which a tank’s interior vapor space is decreased to below the lower explosive limit for the purpose of cleaning, inspection, or repair.
- (6) **“Leak”** means a crack or hole that lets petroleum product vapor or liquid escape that can be identified through the use of sight, sound, smell, an explosimeter, or the use of a meter that measures volatile organic compounds. When an explosimeter or meter is used to detect a leak, a leak is a measurement that is equal to or greater than 100 percent of the lower explosive limit, as detected by a combustible gas detector using the test procedure described in MCAPCO Regulation 2.0940 – “Determination of Leak Tightness and Vapor Leaks”.
- (7) **“Liquid balancing”** means a process used to degas floating roof gasoline storage tanks with a liquid whose vapor pressure is below 1.52 psia. This is done by removing as much gasoline as possible without landing the roof on its internal supports, pumping in the replacement fluid, allowing mixing, remove as much mixture as possible without landing the roof, and repeating these steps until the vapor pressure of the mixture is below 1.52 psia.
- (8) **“Liquid displacement”** means a process by which gasoline vapors, remaining in an empty tank, are displaced by a liquid with a vapor pressure below 1.52 psia.

(b) This Regulation applies to bulk gasoline terminals and the appurtenant equipment necessary to load the tank truck or trailer compartments.

(c) Gasoline shall not be loaded into any tank trucks or trailers from any bulk gasoline terminal unless:

- (1) The bulk gasoline terminal is equipped with a vapor control system that prevents the emissions of volatile organic compounds from exceeding 35 milligrams per liter. The owner or operator shall obtain from the manufacturer and maintain in his records a pre-installation certification stating the vapor control efficiency of the system in use;
- (2) Displaced vapors and gases are vented only to the vapor control system or to a flare;

- (3) A means is provided to prevent liquid drainage from the loading device when it is not in use or to accomplish complete drainage before the loading device is disconnected; and
- (4) All loading and vapor lines are equipped with fittings that make vapor-tight connections and that are automatically and immediately closed upon disconnection.

(d) Sources regulated by Paragraph (b) of this Regulation shall not:

- (1) allow gasoline to be discarded in sewers or stored in open containers or handled in any manner that would result in evaporation, or
- (2) allow the pressure in the vapor collection system to exceed the tank truck or trailer pressure relief settings.

(e) The owner or operator of a bulk gasoline terminal shall paint all tanks used for gasoline storage white or silver at the next scheduled painting or by December 1, 2002, whichever occurs first.

(f) The owner or operator of a bulk gasoline terminal shall install on each external floating roof tank with an inside diameter of 100 feet or less used to store gasoline a self-supporting roof, such as a geodesic dome, at the next time that the tank is taken out of service or by December 1, 2002, whichever occurs first.

(g) The following equipment shall be required on all tanks storing gasoline at a bulk gasoline terminal:

- (1) rim-mounted secondary seals on all external and internal floating roof tanks,
- (2) gaskets on deck fittings, and
- (3) floats in the slotted guide poles with a gasket around the cover of the poles.

(h) Decks shall be required on all above ground tanks with a capacity greater than 19,800 gallons storing gasoline at a bulk gasoline terminal. All decks installed after June 30, 1998 shall comply with the following requirements:

- (1) deck seams shall be welded, bolted or riveted; and
- (2) seams on bolted contact decks and on riveted contact decks shall be gasketed.

(i) If, upon facility or operational modification of a bulk gasoline terminal that existed before December 1, 1992, an increase in benzene emissions results such that:

- (1) emissions of volatile organic compounds increase by more than 25 tons cumulative at any time during the five years following modifications; and
- (2) annual emissions of benzene from the cluster where the bulk gasoline terminal is located (including the pipeline and marketing terminals served by the pipeline) exceed benzene emissions from that cluster based upon calendar year 1991 gasoline throughput and application of the requirements of this Article,

then, the annual increase in benzene emissions due to the modification shall be offset within the cluster by reduction in benzene emissions beyond that otherwise achieved from compliance with this Regulation, in the ratio of at least 1.3 to 1.

(j) The owner or operators of a bulk gasoline terminal that has received an air permit before December 1, 1992, to emit toxic air pollutants under MCAPCO Section 1.5700 - "Toxic Air Pollutant Procedures" to comply with MCAPCO Section 2.1100 - "Control of Toxic Air Pollutants" shall continue to follow all terms and conditions of the permit issued under MCAPCO Section 1.5700 - "Toxic Air Pollutant Procedures" and to bring the terminal into compliance with MCAPCO Section 2.1100 - "Control of Toxic Air Pollutants" according to the terms and conditions of the permit, in which case the bulk gasoline terminal shall continue to need a permit to emit toxic air pollutants and shall be exempted from Paragraphs (e) through (i) of this Regulation.

(k) The owner or operator of a bulk gasoline terminal shall not load, or allow to be loaded, gasoline into any truck tank or trailer unless the truck tank or trailer has been certified leak tight according to MCAPCO Regulation 2.0932 - "Gasoline Truck Tanks and Vapor Collection Systems" within the last 12 months.

(l) The owner or operator of a bulk gasoline terminal shall have on file at the terminal a copy of the certification test conducted according to MCAPCO Regulation 2.0932 - "Gasoline Truck Tanks and Vapor Collection Systems" for each gasoline tank truck loaded at the terminal.

(m) Emissions of gasoline from degassing of external or internal floating roof tanks at a bulk gasoline terminal shall be collected and controlled by at least 90 percent by weight. Liquid balancing shall not be used to degas gasoline storage tanks at bulk gasoline terminals. Bulk gasoline storage tanks containing not more than 138 gallons of liquid gasoline or the equivalent of gasoline vapor and gasoline liquid are exempted from the degassing requirements if gasoline vapors are vented for at least 24-hours. Documentation of degassing external or internal floating roof tanks shall be made according to MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring".

(n) According to MCAPCO Regulation 2.0903, the owner or operator of a bulk gasoline terminal shall visually inspect the following for leaks each day that the terminal is both manned and open for business:

- (1) the vapor collection system,
- (2) the vapor control system, and
- (3) each lane of the loading rack while a gasoline tank truck or trailer is being loaded.

If no leaks are found, the owner or operator shall record that no leaks were found. If a leak is found, the owner or operator shall record the information specified in Paragraph (p) of this Regulation. The owner or operator shall repair all leaks found according to Paragraph (g) of this Regulation.

(o) The owner or operator of a bulk gasoline terminal shall inspect weekly for leaks:

- (1) the vapor collection system,
- (2) the vapor control system, and
- (3) each lane of the loading rack while a gasoline tank truck or trailer is being loaded.

The weekly inspection shall be done using sight, sound, or smell; a meter used to measure volatile organic compounds; or an explosimeter. An inspection using either a meter used to measure volatile organic compounds or an explosimeter shall be conducted every month. If no leaks are found, the owner or operator shall record the data that the inspection was done and that no leaks were found. If a leak is found, the owner or operator shall record the information specified in Paragraph (p) of this Regulation. The owner or operator shall repair all leaks found according to Paragraph (q) of this Regulation.

(p) For each leak found under Paragraph (n) or (o) of this Regulation, the owner or operator of a bulk gasoline terminal shall record:

- (1) the date of the inspection,
- (2) the findings (location, nature and severity of each leak),
- (3) the corrective action taken,
- (4) the date when corrective action was completed, and
- (5) any other information that the terminal deems necessary to demonstrate compliance.

(q) The owner or operator of a bulk gasoline terminal shall repair all leaks as follows:

- (1) The vapor collection hose that connects to the tank truck or trailer shall be repaired or replaced before another tank truck or trailer is loaded at the rack after a leak has been detected originating with the terminal's equipment rather than from the gasoline tank truck or trailer.
- (2) All other leaks shall be repaired as expeditiously as possible but no later than 15 days from their detection. If more than 15 days are required to make the repair, the reasons that the repair cannot be made shall be documented, and the leaking equipment shall not be used after the fifteenth day from when the leak detection was found until the repair is made.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. January 1, 2007; April 1, 2003;
August 1, 2002; July 1, 1998; July 1, 1996; July 1,
1994; December 1, 1992.*

2.0928 GASOLINE SERVICE STATIONS STAGE I

(a) Definitions. For the purpose of this Regulation, the following definitions apply:

- (1) **“Coaxial system”** means the delivery of the product and recovery of vapors occur through a single coaxial fill tube, which is a tube within a tube. Product is delivered through the inner tube, and vapor is recovered through the annular space between the walls of the inner tube and outer tube.
- (2) **“Delivery vessel”** means truck tanks or trailers equipped with a storage tank and used for the transport of gasoline from sources or supply to stationary storage tanks of gasoline dispensing facilities.
- (3) **“Dual point system”** means the delivery of the product to the stationary storage tank and the recovery of vapors from the stationary storage tank occurs through two separate openings in the storage tank and two separate hoses between the truck tank and the stationary storage tank.
- (4) **“Gasoline”** means a petroleum distillate having a Reid vapor pressure of four psia or greater.
- (5) **“Gasoline dispensing facility”** means any site where gasoline is dispensed to motor vehicle gasoline tanks from stationary storage tanks.
- (6) **“Gasoline service station”** means any gasoline dispensing facility where gasoline is sold to the motoring public from stationary storage tanks.
- (7) **“Line”** means any pipe suitable for transferring gasoline.
- (8) **“Operator”** means any person who leases, operates, controls, or supervises a facility at which gasoline is dispensed.
- (9) **“Owner”** means any person who has legal or equitable title to the gasoline storage tank at a facility.
- (10) **“Poppeted vapor recovery adaptor”** means a vapor recovery adaptor that automatically and immediately closes itself when the vapor return line is disconnected and maintains a tight seal when the vapor return line is not connected.
- (11) **“Stationary storage tank”** means a gasoline storage container which is a permanent fixture.
- (12) **“Submerged fill pipe”** means any fill pipe with a discharge opening which is entirely submerged when the pipe normally used to withdraw liquid from the tank can no longer withdraw any liquid, or which is entirely submerged when the level of the liquid is:
 - (A) six inches above the bottom of the tank if the tank does not have a vapor recovery adaptor, or
 - (B) 12 inches above the bottom of the tank if the tank has a vapor recovery adaptor.If the opening of the submerged fill pipe is cut at a slant, the distance is measured from the top of the slanted cut to the bottom of the tank.
- (13) **“Throughput”** means the amount of gasoline dispensed at a facility during a calendar month after November 15, 1990.

(b) Applicability. This Regulation applies to all gasoline dispensing facilities and gasoline

service stations and to delivery vessels delivering gasoline to a gasoline dispensing facility or gasoline service station.

(c) Exemptions. This Regulation does not apply to:

- (1) transfers made to storage tanks at gasoline dispensing facilities or gasoline service stations equipped with floating roofs or their equivalent;
- (2) stationary tanks with a capacity of not more than 2,000 gallons which are in place before July 1, 1979, if the tanks are equipped with a permanent or portable submerged fill pipe;
- (3) stationary storage tanks with a capacity of not more than 550 gallons which are installed after June 30, 1979, if tanks are equipped with a permanent or portable submerged fill pipe;
- (4) stationary storage tanks with a capacity of not more than 2,000 gallons located on a farm or a residence and used to store gasoline for farm equipment or residential use if gasoline is delivered to the tank through a permanent or portable submerged fill pipe except that this exemption does not apply in ozone non-attainment areas;
- (5) stationary storage tanks at a gasoline dispensing facility or gasoline service station where the combined annual throughput of gasoline at the facility or station does not exceed 50,000 gallons, if the tanks are permanently equipped with submerged fill pipes;
- (6) any tanks used exclusively to test the fuel dispensing meters.

(d) With exceptions stated in Paragraph (c) of this Regulation, gasoline shall not be transferred from any delivery vessel into any stationary storage tank unless:

- (1) The tank is equipped with a submerged fill pipe, and the vapors displaced from the storage tank during filling are controlled by a vapor control system as described in Paragraph (e) of this Regulation;
- (2) The vapor control system is in good working order and is connected and operating with a vapor tight connection;
- (3) The vapor control system is properly maintained and all damaged or malfunctioning components or elements of design are repaired, replaced or modified;
- (4) Gauges, meters, or other specified testing devices are maintained in proper working order;
- (5) The delivery vessel and vapor collection system complies with MCAPCO Regulation 2.0932 - "Gasoline Truck Tanks and Vapor Collection Systems"; and
- (6) The following records, as a minimum, are kept in accordance with MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring":
 - (A) the scheduled date for maintenance or the date that a malfunction was detected;
 - (B) the date the maintenance was performed or the malfunction corrected;
and
 - (C) the component or element of design of the control system repaired, replaced, or modified.

(e) The vapor control system required by Paragraph (d) of this Regulation shall include one or

more of the following:

- (1) a vapor-tight line from the storage tank to the delivery vessel and:
 - (A) for a coaxial vapor recovery system, either a popped or unpopped vapor recovery adaptor;
 - (B) for a dual point vapor recovery system, a popped vapor recovery adaptor; or
- (2) a refrigeration-condensation system or equivalent designed to recover at least 90 percent by weight of the organic compounds in the displaced vapor.

(f) If an unpopped vapor recovery adaptor is used pursuant to Part (e)(1)(A) of this Regulation, the tank liquid fill connection shall remain covered either with a vapor-tight cap or a vapor return line except when the vapor return line is being connected or disconnected.

(g) If an unpopped vapor recovery adaptor is used pursuant to Part (e)(1)(A) of this Regulation, the unpopped vapor recovery adaptor shall be replaced with a popped vapor recovery adaptor when the tank is replaced or is removed and upgraded.

(h) Where vapor lines from the storage tanks are manifolded, popped vapor recovery adaptors shall be used. No more than one tank shall be loaded at a time if the manifold vapor lines are size two and one half (2 ½) inches and smaller. If the manifold vapor lines are three (3) inches and larger, then two tanks at a time may be loaded.

(i) Vent lines on tanks with Stage I controls shall have pressure release valves or restrictors.

(j) The vapor-laden delivery vessel:

- (1) shall be designed and maintained to be vapor-tight during loading and unloading operations and during transport with the exception of normal pressure/vacuum venting as required by regulations of the Department of Transportation; and
- (2) if it is refilled in North Carolina, shall be refilled only at:
 - (A) bulk gasoline plants complying with MCAPCO Regulation 2.0926 - "Bulk Gasoline Plants", or
 - (B) bulk gasoline terminals complying with MCAPCO Regulation 2.0927 - "Bulk Gasoline Terminals" or 2.0524 - "New Source Performance Standards".

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); Eff. July 1, 1979; Amended Eff. July 1, 1996; July 1, 1994; March 1, 1991; December 1, 1989.

2.0929 PETROLEUM REFINERY SOURCES (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. March 1, 1991; December 1, 1989; January
1, 1985;
Repealed Eff. July 1, 1996.*

2.0930 SOLVENT METAL CLEANING

- (a) For the purpose of this Regulation, the following definitions apply:
- (1) **“Cold cleaning”** means the batch process of cleaning and removing soils from metal surfaces by spraying, brushing, flushing, or immersion while maintaining the solvent below its boiling point. Wipe cleaning is not included in this definition.
 - (2) **“Conveyorized degreasing”** means the continuous process of cleaning and removing soils from metal surfaces by operating with either cold or vaporized solvents.
 - (3) **“Freeboard height”** means for vapor degreasers the distance from the top of the vapor zone to the top of the degreaser tank. For cold cleaners, freeboard height means the distance from liquid solvent level in the degreaser tank to the top of the tank.
 - (4) **“Freeboard ratio”** means the freeboard height divided by the width of the degreaser.
 - (5) **“Open top vapor degreasing”** means the batch process of cleaning and removing soils from metal surfaces by condensing hot solvent vapor on the colder metal parts.
 - (6) **“Solvent metal cleaning”** means the process of cleaning soils from metal surfaces by cold cleaning or open top vapor degreasing or conveyorized degreasing.
- (b) This Regulation applies to cold cleaning, open top vapor degreasing, and conveyorized degreasing operations.
- (c) The provisions of this Regulation shall apply with the following exceptions:
- (1) Open top vapor degreasers with an open area smaller than 10.8 square feet shall be exempt from Subparagraph (e)(3) of this Regulation; and
 - (2) Conveyorized degreasers with an air/vapor interface smaller than 21.6 square feet shall be exempt from Subparagraph (f)(2) of this Regulation.
- (d) The owner or operator of a cold cleaning facility shall:
- (1) equip the cleaner with a cover and the cover shall be designed so that it can be easily operated with one hand, if:
 - (A) the solvent volatility is greater than 15 millimeters of mercury or 0.3 pounds per square inch measured at 100°F,
 - (B) the solvent is agitated,
 - or
 - (C) the solvent is heated,
 - (2) equip the cleaner with a facility for draining cleaned parts. The drainage facility shall be constructed internally so that parts are enclosed under the cover while draining if the solvent volatility is greater than 32 millimeters of mercury or 0.6 pounds per

- square inch measured at 100°F. However, the drainage facility may be external for applications where an internal type cannot fit into the cleaning system;
- (3) install one of the following control devices if the solvent volatility is greater than 33 millimeters of mercury or 0.6 pounds per square inch measured at 100°F, or if the solvent is heated above 120°F:
 - (A) freeboard which gives a freeboard ratio greater than or equal to 0.7;
 - (B) water cover if the solvent is insoluble in and heavier than water;or
 - (C) other systems of equivalent control, such as refrigerated chiller or carbon adsorption, approved by the Director;
 - (4) provide a permanent, conspicuous label, summarizing the operating requirements;
 - (5) store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere;
 - (6) close the cover whenever parts are not being handled in the cleaner;
 - (7) drain the cleaned parts for at least 15 seconds or until dripping ceases;
 - and
 - (8) if used, supply a solvent spray which is a solid fluid stream (not a fine, atomized, or shower type spray) at a pressure which does not cause excessive splashing.

(e) With the exception stated in Paragraph (c) of this Regulation, the owner or operator of an open top vapor degreaser shall:

- (1) equip the vapor degreaser with a cover which can be opened and closed easily without disturbing the vapor zone;
- (2) provide the following safety switches or devices:
 - (A) a condenser flow switch and thermostat or other device which prevents heat input if the condenser coolant is either not circulating or too warm,
 - (B) a spray safety switch or other device which shuts off the spray pump if the vapor level drops more than 10 inches, and
 - (C) a vapor level control thermostat or other device which prevents heat input when the vapor level rises too high;
- (3) install one of the following control devices:
 - (A) freeboard ratio greater than or equal to 0.75. If the degreaser opening is greater than 10.8 square feet, the cover must be powered;
 - (B) refrigerated chiller;
 - (C) enclosed design (The cover or door opens only when the dry part is actually entering or exiting the degreaser.);
 - (D) carbon adsorption system, with ventilation greater than or equal to 50 cubic feet per minute per square foot of air/vapor area (when cover is open), and exhausting less than 25 parts per million of solvent averaged over one complete adsorption cycle;
- (4) keep the cover closed at all times except when processing workloads through the degreaser;
- (5) minimize solvent carry out by:

- (A) racking parts to allow complete drainage,
 - (B) moving parts in and out of the degreaser at less than 11 feet per minute,
 - (C) holding the parts in the vapor zone at least 30 seconds or until condensation ceases,
 - (D) tipping out any pools of solvent on the cleaned parts before removal from the vapor zone, and
 - (E) allowing parts to dry within the degreaser for at least 15 seconds or until visually dry;
- (6) not degrease porous or absorbent materials, such as cloth, leather, wood, or rope;
 - (7) not occupy more than half of the degreaser's open top area with a workload;
 - (8) not load the degreaser to the point where the vapor level would drop more than 10 inches when the workload is removed from the vapor zone;
 - (9) always spray below the vapor level;
 - (10) repair solvent leaks immediately or shutdown the degreaser;
 - (11) store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere;
 - (12) not operate the cleaner so as to allow water to be visually detectable in solvent exiting the water separator;
 - (13) not use ventilation fans near the degreaser opening, nor provide exhaust ventilation exceeding 65 cubic feet per minute per square foot of degreaser open area, unless necessary to meet OSHA requirements (OSHA is the U.S. Occupational Safety and Health Administration; in North Carolina the N.C. Labor Department has delegation of OSHA programs);
and
 - (14) provide a permanent, conspicuous label, summarizing the operating procedures of Subparagraphs (4) through (12) of this Paragraph.

(f) With the exception stated in Paragraph (c) of this Regulation, the owner or operator of a conveyorized degreaser shall:

- (1) not use workplace fans near the degreaser opening, nor provide exhaust ventilation exceeding 65 cubic feet per minute per square foot of degreaser opening, unless necessary to meet OSHA requirements;
- (2) install one of the following control devices:
 - (A) refrigerated chiller;
 - (B) carbon adsorption system, with ventilation greater than or equal to 50 cubic feet per minute per square foot of air/vapor area (when downtime covers are open), and exhausting less than 25 parts per million of solvent by volume averaged over a complete adsorption cycle;
- (3) equip the cleaner with equipment, such as a drying tunnel or rotating (tumbling) basket, sufficient to prevent cleaned parts from carrying out solvent liquid or vapor;
- (4) provide the following safety switches or devices:
 - (A) a condenser flow switch and thermostat or other device which prevents heat input if the condenser coolant is either not circulating or too warm,

- (B) a spray safety switch or other device which shuts off the spray pump or the conveyor if the vapor level drops more than 10 inches,
and
- (C) a vapor level control thermostat or other device which prevents heat input when the vapor level rises too high;
- (5) minimize openings during operation so that entrances and exits will silhouette workloads with an average clearance between the parts and the edge of the degreaser opening of less than four inches or less than 10 percent of the width of the opening;
- (6) provide downtime covers for closing off the entrance and exit during shutdown hours;
- (7) minimize carry out emissions by:
 - (A) racking parts for best drainage; and
 - (B) maintaining the vertical conveyor speed at less than 11 feet per minute;
- (8) store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere;
- (9) repair solvent leaks immediately, or shut down the degreaser;
- (10) not operate the cleaner so as to allow water to be visually detectable in solvent exiting the water separator;
and
- (11) place downtime covers over entrances and exits of conveyORIZED degreasers immediately after the conveyors and exhausts are shutdown and not remove them until just before start-up.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. Mar. 1, 1991; Dec. 1, 1989; January 1, 1985.

2.0931 CUTBACK ASPHALT

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Asphalt”** means a dark-brown to black cementitious material (solid, semisolid, or liquid in consistency) in which the predominating constituents are bitumens which occur in nature as such or which are obtained as residue in refining petroleum.
- (2) **“Cutback asphalt”** means asphalt cement which has been liquefied by blending with petroleum solvents (diluent). Upon exposure to atmospheric conditions, the diluents evaporate, leaving the asphalt cement to perform its function.
- (3) **“Emulsified asphalt”** means an emulsion of asphalt cement and water which contains a small amount of an emulsifying agent; a heterogeneous system containing two normally immiscible phases (asphalt and water) in which the water forms the continuous phase of the emulsion, and minute globules of asphalt form the discontinuous phase.
- (4) **“Penetrating prime coat”** means an application of low-viscosity liquid asphalt to an absorbent surface. It is used to prepare an untreated base for an asphalt surface. The prime penetrates the base and plugs the voids, hardens the top, and helps bind it to the overlying asphalt course. It also reduces the necessity of maintaining an untreated base course prior to placing the asphalt pavement.

(b) This Regulation applies to the manufacture and use of cutback asphalts for the purpose of paving or maintaining roads, highways, streets, parking lots, driveways, curbs, sidewalks, airfields (runways, taxiways, and parking aprons), recreational facilities (tennis courts, playgrounds, and trails), and other similar structures.

(c) Cutback asphalt shall not be manufactured, mixed, stored, used, or applied except where:

- (1) Long-life (one month or more) stockpile storage is necessary;
- (2) The use or application at ambient temperatures less than 50°F, as measured at the nearest National Weather Service Field Office or Federal Aviation Administration Station, is necessary;
- (3) The cutback asphalt is to be used solely as a penetrating prime coat;
or
- (4) The user can demonstrate to the Director that there are no volatile organic compound emissions under conditions of normal use.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1979;
Amended Eff. December 1, 1989; January 1, 1985; June 1, 1980.*

2.0932 GASOLINE TRUCK TANKS AND VAPOR COLLECTION SYSTEMS

(a) For the purposes of this Regulation, the following definitions apply:

- (1) **“Bottom filling”** means the filling of a tank truck or stationary storage tank through an opening that is flush with the tank bottom.
- (2) **“Bulk gasoline plant”** means a gasoline storage and distribution facility that has an average daily throughput of less than 20,000 gallons of gasoline and usually receives gasoline from bulk terminals by trailer transport, stores it in tanks, and subsequently dispenses it via account trucks to local farms, businesses, and service stations.
- (3) **“Bulk gasoline terminal”** means:
 - (A) breakout tanks of an interstate oil pipeline facility; or
 - (B) a gasoline storage facility that usually receives gasoline from refineries primarily by pipeline, ship, or barge; delivers gasoline to bulk gasoline plants or to commercial or retail accounts primarily by tank truck; and has an average daily throughput of no less than 20,000 gallons of gasoline.
- (4) **“Certified facility”** means any facility that has been certified under 15A NCAC 2D Rule .0960 - “Certification of Leak Tightness Tester” to perform leak tightness tests on truck tanks.
- (5) **“Gasoline”** means any petroleum distillate having a Reid vapor pressure of 4.0 psia or greater.
- (6) **“Gasoline dispensing facility”** means any site where gasoline is dispensed to motor vehicle gasoline tanks from stationary storage tanks.
- (7) **“Gasoline service station”** means any gasoline dispensing facility where gasoline is sold to the motoring public from stationary storage tanks.
- (8) **“Truck tank”** means the storage vessels of trucks or trailers used to transport gasoline from sources of supply to stationary storage tanks of bulk gasoline terminals, bulk gasoline plants, gasoline dispensing facilities and gasoline service stations.
- (9) **“Truck tank vapor collection equipment”** means any piping, hoses, and devices on the truck tank used to collect and route gasoline vapors in the tank to or from the bulk gasoline terminal, bulk gasoline plant, gasoline dispensing facility or gasoline service station vapor control system or vapor balance system.
- (10) **“Vapor balance system”** means a combination of pipes or hoses that create a closed system between the vapor spaces of an unloading tank and a receiving tank such that vapors displaced from the receiving tank are transferred to the tank being unloaded.
- (11) **“Vapor collection system”** means a vapor balance system or any other system used to collect and control emissions of volatile organic compounds.

(b) This Regulation applies to gasoline truck tanks equipped for vapor collection and to vapor control systems at bulk gasoline terminals, bulk gasoline plants, gasoline dispensing facilities, and gasoline service stations equipped with vapor balance or vapor control systems.

(c) Gasoline Truck Tanks

- (1) Gasoline truck tanks and their vapor collection systems shall be tested annually by a certified facility. The test procedure that shall be used is described in Section 2.2600 of this Article and is according to MCAPCO Regulation 2.0912 - “General Provisions

on Test Methods and Procedures”. The gasoline truck tank shall not be used if it sustains a pressure change greater than 1.0 inch of water in five minutes when pressurized to a gauge pressure of 18 inches of water or when evacuated to a gauge pressure of 6.0 inches of water.

- (2) Each gasoline truck tank that has been certified leak tight, according to Subparagraph (1) of this Paragraph shall display a sticker on the front tank shell.
- (3) There shall be no liquid leaks from any gasoline truck tank.
- (4) Any truck tank with a leak equal to or greater than 100 percent of the lower explosive limit, as detected by a combustible gas detector using the test procedure described in MCAPCO Regulation 2.2615 – “Determination of Leak Tightness and Vapor Leaks” shall not be used beyond 15 days after the leak has been discovered, unless the leak has been repaired and the tank has been certified to be leak tight according to Subparagraph (1) of this Paragraph.
- (5) The owner or operator of a gasoline truck tanks with a vapor collection system shall maintain records of all certification testing and repairs. The records shall identify the gasoline truck tank, the date of the test or repair; and, if applicable, the type of repair and the date of the retest. The records of certification tests shall include:
 - (A) the gasoline truck tank identification number;
 - (B) the initial test pressure and the time of the reading;
 - (C) the final test pressure and the time of the reading;
 - (D) the initial test vacuum and the time of the reading;
 - (E) the final test vacuum and the time of the reading;
 - (F) the date and location of the test;
 - (G) the NC sticker number issued, and
 - (H) the final change in pressure of the internal vapor value test.
- (6) A copy of the most recent certification report shall be kept with the truck tank. The owner or operator of the truck tank shall also file a copy of the most recent certification test with each bulk gasoline terminal that loads the truck tank. The records shall be maintained for at least two years after the date of the testing or repair, and copies of such records shall be made available within a reasonable time to the Director upon written request.

(d) Bulk Gasoline Terminals, Bulk Gasoline Plants Equipped With Vapor Balance or Vapor Control Systems

- (1) The vapor collection system and vapor control system shall be designed and operated to prevent gauge pressure in the truck tank from exceeding 18 inches of water and to prevent a vacuum of greater than six inches of water.
- (2) During loading and unloading operations there shall be:
 - (A) no vapor leakage from the vapor collection system such that a reading equal to or greater than 100 percent of the lower explosive limit at one inch around the perimeter of each potential leak source as detected by a combustible gas detector using the test procedure described in MCAPCO Regulation 2.2615; and
 - (B) no liquid leaks.
- (3) If a leak is discovered that exceeds the limit in Subparagraph (2) of this Paragraph:

- (A) For bulk gasoline plants, the vapor collection system or vapor control system (and therefore the source) shall not be used beyond 15 days after the leak has been discovered, unless the leak has been repaired and the system has been retested and found to comply with Subparagraph (2) of this Paragraph:
- (B) For bulk gasoline terminals, the vapor collection system or vapor control system shall be repaired following the procedures in MCAPCO Regulation – “Bulk Gasoline Terminals”
- (4) The owner or operator of a vapor collection system at a bulk gasoline plant or a bulk gasoline terminal shall monitor, according to MCAPCO Regulations 2.0912 - “General Provisions on Test Methods and Procedures” the vapor collection system at least once per year. If after two complete annual checks no more than 10 leaks are found, the Director may allow less frequent monitoring. If more than 20 leaks are found, the Director may require that the frequency of monitoring be increased.
- (5) The owner or operator of a vapor control systems at bulk gasoline terminals, bulk gasoline plants, gasoline dispensing facilities, and gasoline service stations equipped with vapor balance or vapor control systems shall maintain records of all certification testing and repairs. The record shall identify the vapor collection system, or vapor control systems; the date of the test or repair; and, if applicable, the type of repair and the date of retest.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;*

Amended Eff. June 1, 2008; January 1, 2007; April 1, 2003; August 1, 2002; July 1, 1994; December 1, 1989; January 1, 1985.

2.0933 PETROLEUM LIQUID STORAGE IN EXTERNAL FLOATING ROOF TANKS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Condensate”** means hydrocarbon liquid separated from natural gas which condenses due to changes in the temperature or pressure and remains liquid at standard conditions.
- (2) **“Crude oil”** means a naturally occurring mixture consisting of hydrocarbons or sulfur, nitrogen or oxygen derivatives of hydrocarbons or mixtures thereof which is a liquid in the reservoir at standard conditions.
- (3) **“Custody transfer”** means the transfer of produced crude oil or condensate, after processing or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.
- (4) **“External floating roof”** means a storage vessel cover in an open top tank consisting of a double deck or pontoon single deck which rests upon and is supported by the petroleum liquid being contained and is equipped with a closure seal or seals to close the space between the roof edge and tank shell.
- (5) **“Internal floating roof”** means a cover or roof in a fixed roof tank which rests upon or is floated upon the petroleum liquid being contained, and is equipped with a closure seal or seals to close the space between the roof edge and tank shell.
- (6) **“Liquid-mounted seal”** means a primary seal mounted so the bottom of the seal covers the liquid surface between the tank shell and the floating roof.
- (7) **“Vapor-mounted seal”** means a primary seal mounted so there is an annular vapor space underneath the seal. The annular vapor space is bounded by the bottom of the primary seal, the tank shell, the liquid surface, and the floating roof.
- (8) **“Petroleum liquids”** means crude oil, condensate, and any finished or intermediate products manufactured or extracted in a petroleum refinery.

(b) This Regulation applies to all external floating roof tanks with capacities greater than 950 barrels containing petroleum liquids whose true vapor pressure exceed 1.52 pounds per square inch absolute.

(c) This Regulation does not apply to petroleum liquid storage vessels:

- (1) that have external floating roofs that have capacities less than 10,000 barrels and that are used to store produced crude oil and condensate prior to custody transfer;
 - (2) that have external floating roofs and that store waxy, heavy-pour crudes;
 - (3) that have external floating roofs, and that contain a petroleum liquid with a true vapor pressure less than 4.0 pounds per square inch absolute and:
 - (A) The tanks are of welded construction; and
 - (B) The primary seal is a metallic-type shoe seal, a liquid-mounted foam seal, a liquid-mounted filled type seal, or any other closure device of demonstrated equivalence;
- or
- (4) that have fixed roofs with or without internal floating roofs.

(d) With the exceptions stated in Paragraph (c) of this Regulation, an external floating roof tank subject to this Regulation shall not be used unless:

- (1) The tank has:
 - (A) a continuous secondary seal extending from the floating roof to the tank wall (a rim-mounted secondary),
 - (B) a metallic-type shoe primary seal and a secondary seal from the top of the shoe seal to the tank wall (shoe-mounted secondary seal);
or
 - (C) a closure or other control device demonstrated to have an efficiency equal to or greater than that required under Part (A) or (B) of this Subparagraph.
- (2) The seal closure devices meet the following requirements:
 - (A) There shall be no visible holes, tears, or other openings in the seal or seal fabric;
 - (B) The seal shall be intact and uniformly in place around the circumference of the floating roof between the floating roof and the tank wall;
and
 - (C) For vapor mounted primary seals, the gap-area of gaps exceeding 0.125 inch in width between the secondary seal and the tank wall shall not exceed 1.0 square inch per foot of tank diameter;
- (3) All openings in the external floating roof, except for automatic bleeder vents, rim space vents, and leg sleeves, are:
 - (A) provided with a projection below the liquid surface;
and
 - (B) equipped with covers, seals, or lids that remain in a closed position at all times except when in actual use;
- (4) Automatic bleeder vents are closed at all times except when the roof is floated off or landed on the roof leg supports;
- (5) Rim vents are set to open only when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting;
- (6) Any emergency roof drains are provided with slotted membrane fabric covers or equivalent covers that cover at least 90 percent of the area at the opening;
- (7) Routine visual inspections are conducted once per month;
- (8) For tanks equipped with a vapor-mounted primary seal, the secondary seal gap measurements are made annually in accordance with Paragraph (e) of this Regulation;
and
- (9) Records are maintained in accordance with MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring" and include:
 - (A) reports of the results of inspections conducted under Subparagraph (7) and (8) of this Paragraph;
 - (B) a record of the average monthly storage temperature and the true vapor pressures or Reid vapor pressures of the petroleum liquids stored;
and
 - (C) records of the throughput quantities and types of volatile petroleum liquids for each storage vessel.

(e) The secondary seal gap area is determined by measuring the length and width of the gaps around the entire circumference of the secondary seal. Only gaps equal to or greater than 0.125

inch are used in computing the gap area. The area of the gaps is accumulated to determine compliance with Part (d)(2)(C) of this Regulation.

(f) Notwithstanding the definition of volatile organic compound found in MCAPCO Regulation 2.0901 - “Definitions” Paragraph (28), the owner or operator of a petroleum liquid storage vessel with an external floating roof not equipped with a secondary seal or approved alternative, that contains a petroleum liquid with a true vapor pressure greater than 1.0 pound per square inch shall maintain records of the average monthly storage temperature, the type of liquid, throughput quantities, and the maximum true vapor pressure for all petroleum liquids with a true vapor pressure greater than 1.0 pound per square inch.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. May 1, 2004; July 1, 1994; March 1, 1991; December 1, 1989;
January 1, 1985*

2.0934 COATING OF MISCELLANEOUS METAL PARTS AND PRODUCTS (REPEALED)

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. July 1, 1996; December 1, 1989; January 1,
1985.
Repealed September 1, 2010*

2.0935 FACTORY SURFACE COATING OF FLAT WOOD PANELING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Flat wood paneling coatings”** means wood paneling product that are any interior, exterior or tileboard (class I hardboard) panel to which a protective, decorative, or functional material or layer has been applied.
- (2) **“Hardboard”** is a panel manufactured primarily from inter felted lignocellulosic fibers which are consolidated under heat and pressure in a hot-press.
- (3) **“Tileboard”** means a premium interior wall paneling product made of hardboard that is used in high moisture area of the home.

(b) This Regulation applies to each flat wood paneling coatings source whose volatile organic compounds emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability” at the facilities with flat wood paneling coating applications for the following products:

- (1) class II finishes on hardboard panels;
- (2) exterior siding;
- (3) natural finish hardwood plywood panels;

- (4) printed interior panels made of hardwood, plywood, and thin particleboard; and
- (5) tileboard made of hardboard.

(c) Emissions of volatile organic compounds from any factory finished flat wood product operation subject to this Regulation shall not exceed 2.1 pounds of volatile organic compounds per gallon material excluding water and exempt compounds (2.9 pounds of volatile organic compounds per gallon solids.)

(d) EPA Method 24 (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at surface coating of flat wood paneling facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(e) Any facility that meet definition of Paragraph (b) of this Regulation and which has chosen to use add-on controls for flat wood paneling coating operation rather than the emission limits established in Paragraph (c) of this Regulation shall install control equipment with an overall control efficiency of 90 percent or use a combination of coating and add-on control equipment on a flat wood paneling coating operation to meet limits established in Paragraph (c) of this Regulation.

(f) The owner or operator of any facility subject to this rule shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. September 1, 2010; July 1, 1996; December 1, 1989;
January 1, 1985.

2.0936 GRAPHIC ARTS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. December 1, 1993; December 1, 1989;
January 1, 1985; June 1, 1981.
Repealed Eff. September 1, 2010

2.0937 MANUFACTURE OF PNEUMATIC RUBBER TIRES

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Bead dipping”** means the dipping of an assembled tire bead into a solvent based cement.
- (2) **“Green tires”** means assembled tires before molding and curing have occurred.
- (3) **“Green tire spraying”** means the spraying of green tires, both inside and outside, with release compounds which help remove air from the tire during molding and prevent the tire from sticking to the mold after curing.
- (4) **“Pneumatic rubber tire manufacture”** means the production of passenger car tires, light and medium truck tires, and other tires manufactured on assembly lines.
- (5) **“Tread end cementing”** means the application of a solvent based cement to the tire tread ends.
- (6) **“Undertread cementing”** means the application of a solvent based cement to the underside of a tire tread.

(b) This Regulation applies to undertread cementing, tread end cementing, bead dipping, and green tire spraying operations of pneumatic rubber tire manufacturing.

(c) With the exception stated in Paragraph (d) of this Regulation, emissions of volatile organic compounds from any pneumatic rubber tire manufacturing plant shall not exceed:

- (1) 25 grams of volatile organic compounds per tire from each undertread cementing operation,
- (2) 4.0 grams of volatile organic compounds per tire from each tread end cementing operation,
- (3) 1.9 grams of volatile organic compounds per tire from each bead dipping operation, or
- (4) 24 grams of volatile organic compounds per tire from each green tire spraying operation.

(d) If the total volatile organic compound emissions from all undertread cementing, tread end cementing, bead dipping, and green tire spraying operations at a pneumatic rubber tire manufacturing facility does not exceed 50 grams per tire, Paragraph (c) of this Regulation shall not apply.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. July 1, 1996; December 1, 1989; January 1, 1985.*

2.0938 PERCHLOROETHYLENE DRY CLEANING SYSTEM (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. December 1, 1989; January 1, 1985;
Repealed Eff. July 1, 1998.

2.0939 DETERMINATION OF VOLATILE ORGANIC COMPOUND EMISSIONS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. July 1, 1988; May 1, 1985; December 1, 1984.
Repealed Eff. June 1, 2008

2.0940 DETERMINATION OF LEAK TIGHTNESS AND VAPOR LEAKS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1980;
Amended Eff. July 1, 1988; January 1, 1985.
Repealed Eff. June 1, 2008

2.0941 ALTERNATIVE METHOD FOR LEAK TIGHTNESS (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-215.107(a)(5);
Eff. July 1, 1980.
Amended Eff. December 1, 1989.
Repealed Eff. June 1, 2008

2.0942 DETERMINATION OF SOLVENT IN FILTER WASTE (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.68; 143-215.107(a)(5);
Eff. July 1, 1980.
Repealed Eff. June 1, 2008

2.0943 SYNTHETIC ORGANIC CHEMICAL AND POLYMER MANUFACTURING

(a) For the purposes of this Regulation, the following definitions apply:

- (1) **“Closed vent system”** means a system which is not open to the atmosphere and which is composed of piping, connections, and if necessary, flow inducing devices that transport gas or vapor from a fugitive emission source to an enclosed combustion device or vapor recovery system.
- (2) **“Enclosed combustion device”** means any combustion device which is not open to the atmosphere such as a process heater or furnace, but not a flare.
- (3) **“Fugitive emission source”** means each pump, valve, safety/relief valve, open-ended valve, flange or other connector, compressor, or sampling system.
- (4) **“In gas vapor service”** means that the fugitive emission source contains process fluid that is in the gaseous state at operating conditions.
- (5) **“In light liquid service”** means that the fugitive emission source contains a liquid having:
 - (A) a vapor pressure of one or more of the components greater than 0.3 kilopascals at 20°C, and
 - (B) a total concentration of the pure components having a vapor pressure greater than 0.3 kilopascals at 20°C equal to or greater than 10 percent by weight, and the fluid is a liquid at operating conditions.
- (6) **“Open-ended valve”** means any valve, except safety/relief valves, with one side of the valve seat in contact with process fluid and one side that is open to the atmosphere, either directly or through open piping.
- (7) **“Polymer manufacturing”** means the industry that produces, as intermediates or final products, polyethylene, polypropylene, or polystyrene.
- (8) **“Process unit”** means equipment assembled to produce, as intermediates or final products, polyethylene, polypropylene, polystyrene, or one or more of the chemicals listed in 40 CFR 60.489. A process unit can operate independently if supplied with sufficient feed or raw materials and sufficient storage facilities for the final product.
- (9) **“Quarter”** means a three month period. The first quarter concludes at the end of the last full month during the 180 days following initial start-up.
- (10) **“Synthetic organic chemical manufacturing”** means the industry that produces, as intermediates or final products, one or more of the chemicals listed in 40 CFR 60.489.

(b) This Regulation applies to synthetic organic chemicals manufacturing facilities and polymer manufacturing facilities.

(c) The owner or operator of a synthetic organic chemical manufacturing facility or a polymer manufacturing facility shall not cause, allow or permit:

- (1) any liquid leakage of volatile organic compounds
or
- (2) any gaseous leakage of volatile organic compound of 10,000 ppm or greater from any fugitive emission source.

The owner or operator of these facilities shall control emissions of volatile organic compounds from open-ended valves as described in Paragraph (f) of this Regulation.

(d) The owner or operator shall visually inspect each week every pump in light liquid service. If there are indications of liquid leakage, the owner or operator shall repair the pump within 15 days after detection except as provided in Paragraph (k) of this Regulation.

(e) Using the procedures in Section 2.2600 of this Article, the owner or operator shall monitor each pump, valve, compressor and safety/relief valve in gas/vapor service or in light liquid service for gaseous leaks at least once each quarter. The owner or operator shall monitor safety/relief valves after each overpressure relief to ensure the valve has properly reseated. If a volatile organic compound concentration of 10,000 ppm or greater is measured, the owner or operator shall repair the component within 15 days after detection except as provided in Paragraph (k) of this Regulation. Exceptions to the quarterly monitoring frequency are provided for in Paragraphs (h), (i) and (j) of this Regulation.

(f) The owner or operator shall install on each open-ended valve:

- (1) a cap,
- (2) a blind flange,
- (3) a plug, or
- (4) a second closed valve,

which shall remain attached to seal the open end at all times except during operations requiring process fluid flow through the opened line.

(g) If any fugitive emission source appears to be leaking on the basis of sight, smell, or sound, it shall be repaired within 15 days after detection except as provided in Paragraph (k) of this Regulation.

(h) If after four consecutive quarters of monitoring no more than two percent of the valves in gas/vapor service or in light liquid service are found leaking more than 10,000 ppm of volatile organic compounds, then the owner or operator may monitor valves for gaseous leaks only every third quarter. If the number of these valves leaking more than 10,000 ppm of volatile organic compounds remains at or below two percent, these valves need only be monitored for gaseous leaks every third quarter. However, if more than two percent of these valves are found leaking more than 10,000 ppm of volatile organic compounds, they shall be monitored every quarter until four consecutive quarters are monitored which have no more than two percent of these valves leaking more than 10,000 ppm of volatile organic compounds.

(i) When a fugitive emission source is unsafe to monitor because of extreme temperatures, pressures, or other reasons, the owner or operator of the facility shall monitor the fugitive emission source only when process conditions are such that the fugitive emission source is not operating under extreme conditions. The Director may allow monitoring of these fugitive emission sources less frequently than each quarter, provided they are monitored at least once per year.

(j) Any fugitive emission source more than 12 feet above a permanent support surface may be monitored only once per year.

(k) The repair of a fugitive emission source may be delayed until the next turnaround if the repair is technically infeasible without a complete or partial shutdown of the process unit.

(l) The owner or operator of the facility shall maintain records in accordance with MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring", which shall include:

- (1) identification of the source being inspected or monitored,
- (2) dates of inspection or monitoring,
- (3) results of inspection or monitoring,
- (4) action taken if a leak was detected,
- (5) type of repair made and when it was made,
and
- (6) if the repair were delayed, an explanation as to why.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107 (a)(5);
Eff. May 1, 1985;
Amended Eff. June 1, 2008; March 1, 1991; December 1, 1989.*

2.0944 MANUFACTURE OF POLYETHYLENE, POLYPROPYLENE AND POLYSTYRENE

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"By-product and diluent recovery operation"** means the process that separates the diluent from the by-product (atactic) and purifies and dries the diluent for recycle.
- (2) **"Continuous mixer"** means the process that mixes polymer with anti-oxidants.
- (3) **"Decanter"** means the process that separates the diluent/crude product slurry from the alcohol-water solution by decantation.
- (4) **"Ethylene recycle treater"** means the process that removes water and other impurities from the recovered ethylene.
- (5) **"High-density polyethylene plants using liquid phase slurry processes"** means plants that produce high-density polyethylene in which the product, polyethylene, is carried as a slurry in a continuous stream of process diluent, usually pentane or isobutane.
- (6) **"Neutralizer"** means the process that removes catalyst residue from the diluent/crude product slurry.
- (7) **"Polypropylene plants using liquid phase processes"** means plants that produce polypropylene in which the product, polypropylene, is carried as a slurry in a continuous stream of process diluent, usually hexane.
- (8) **"Polystyrene plants using continuous processes"** means plants which produce polystyrene in which the product, polystyrene, is transferred in a continuous stream in a molten state.

- (9) **“Product devolatilizer system”** means the process that separates unreacted styrene monomer and by-products from the polymer melt.
- (10) **“Reactor”** means the process in which the polymerization takes place.

(b) This Regulation applies to:

- (1) polypropylene plants using liquid phase processes,
- (2) high-density polyethylene plants using liquid phase slurry processes,
and
- (3) polystyrene plants using continuous processes.

(c) For polypropylene plants subject to this Regulation, the emissions of volatile organic compounds shall be reduced by 98 percent by weight or to 20 ppm, whichever is less stringent, from:

- (1) reactor vents,
- (2) decanter vents,
- (3) neutralizer vents,
- (4) by-product and diluent recovery operation vents,
- (5) dryer vents,
and
- (6) extrusion and pelletizing vents.

(d) For high-density polyethylene plants subject to this Regulation, the emissions of volatile organic compounds shall be reduced by 98 percent by weight or to 20 ppm, whichever is less stringent, from:

- (1) ethylene recycle treater vents,
- (2) dryer vents,
and
- (3) continuous mixer vents.

(e) For polystyrene plants subject to this Regulation, the emissions of volatile organic compounds shall not exceed 0.24 pounds per ton of product from the product devolatilizer system.

(f) If flares are used to comply with this Regulation all of the following conditions shall be met:

- (1) Visible emissions shall not exceed five minutes in any two-hour period;
- (2) A flame shall be present;
- (3) If the flame is steam-assisted or air-assisted, the net heating value shall be at least 300 Btu per standard cubic foot. If the flame is non-assisted, the net heating value shall be at least 200 Btu per standard cubic foot;
and
- (4) If the flare is steam-assisted or non-assisted, the exit velocity shall be no more than 60 feet per second. If the flare is air-assisted, the exit velocity shall be no more than $(8.706 + 0.7084 HT)$ feet per second, where HT is the net heating value.

A flare that meets the conditions given in Subparagraphs (1) through (4) of this Paragraph are presumed to achieve 98 percent destruction of volatile organic compounds by weight. If the

owner or operator of the source chooses to use a flare that fails to meet one or more of these conditions, he shall demonstrate to the Director that the flare shall destroy at least 98 percent of the volatile organic compounds by weight. To determine if the specifications for the flare are being met, the owner or operator of a source using the flare to control volatile organic compound emissions shall install, operate, and maintain necessary monitoring instruments and shall keep necessary records as required by MCAPCO Regulation 2.0903 - "Recordkeeping: Reporting: Monitoring".

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. May 1, 1985.

2.0945 PETROLEUM DRY CLEANING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"Cartridge filter"** means perforated canisters containing filtration paper or filter paper, and activated carbon that are used in a pressurized system to remove solid particles and fugitive dyes from soil-laden solvent, together with the piping and ductwork used in the installation of this device.
- (2) **"Containers and conveyors of solvent"** means piping, ductwork, pumps, storage tanks, and other ancillary equipment that are associated with the installation and operation of washers, dryers, filters, stills, and settling tanks.
- (3) **"Dry cleaning"** means a process for the cleaning of textiles and fabric products in which articles are washed in a non-aqueous solution (solvent) and then dried by exposure to a heated air stream.
- (4) **"Dryer"** means a machine used to remove petroleum solvent from articles of clothing or other textile or leather goods, after washing and removing of excess petroleum solvent, together with the piping and ductwork used in the installation of this device.
- (5) **"Perceptible leaks"** means any petroleum solvent vapor or liquid leaks that are conspicuous from visual observation or that bubble after application of a soap solution, such as pools or droplets of liquid, open containers of solvent, or solvent laden waste standing open to the atmosphere.
- (6) **"Petroleum solvent"** means organic material produced by petroleum distillation comprising a hydrocarbon range of eight to 12 carbon atoms per organic molecule that exists as a liquid under standard conditions.
- (7) **"Petroleum solvent dry cleaning"** means a dry cleaning facility that uses petroleum solvent in a combination of washers, dryers, filters, stills, and settling tanks.
- (8) **"Settling tank"** means a container which gravimetrically separates oils, grease, and dirt from petroleum solvent, together with the piping and ductwork used in the installation of the device.
- (9) **"Solvent filter"** means a discrete solvent filter unit containing a porous medium which traps and removes contaminants from petroleum solvent, together with the piping and ductwork used in the installation of this device.
- (10) **"Solvent recovery dryer"** means a class of dry cleaning dryers that employs a

condenser to condense and recover solvent vapors evaporated in a closed-loop stream of heated air, together with the piping and ductwork used in the installation of this device.

- (11) **“Still”** means a device used to volatilize, separate, and recover petroleum solvent from contaminated solvent, together with the piping and ductwork used in the installation of this device.
- (12) **“Washer”** means a machine which agitates fabric articles in a petroleum solvent bath and spins the articles to remove the solvent, together with the piping and ductwork used in the installation of this device.

(b) This Regulation applies to petroleum solvent washers, dryers, solvent filters, settling tanks, stills, and other containers and conveyors of petroleum solvent that are used in petroleum solvent dry cleaning facilities that consume 32,500 gallons or more of petroleum solvent annually.

(c) The owner or operator of a petroleum solvent dry cleaning dryer subject to this Regulation shall:

- (1) limit emissions of volatile organic compounds to the atmosphere to an average of 3.5 pounds of volatile organic compounds per 100 pounds dry weight of articles dry cleaned, or
- (2) install and operate a solvent recovery dryer in a manner such that the dryer remains closed and the recovery phase continues until a final recovered solvent flow rate of 50 milliliters per minute is attained.

(d) The owner or operator of a petroleum solvent filter subject to this Regulation shall:

- (1) reduce the volatile organic compound content in all filter wastes to 1.0 pound or less per 100 pounds dry weight of articles dry cleaned, before disposal and exposure to the atmosphere, or
- (2) install and operate a cartridge filter and drain the filter cartridges in their sealed housings for 8 hours or more before their removal.

(e) The owner or operator of a petroleum solvent dry cleaning facility subject to this Regulation shall inspect the facility every 15 days and shall repair all perceptible leaks within 15 working days after identifying the sources of the leaks. If necessary repair parts are not on hand, the owner or operator shall order these parts within 15 working days and repair the leaks no later than 15 working days following the arrival of the necessary parts. The owner or operator shall maintain records, in accordance with MCAPCO Regulation 2.0903 - “Recordkeeping: Reporting: Monitoring”, of when inspections were made, what was inspected, leaks found, repairs made and when repairs were made.

(f) To determine compliance with Subparagraph (c)(1) of this Regulation, the owner or operator shall use the test method in Section 2.2600 of this Article and shall:

- (1) field calibrate the flame ionization analyzer with propane standards;
- (2) determine in a laboratory, the ratio of the flame ionization analyzer response to a given parts per million by volume concentration of propane to the response to the same parts

- per million concentration of the volatile organic compounds to be measured;
- (3) determine the weight of volatile organic compounds vented to the atmosphere by:
 - (A) multiplying the ratio determined in Subparagraph (2) of this Paragraph by the measured concentration of volatile organic compound gas (as propane) as indicated by the flame ionization analyzer response output record,
 - (B) converting the parts per million by volume value calculated in Part (A) of this Subparagraph into a mass concentration value for the volatile organic compounds present,
and
 - (C) multiplying the mass concentration value calculated in Part (B) of this Subparagraph by the exhaust flow rate; and
 - (4) Calculate and record the dry weight of articles dry cleaned.

The test shall be repeated for normal operating conditions that encompass at least 30 dryer loads that total not less than 4,000 pounds dry weight and that represent a normal range of variation in fabrics, solvents, load weights, temperatures, flow rates, and process deviations.

(g) To determine compliance with Subparagraph (c)(2) of this Regulation, the owner or operator shall verify that the flow rate of recovered solvent from the solvent recovery dryer at the termination of the recovery phase is no greater than 50 milliliters per minute. This one-time procedure shall be conducted for a duration of not less than two weeks during which not less than 50 percent of the dryer loads shall be monitored for their final recovered solvent flow rate. Near the end of the recovery cycle, the flow of recovered solvent shall be diverted to a graduated cylinder. The cycle shall continue until the minimum flow of solvent is 50 milliliters per minute. The type of articles cleaned and the total length of the cycle shall be recorded.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. May 1, 1985;
Amended Eff. June 1, 2008

2.0946 COMPLIANCE SCHEDULE: GASOLINE HANDLING (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. May 1, 1990;
Repealed Eff. April 1, 1997.

2.0947 MANUFACTURE OF SYNTHESIZED PHARMACEUTICAL PRODUCTS

- (a) For the purposes of this Regulation, the following definitions apply:
 - (1) **“Production equipment exhaust system”** means a device for collecting and directing out of the work area fugitive emissions of volatile organic compounds from reactor openings, centrifuge openings, and other vessel openings for the purpose of protecting

workers from excessive exposure to volatile organic compounds.

- (2) **“Synthesized pharmaceutical manufacturing”** means manufacture of pharmaceutical products by chemical synthesis.

(b) This Regulation applies to synthesized pharmaceutical products manufacturing facilities.

(c) The owner or operator of a synthesized pharmaceutical products manufacturing facility shall control the emissions of volatile organic compounds from:

- (1) reactors, distillation operations, crystallizers, centrifuges, and vacuum dryers that have the potential to emit 15 pounds per day or more of volatile organic compounds with surface condensers that meet the requirements of Paragraph (e) of this Regulation or equivalent controls;
- (2) air dryers and production equipment exhaust system by reducing emissions of volatile organic compounds:
 - (A) by 90 percent if they are 330 pounds per day or more; or
 - (B) to 33 pounds per day if they are less than 330 pounds per day.
- (3) storage tanks by:
 - (A) providing a vapor balance system or equivalent control that is at least 90 percent effective in reducing emissions from truck or railcar deliveries to storage tanks with capacities greater than 2,000 gallons that store volatile organic compounds with a vapor pressure greater than 4.1 pounds per square inch at 68°F;
and
 - (B) installing pressure/vacuum conservation vents, which shall be set ± 0.8 inches of water unless a more effective control system is used, on all storage tanks that store volatile organic compounds with a vapor pressure greater than 1.5 pounds per square inch at 68°F;
- (4) centrifuges containing volatile organic compounds, rotary vacuum filters processing liquid containing volatile organic compounds, and other filters having an exposed liquid surface where the liquid contains volatile organic compounds by enclosing those centrifuges and filters that contain or process volatile organic compounds with a vapor pressure of 0.5 pounds per square inch or more at 68°F; and
- (5) in-process tanks by installing covers, which shall remain closed except when production, sampling, maintenance, or inspection procedures require operator access.

(d) The owner or operator of a synthesized pharmaceutical products manufacturing facility shall repair as expeditiously as possible all leaks from which liquid volatile organic compounds can be seen running or dripping. This repair must take place at least within 15 days after which said leak is discovered unless the leaking component cannot be repaired before the process is shutdown in which case the leaking component must be repaired before the process is restarted.

(e) If surface condensers are used to comply with Subparagraph (c)(1) of this Regulation, the condenser outlet temperature shall not exceed:

- (1) -13°F when condensing volatile organic compounds of vapor pressure

- greater than 5.8 psi at 68°F;
- (2) 5°F when condensing volatile organic compounds of vapor pressure greater than 2.9 psi at 68°F;
 - (3) 32°F when condensing volatile organic compounds of vapor pressure greater than 1.5 psi at 68°F;
 - (4) 50°F when condensing volatile organic compounds of vapor pressure greater than 1.0 psi at 68°F; or
 - (5) 77°F when condensing volatile organic compounds of vapor pressure greater than 0.5 psi at 68°F.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1994.

2.0948 VOC EMISSIONS FROM TRANSFER OPERATIONS

(a) This Regulation applies to operations that transfer volatile organic compounds from a storage tank to truck-tanks, trailers, or railroad tank cars that are not covered by MCAPCO Regulation 2.0926 - “Bulk Gasoline Plants”, 2.0927 - “Bulk Gasoline Terminals”, or 2.0928 - “Gasoline Stations Stage I”.

(b) The owner or operator of a source to which this Regulation applies shall not load in any one day more than 20,000 gallons of any volatile organic compound with a vapor pressure of 1.5 pounds per square inch or greater under actual conditions into any truck-tank, trailer, or railroad tank car from any loading facility unless the loading uses submerged loading through boom loaders that extend down into the compartment being loaded or by other methods that are at least as efficient based on source testing or engineering calculations.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1994.
Amended Effective July 1, 2000.

2.0949 STORAGE OF MISCELLANEOUS VOLATILE ORGANIC COMPOUNDS

(a) This Regulation applies to the storage of volatile organic compounds in stationary tanks, reservoirs, or other containers with a capacity greater than 50,000 gallons that are not covered by MCAPCO Regulation 2.0925 - “Petroleum Liquid Storage in Fixed Roof Tanks” or 2.0933 - “Petroleum Liquid Storage in External Floating Roof Tanks”.

(b) The owner or operator of any source to which this Regulation applies shall not place, store, or hold in any stationary tank, reservoir, or other container with a capacity greater than 50,000 gallons, any liquid volatile organic compound that has a vapor pressure of 1.5 pounds per square inch absolute or greater under actual storage conditions unless such tank, reservoir, or other container:

- (1) is a pressure tank capable of maintaining working pressures sufficient at all times to prevent vapor gas loss into the atmosphere; or
- (2) is designed and equipped with one of the following vapor loss control devices:
 - (A) a floating pontoon, double deck type floating roof or internal pan type floating roof equipped with closure seals to enclose any space between the cover's edge and compartment wall; this control equipment shall not be permitted for volatile organic compounds with a vapor pressure of 11.0 pounds per square inch absolute or greater under actual storage conditions; all tank gauging or sampling devices shall be gas-tight except when tank gauging or sampling is taking place;
 - (B) a vapor recovery system or other equipment or means of air pollution control that reduces the emission of organic materials into the atmosphere by at least 90 percent by weight; all tank gauging or sampling devices shall be gas-tight except when tank gauging or sampling is taking place.

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1994.
Amended Eff. July 1, 2000.

2.0950 INTERIM STANDARDS FOR CERTAIN SOURCE CATEGORIES (REPEALED)

History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1994;
Amended Eff. May 1, 1995;
Repealed Eff. July 1, 2000.

2.0951 RACT FOR SOURCES OF VOLATILE ORGANIC COMPOUNDS

(a) Facilities required to install RACT pursuant to MCAPCO Regulation 2.0902 – “Applicability” shall determine the emissions control level according to this Regulation. If the only other applicable emissions control Regulation for the facility in this Section is MCAPCO Regulation 2.0958 – “Work Practices For Sources Of Volatile Organic Compounds” than both this Regulation and MCAPCO Regulation 2.0958 apply.

(b) This Regulation does not apply to architectural or maintenance coating.

(c) The owner or operator of any facility to which this Regulation applies shall comply by either of the following:

- (1) install and operate reasonable available control technology as defined by category specific emission standards defined in this Section,

- or
- (2) install and operate reasonably available control technology demonstrated to the Director and the U.S. Environmental Protection Agency to advance attainment.

(d) If the owner or operator of a facility chooses to install reasonable available control technology under Paragraph (c)(2) of this Regulation, the owner or operator shall submit:

- (1) the name and location of the facility;
- (2) information identifying the source for which a reasonable available control technology limitation or standard is being proposed;
- (3) a demonstration that shows the proposed reasonable available control technology limitation or standard satisfies the requirements for reasonable available control technology; and
- (4) a proposal for demonstrating compliance with the proposed reasonable control technology limitation or standard.

State History Note:

Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);

Eff. July 1, 1994;

Amended Eff. May 1, 2013, September 1, 2010; July 1, 2000; July 1, 1996.

MCAQ History Note:

Eff. June 17, 2014

2.0952 PETITION FOR ALTERNATIVE CONTROLS FOR RACT

(a) This Regulation applies to all sources covered under this Section.

(b) If the owner or operator of any source of volatile organic compounds subject to the requirements of this Section can demonstrate that compliance with Regulations in this Section would be technologically or economically infeasible, he may petition the Director of the Department to allow the use of alternative operational or equipment controls for the reduction of volatile organic compound emissions. Petition shall be made for each source to the Director.

(c) The petition shall contain:

- (1) the name and address of the company and the name and telephone number of a company officer over whose signature the petition is submitted;
- (2) a description of all operations conducted at the location to which the petition applies and the purpose that the volatile organic compound emitting equipment serves within the operations;
- (3) reference to the specific operational and equipment controls under the Regulations of this Section for which alternative operational or equipment controls are proposed;
- (4) a description of the proposed alternative operational or equipment controls, the

- magnitude of volatile organic compound emission reduction that will be achieved, and the quantity and composition of volatile organic compounds that will be emitted if the alternative operational or equipment controls are instituted;
- (5) a plan, which will be instituted in addition to the proposed alternative operational or equipment controls, to reduce, where technologically and economically feasible, volatile organic compound emissions from other source operations at the facility, further than that required under the Regulations of this Section, if these sources exist at the facility, such that aggregate volatile organic compound emissions from the facility will in no case be greater through application of the alternative control than would be allowed through conformance with the Regulations of this Section;
 - (6) a schedule for the installation or institution of the alternative operational or equipment controls in conformance with MCAPCO Regulation 2.0909 - "Compliance Schedules for Sources in New Non-Attainment Areas", as applicable;
- and
- (7) certification that emissions of all other air contaminants from the subject source are in compliance with all applicable local, state and federal laws and regulations.

The petition may include a copy of the permit application and need not duplicate information in the permit application.

(d) The Director shall approve a petition for alternative control if:

- (1) The petition is submitted in accordance with Paragraph (d) of this Regulation;
- (2) The Director determines that the petitioner cannot comply with the Regulations in question because of technological or economical infeasibility;
- (3) All other air contaminant emissions from the facility are in compliance with, or under a schedule for compliance as expeditiously as practicable with, all applicable local, state, and federal regulations and;
- (4) The petition contains a schedule for achieving and maintaining reduction of volatile organic compound emissions to the maximum extent feasible and as expeditiously as practicable.

(e) When controls different from those specified in the appropriate emission standards in this Section are approved by the Director the permit shall contain a condition stating such controls.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 1994;*

*Amended Eff. September 1, 2010; January 1, 2009; April 1, 2003; July 1, 1995;
May 1, 1995.*

2.0953 VAPOR RETURN PIPING FOR STAGE II VAPOR RECOVERY (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a); 150B-21.6;

Eff. July 1, 1994;
Amended Eff. April 1, 2003; July 1, 1998; July 1, 1996.
Repealed Eff. January 1, 2009

2.0954 STAGE II VAPOR RECOVERY (REPEALED)

History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a); 150B-21.6;
Eff. May 1, 1995;
Amended Eff. April 1, 2003; April 1, 1997; July 1, 1996;
April 1, 1996; May 1, 1995.
Repealed Eff. January 1, 2009

2.0955 THREAD BONDING MANUFACTURING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Capture hoods”** means any device designed to remove emissions from the solution bath tray areas during the manufacturing process.
- (2) **“Curing”** means exposing coated threads to high temperatures in an oven until the nylon solution mixture hardens (vaporizing the solvents) and bonds to the threads.
- (3) **“Day tanks”** means holding tanks that contain nylon solution mixture ready for use.
- (4) **“Drying ovens”** means any apparatus through which the coated threads are conveyed while curing.
- (5) **“Enclose”** means to construct an area within the plant that has a separate ventilation system and is maintained at a slightly negative pressure.
- (6) **“Fugitive emissions”** means emissions that cannot be collected and routed to a control system.
- (7) **“Nylon thread coating process”** means a process in which threads are coated with a nylon solution and oven cured.
- (8) **“Permanent label”** means a label that cannot be easily removed or defaced.
- (9) **“Polyester solution mixture”** means a mixture of polyester and solvents which is used for thread coating.
- (10) **“Storing”** means reserving material supply for future use.
- (11) **“Thread bonding manufacturing”** means coating single or multi-strand threads with plastic (nylon or polyester solution mixture) to impart properties such as additional strength and durability, water resistance, and moth repellency.
- (12) **“Transporting”** means moving material supply from one place to another.

(b) This Regulation applies in accordance with MCAPCO Regulation 2.0902 - “Applicability” to any thread bonding manufacturing facility with total uncontrolled exhaust emissions from nylon thread coating process collection hoods and drying ovens of volatile organic compounds (VOC) equal to or greater than 100 tons per year.

(c) Annual VOC emissions from each nylon thread coating process shall be determined by

multiplying the hourly amount of VOC consumed by the total scheduled operating hours per year.

(d) Emissions from each nylon thread coating process subject to this Regulation shall be reduced:

- (1) by at least 95 percent by weight,
or
- (2) by installing a thermal incinerator with a temperature of at least 1600° F and a residence time of at least 0.75 seconds.

(e) The owner or operator of any thread bonding manufacturing facility shall:

- (1) enclose the nylon thread coating process area of the plant to prevent fugitive emissions from entering other plant areas;
- (2) store all VOC containing materials in covered tanks or containers;
- (3) ensure that equipment used for transporting or storing VOC containing material does not leak and that all lids and seals used by such equipment are kept in the closed position at all times except when in actual use;
- (4) not cause or allow VOC containing material to be splashed, spilled, or discarded in sewers;
- (5) hold only enough nylon solution mixture in the day tanks to accommodate daily process times measured in hours;
and
- (6) place permanent and conspicuous labels on all equipment affected by Subparagraphs (3) through (5) of this Paragraph summarizing handling procedures described in Subparagraphs (3) through (5) of this Paragraph for VOC contaminated materials at the nylon thread coating process.

(f) The owner or operator of a thread bonding manufacturing facility shall notify the Director within 30 days after the calculated annual emissions of VOC from nylon thread coating processes equal or exceed 100 tons per year. The owner or operator shall submit within six months after such calculation a permit application including a schedule to bring the facility into compliance with this Regulation.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a);
Eff. May 1, 1995.*

2.0956 GLASS CHRISTMAS ORNAMENT MANUFACTURING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Coating”** means the application of a layer of material, either by dipping or spraying, in a relatively unbroken film onto glass Christmas ornaments.
- (2) **“Curing ovens”** means any apparatus through which the coated glass Christmas ornaments are conveyed while drying.
- (3) **“Glass Christmas ornament”** means any glass ornament that is coated with a decorative exterior and is traditionally hung on Christmas trees.

- (4) **“Glass Christmas ornament manufacturing facility”** means a facility that coats glass Christmas ornaments through the process of interior coating or exterior coating that uses either mechanical or hand-dipping methods, drying (curing), cutting, and packaging operations.
- (5) **“Mechanical coating lines”** means equipment that facilitates mechanized dipping or spraying of a coating onto glass Christmas ornaments in which the neck of each ornament is held mechanically during the coating operation.
- (6) **“Solvent-borne coating”** means a coating that uses organic solvents as an ingredient.

(b) This Regulation applies in accordance with MCAPCO Regulation 2.0902 - “Applicability” to any curing ovens servicing the mechanical coating lines in the coating of glass Christmas ornaments at glass Christmas tree ornament manufacturing facilities with potential volatile organic compound (VOC) emissions of 100 tons per year or more.

(c) This Regulation does not apply to glass Christmas ornament manufacturing facilities that do not use solvent-borne coating materials.

(d) Emissions of VOC from each curing oven shall be reduced by at least 90 percent by weight.

(e) If the owner or operator of a facility subject to this Regulation chooses to use low VOC content, solvent-borne coatings to reduce emissions, the emission reduction from the use of these coatings shall be equivalent to that achieved using add-on controls.

(f) The owner or operator of a Christmas tree ornament manufacturing facility shall notify the Director within 30 days after the calculated annual emissions of VOC from the facility equal or exceed 100 tons per year. The owner or operator shall submit within six months after such calculation a permit application including a schedule to bring the facility into compliance with this Regulation.

History Note: *Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a);
Eff. May 1, 1995.*

2.0957 COMMERCIAL BAKERIES

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **“Baking Oven”** means an oven used at any time for the purpose of baking yeast-leavened products, including bread and rolls.
- (2) **“Commercial Bakery”** means an establishment where bread and baked goods are produced.

(b) This Regulation applies in accordance with MCAPCO Regulation 2.0902 - “Applicability” to any baking oven at a commercial bakery with potential volatile organic compound (VOC) emissions of 100 tons per year or more . Daily volatile organic compound emissions shall be

determined according to the calculation procedures in Paragraph (d) of this Regulation.

- (c) Emissions of VOC from baking ovens subject to this Regulation shall be reduced by at least:
- (1) 90 percent by weight, or
 - (2) 60 percent by weight, if biofiltration is used.

(d) Daily volatile organic compound emissions from each commercial baking oven shall be determined according to the following:

$$\text{EtOH} = 0.40425 + 0.444585[(Y \times T) + (S \times t)]$$

where:

EtOH =	pounds ethanol per ton of baked bread.
Y =	baker's percent yeast in sponge to the nearest tenth of a percent.
T =	total time of fermentation in hours to the nearest tenth of an hour.
S =	baker's percent of yeast added to dough to the nearest tenth of a percent.
t =	proof time + floor time in hours to the nearest tenth of an hour.

(e) The owner or operator of a commercial bakery shall notify the Director within 30 days after the calculated emissions of VOC from the bakery equal or exceed 100 tons per year. The owner or operator shall submit within six months after such calculation a permit application including a schedule to bring the facility into compliance with this Regulation.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a);
Eff. May 1, 1995.*

2.0958 WORK PRACTICES FOR SOURCES OF VOLATILE ORGANIC COMPOUNDS

(a) This Regulation applies to all facilities that use volatile organic compounds as solvents, carriers, material processing media, or industrial chemical reactants, or in other similar uses or that mix, blend, or manufacture volatile organic compounds, or emit volatile organic compounds as a product of chemical reactions.

(b) This Regulation does not apply to:

- (1) architectural or maintenance coating, or
- (2) sources subject to 40 CFR Part 63, Subpart JJ (National Emissions Standards For Wood Furniture Manufacturing).

(c) The owner or operator of any facility subject to this Regulation shall:

- (1) store all material, including waste material, containing volatile organic compounds in containers covered with a tightly fitting lid that is free of cracks, holes, or other defects, when not in use,

- (2) clean up spills as soon as possible following proper safety procedures,
- (3) store wipe rags in closed containers,
- (4) not clean sponges, fabric, wood, paper products, and other absorbent materials,
- (5) drain solvents used to clean supply lines and other coating equipment into closable containers and close containers immediately after each use,
- (6) clean mixing, blending, and manufacturing vats and containers by adding cleaning solvent, closing the vat or container before agitating the cleaning solvent. The spent cleaning solvent shall then be poured into a closed container.

(d) When cleaning parts, the owner or operator of any facility subject to this Regulation shall:

- (1) flush parts in the freeboard area,
- (2) take precautions to reduce the pooling of solvent on and in the parts,
- (3) tilt or rotate parts to drain solvent and allow a minimum of 15 seconds for drying or until all dripping has stopped, whichever is longer,
- (4) not fill cleaning machines above the fill line,
- (5) not agitate solvent to the point of causing splashing.

(e) The owner or operator of a source on which a control device has been installed to comply with MCAPCO Regulation 2.0518 - "Miscellaneous Volatile Organic Compound Emissions" Paragraph (d) shall continue to maintain and operate the control device unless the Director determines that the removal of the control device shall not cause or contribute to a violation of the ozone ambient air quality standard (MCAPCO Regulation 2.0405 - "Ozone").

(f) The owner or operator of a source that has complied with MCAPCO 2.0518 - "Miscellaneous Volatile Organic Compound Emissions" by complying with a Regulation in this Section, shall continue to comply with that Regulation unless the Director determines that if the source ceases to comply with that Regulation, it shall not cause or contribute to a violation of the ozone ambient air quality standard (MCAPCO Regulation 2.0405 - "Ozone").

(g) All sources at a facility subject to this Regulation shall be permitted unless they are exempted from permitting by MCAPCO Regulation 1.5211 - "Applicability".

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. July 1, 2000.*

2.0959 PETITION FOR SUPERIOR ALTERNATIVE CONTROLS

(a) This Regulation applies to all sources covered under this Section.

(b) If the owner or operator of any source of volatile organic compounds subject to the requirements of this Section, can demonstrate that an alternative operational or equipment control is superior to the required control, he may petition the Director to allow the use of alternative operational or equipment controls for the reduction of volatile organic compound emissions. The petition shall be made for each source to the Director.

(c) The petition shall contain:

- (1) the name and address of the company and the name and telephone number of a company officer over whose signature the petition is submitted;
- (2) a description of all operations conducted at the location to which the petition applies and the purpose that the volatile organic compound emitting equipment serves within the operations;
- (3) reference to the specific operational and equipment controls under the Regulations of this Section for which alternative operational or equipment controls are proposed;
- (4) a detailed description of the proposed alternative operational or equipment controls, the magnitude of volatile organic compound emission reduction that will be achieved, and the quantity and composition of volatile organic compounds that will be emitted if the alternative operational or equipment controls are instituted; and
- (5) certification that emissions of all other air contaminants from the subject source are in compliance with all applicable local, state and federal laws and regulations.

The petition may include a copy of the permit application and need not duplicate information in the permit application.

(d) The Director shall approve a petition for alternative control if:

- (1) The petition is submitted in accordance with Paragraph (c) of this Regulation;
- (2) The Director determines that the proposed alternative operational or equipment control is superior to the required controls;
- (3) All other air contaminant emissions from the facility are in compliance with, or under a schedule for compliance as expeditiously as practicable with, all applicable local, state, and federal regulations; and
- (4) The petition contains a schedule for achieving and maintaining reduction of volatile organic compound emissions to the maximum extent feasible and as expeditiously as practicable.

(e) When controls different from those specified in the appropriate emission standards in this Section are approved by the Director, the permit shall contain a condition stating such controls.

*History Note: Statutory Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. April 1, 2003.*

2.0961 OFFSET LITHOGRAPHIC PRINTING AND LETTERPRESS PRINTING

(a) For the purposes of this Regulation, definitions listed in this Paragraph and MCAPCO Regulations 2.0101 – “Definitions”, 2.0901 – “Definitions” shall apply:

- (1) **“Composite partial vapor pressure”** means the sum of the partial pressure of the compounds defined as volatile organic compounds. Volatile organic compounds composite partial vapor pressure is calculated as follows:

$$PP_c = \sum_{i=1}^n \frac{(W_i)(VP_i)/MW_i}{\frac{W_w}{MW_w} + \frac{W_c}{MW_c} + \sum_{i=1}^n \frac{W_i}{MW_i}}$$

Where:

W_i = Weight of the “i” volatile organic compound, in grams

W_w = Weight of water, in grams

W_c = Weight of exempt compound, in grams

MW_i = Molecular weight of the “i” volatile organic compound, in g/g-mole

MW_w = Molecular weight of water, in g/g-mole

MW_c = Molecular weight of exempt compound, in g/g-mole

PP_c = Volatile organic compounds composite partial vapor pressure at 20 degrees Celsius (68 degrees Fahrenheit), in mm Hg

VP_i = Vapor pressure of the “i” volatile organic compound at 20 degrees Celsius (68 degrees Fahrenheit), in mm Hg

- (2) **"First installation date"** means the actual date when this control device becomes operational. This date does not change if the control device is later redirected to a new press.
- (3) **"Fountain solution"** means water-based solution that applies to lithographic plate to render the non-image areas unresponsive to the ink.
- (4) **"Heatset"** means any operation in which heat is required to evaporate ink oils from the printing ink, excluding ultraviolet (UV) curing, electron beam curing and infrared drying.
- (5) **"Letterpress printing"** means a printing process in which the image area is raised relative to the non-image area and the paste ink is transferred to the substrate directly from the image surface.
- (6) **"Non-heatset"** means a lithographic printing process where the printing inks are set by absorption or oxidation of the ink oil, not by evaporation of the ink oils in a dryer. For the purposes of this rule, use of an infrared heater or printing conducted using ultraviolet-cured or electron beam-cured inks is considered non-heatset.
- (7) **"Offset lithography"** means a printing process that uses sheet-fed or web method of press feeding and transfers ink from the lithographic plate to a rubber-covered intermediate "blanket" cylinder and then from the blanket cylinder to the substrate.
- (8) **"Press"** means a printing production assembly composed of one or more units used to produce a printed substrate including any associated coating, spray powder application, heatset web dryer, ultraviolet or electron beam curing units, or infrared heating units.
- (9) **"Sheet-fed printing"** "Sheet-fed printing" means offset lithographic printing

when individual sheets of paper or other substrate are fed to the press.

- (10) **"Web printing"** means offset lithographic printing when continuous rolls of substrate material are fed to the press and rewound or cut to size after printing.

(b) This Regulation applies to any offset lithographic and any letterpress printing operations sources that are not cover by Subparagraph (c)(1) of MCAPCO Regulation 2.0966 – “Paper, Film and Foil Coating” whose emissions of volatile organic compounds exceeds:

- (1) the threshold established in Paragraphs (b) and (f) of MCAPCO Regulation 2.0902 – “Applicability”; or
- (2) an equivalent level of three tons per twelve-consecutive month rolling period.

(c) Volatile organic compounds content in the fountain solution for on-press (as-applied) heatset web offset lithographic printing meet one of the following requirements or equivalent level of control as determined in permit conditions:

- (1) contain 1.6 percent alcohol or less, by weight, as applied in the fountain solution;
- (2) contain three percent alcohol or less, by weight, on-press (as-applied) in the fountain solution if the fountain solution is refrigerated to below 60 degrees Fahrenheit; or
- (3) contain five percent alcohol substitute or less, by weight, on-press (as-applied) and no alcohol in the fountain solution.

(d) Volatile organic compounds content in the fountain solution ~~from~~ for on-press (as-applied) sheet-fed lithographic printing meet one of the following requirements or equivalent level of control as determined in permit conditions:

- (1) contain five percent alcohol or less, by weight, on-press (as-applied) in the fountain solution;
- (2) contain 8.5 percent alcohol or less, by weight, on-press (as-applied) in the fountain solution if the fountain solution is refrigerated to below 60 degrees Fahrenheit; or
- (3) contain five percent alcohol substitute or less, by weight, on-press (as-applied) and no alcohol in the in the fountain solution.

(e) Volatile organic compounds content emissions from fountain solution for non-heatset web offset lithographic printing shall not exceed five percent alcohol substitute (by weight) on-press (as applied) and contain no alcohol in the fountain solution.

(f) An owner or operator of an individual web offset lithographic printing press dryer or letterpress-printing heatset press subject to this Regulation that emits 25 or more tons per year potential emissions of volatile organic compounds shall:

- (1) use an enforceable limitation on potential emissions to keep individual heatset press below 25 tons per year potential to emit volatile organic compounds (petroleum ink oil), which can be achieved by using inks and coatings that contain less than 31.25 tons per year volatile organic compound (petroleum ink oil) where 20 percent retention factor of petroleum ink oil applies, or by using other methods

- established by permit conditions; or
- (2) use an add-on control system that meets one of the following requirements;
 - (A) reduce volatile organic compound emissions from each dryer by at least 90 percent volatile organic compounds control efficiency established by procedures defined in Paragraph (h) of this Regulation for a control device from heatset dryers at whose first installation date was prior to July 1, 2010, at facilities with potential to emit 100 tons or more of volatile organic compounds per year, and prior to May 1, 2013, at facilities with potential to emit less than 100 tons of volatile organic compounds per year; or
 - (B) reduce volatile organic compound emissions from each dryer by at least 95 percent volatile organic compounds control efficiency established by procedures defined in Paragraph (h) of this Regulation for a control device from heatset dryers at whose first installation date was on, or after, July 1, 2010, at facilities with potential to emit 100 tons or more of volatile organic compounds per year, and on, or after, May 1, 2013, at facilities with potential to emit less than 100 tons of volatile organic compounds per year; or
 - (C) maintain a maximum volatile organic compound outlet concentration of 20 parts per million by volume (ppmv), as hexane (C₆H₁₄) on a dry basis.
- (g) The control limits established in:
- (1) Paragraph (d) shall not be applied to sheet-fed presses with maximum sheet size 11x 17 inches or smaller;
 - (2) Paragraphs (c), (d), and (e), shall not be applied to any press with total fountain solution reservoir of less than one gallon;
 - (3) Paragraph (f) shall not be applied to a press with a potential to emit below 25 tons per year used for book printing, and presses with maximum web width of 22 inches or less; and
 - (4) Paragraph (f)(2) shall not be applied to a heatset press used for book printing, or to a heatset press with maximum web width of 22 inches or less.
- (h) If the owner or operator of a printing press is required by permit conditions to determine:
- (1) the volatile organic compound content, the EPA Test Method 24 or approved alternative methods shall be used;
 - (2) the control efficiency by measuring volatile organic compounds at the control device inlet and outlet, the EPA test Methods 18, 25 and 25A, or approved alternate methods shall be used.
- (i) All test methods defined in Paragraph (h) of this Regulation shall be conducted at typical operating conditions and flow rates.
- (j) The owner or operator of any facility subject to this Regulation shall demonstrate compliance with RACT applicability requirements by calculation volatile organic compound emissions and

keep records of the basis of the calculations required by MCAPCO Regulations 2.0605 – “General Recordkeeping and Reporting Requirements” and 2.0903 – “Recordkeeping: Reporting: Monitoring”. Volatile organic compound emissions from offset lithographic printing and letterpress printing shall be determined by permit condition requirements or by using the following retention and capture efficiency factors:

- (1) the retention factors are:
 - (A) 20 percent for heatset petroleum ink oils;
 - (B) 100 percent for heatset vegetable ink oils;
 - (C) 95 percent for sheet-fed and coldest web petroleum ink oils;
 - (D) 100 percent for sheet-fed and coldest web vegetable ink oils.
- (2) the retention factor is 50 percent for low volatile organic compounds composite vapor pressure cleaning materials in shop towels where:
 - (A) volatile organic compounds composite vapor pressure of the cleaning material is less than 10 mm Hg at 20°C; and
 - (B) cleaning materials and used shop towels are kept in closed containers.
- (3) carryover (capture) factors of volatile organic compounds from automatic blanket wash and fountain solution to offset lithographic heatset dryers are:
 - (A) 40 percent VOC carryover (capture) for automatic blanket washing when the volatile organic compounds composite vapor pressure of the cleaning material is less than 10 mm Hg at 20°C;
 - (B) 70 percent VOC carryover (capture) factor for alcohol substitutes in fountain solutions.
- (4) capture efficiency for volatile organic compounds (petroleum ink oil) from oil-based paste inks and oil-based paste varnishes (coatings) in heatset web offset lithographic presses and heatset web letterset presses shall be demonstrated by showing that the dryer is operated at negative pressure, the capture efficiency for VOC from the heatset lithographic inks and varnishes (coatings) formulated with low volatility ink oils is 100 percent of the VOC (ink oils) volatilized in the dryer. Capture efficiency test is not required in this situation.

(k) Except as specified in this Paragraph, all cleaning materials used for cleaning a press, press parts, or to remove dried ink from the areas around the press shall meet one of the following requirements:

- (1) the volatile organic compounds content shall be less than 70 percent by weight; or
- (2) composite partial vapor pressure of volatile organic compounds shall be less than 10 mm Hg at 20°C;
- (3) no more than 110 gallons per year of cleaning materials that do not meet the requirements of Subparagraph (1) or (2) of this Paragraph shall be used during any consecutive twelve month period.

(l) The owner or operator of any facility subject to this Regulation shall maintain the following records for a minimum of five years:

- (1) parametric monitoring for processes and control devices as determined and at the frequency specified in the permit or by Paragraph (f) of this Regulation; and

- (2) the total amount of each individual or class of fountain solution and ink used monthly for the printing operations and the percentage of volatile organic compounds, alcohol, and alcohol substitute as applied in it; and
- (3) the total amount of each individual or class of cleaning solutions used monthly with vapor pressure and the percentage of volatile organic compounds as applied in it; and
- (4) the total amount of cleaning solutions used monthly with vapor pressures and the percent of volatile organic compounds as applied which does not meet the vapor pressure or percentage of volatile organic compounds requirements of Paragraph (k) of this Regulation; and
- (5) temperature of fountain solutions for lithographic printing presses using alcohol at the frequency specified in the permit; and
- (6) any other parameters required by the permit in accordance with MCAPCO Regulations 2.0605 – “General Recordkeeping and Reporting Requirements” and 2.0903 – “Recordkeeping: Reporting: Monitoring”.

(m) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

State History Note:

Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);

Eff. September 1, 2010.

Amended Eff. May 1, 2013

MCAQ History Note:

Eff. June 17, 2014

2.0962 INDUSTRIAL CLEANING SOLVENTS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"Organic solvent"** means a liquid hydrocarbon, such as methyl ethyl ketone or toluene, used to dissolve paints, varnishes, grease, oil, or other hydrocarbons.
- (2) **"Solvent cleaning"** means the process of removing the excess penetrant from the surface or a part by wiping, flushing, or spraying with a solvent for the penetrant.
- (3) **"Wipe cleaning"** means the method of cleaning that utilizes a material such as a rag wetted with a solvent prior to a physical rubbing process to remove contaminants from surfaces.

(b) This Regulation applies, with exemptions defined in Paragraph (c) and (d) of this Regulation, to sources whose volatile organic compound emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability” from the following cleaning operations:

- (1) spray gun cleaning;
- (2) spray booth cleaning;
- (3) large manufactured components cleaning;
- (4) parts cleaning;
- (5) equipment cleaning;
- (6) line cleaning;
- (7) floor cleaning;
- (8) tank cleaning; and
- (9) small manufactured components cleaning.

(c) Paragraph (e) of this Regulation does not apply to any cleaning materials used for cleaning operations covered by MCAPCO Regulations 2.0918 – “Can Coating”, 2.0919 – “Coil Coating”, 2.0921 – “Fabric and Vinyl Coating”, 2.0923 – “Surface Coating of Large Appliances”, 2.0924 – “Magnet Wire Coating”, 2.0930 – “Solvent Metal Cleaning”, 2.0935 – “Factory Surface Coating of Flat Wood Panels”, 2.0936 – “Graphic Arts”, 2.0961 – “Offset Lithographic Printing and Letterpress Printing”, 2.0963 – “Fiberglass Boat Manufacturing Materials”, 2.0964 – “Miscellaneous Industrial Adhesives”, 2.0965 – “Flexible Package Printing”, 2.0966 – “Paper, Film and Foil Coatings”, 2.0967 – “Miscellaneous Metal and Plastic Parts Coatings”, and 2.0968 – “Automobile and Light Duty Truck Assembly Coatings” are exempted from the requirements of this Regulation.

(d) Cleaning operations of portable or stationary mixing vats, high dispersion mills, grinding mills, tote tanks and roller mills for manufacturing of coating, ink or adhesive shall apply one or more of the following methods:

- (1) use industrial cleaning solvents that either contains less than 1.67 pounds VOC per gallon or has an initial boiling point greater than 120 degrees Celsius, and where the initial boiling point exceeds the maximum operating temperature by at least 100 degrees Celsius. The industrial cleaning solvents shall be collected and stored in closed containers;
- (2) implement the following work practices:
 - (A) maintain the equipment being cleaned as leak free; and
 - (B) drain volatile organic compounds containing cleaning materials from the cleaned equipment upon completion of cleaning; and
 - (C) store or dispose of volatile organic compounds containing cleaning materials, including waste solvent, in a manner that will prevent evaporation into atmosphere; and
 - (D) store all volatile organic containing cleaning materials in closed containers;
- (3) collect and vent the emissions from equipment cleaning to an add-on control system as set forth in Paragraph (g) of this Regulation; or
- (4) use organic solvents other than listed in Paragraph (d)(1) of this Regulation if no more than 60 gallons of fresh solvent shall be used per month. Organic solvent that is used or recycled either onsite or offsite for further use in equipment cleaning or the manufacture of coating, ink, or adhesive shall not be included in this limit.

(e) Any cleaning material of the nine cleaning operations listed in Paragraph (b) of this

Regulation shall have:

- (1) volatile organic compounds content that does not exceed 0.42 pounds per gallon;
or
- (2) composite vapor pressure limit of eight millimeters of mercury (mmHg) at 20 degrees Celsius.

(f) EPA Method 24 (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used in industrial cleaning solvents operations unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(g) Facilities which have chosen to use add-on control rather than to comply with the emission limits established in Paragraph (d) of this Regulation shall install control equipment with 85 percent overall efficiency.

(h) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

State History Note:

Authority G.S. 143 215.3(a)(1); 143 215.107(a)(5);

Eff. September 1, 2010.

Amended Eff, May 1, 2013

MCAQ History Note:

Eff. June 17, 2014

2.0963 FIBERGLASS BOAT MANUFACTURING MATERIALS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"Closed molding"** means any fabrication techniques in which pressure is used to distribute the resin through the reinforcing fabric placed between two mold surfaces to either saturate the fabric or fill the mold cavity.
- (2) **"Monomer"** means a volatile organic compound that partly combines with itself, or other similar compounds, by a cross-linking reaction to become a part of the cured resin.
- (3) **"Open molding"** means the open mold which is first spray-coated with a clear or pigmented polyester resin known as a gel coat. The gel coat will become the outer surface of the finished part.

(b) This Regulation applies to a facility that manufactures hulls or decks of boats and related parts, builds molds to make fiberglass boat hulls or decks and related parts from fiberglass, or

makes polyester resin putties for assembling fiberglass parts; and whose volatile organic compounds emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability” from sources for the following operations:

- (1) open molding and gel coat operations (including pigmented gel coat, clear gel coat, production resin, tooling gel coat, and tooling resin);
- (2) resins and gel coat mixing operations; and
- (3) resins and gel coat application equipment cleaning operations.

(c) The following activities are exempted from the provisions of this Rule:

- (1) surface coatings applied to fiberglass boats;
- (2) surface coatings for fiberglass and metal recreational boats (pleasure craft); and
- (3) industrial adhesives used in the assembly of fiberglass boats.

(d) Volatile organic compounds content limits in resin and gel coat that are used for any molding operations listed in Paragraph (b) of this Regulation and closed molding operations that do not meet the definition of monomer established in Subparagraph (a)(2) of this Regulation, such as vacuum bagging operations, shall not exceed monomer volatile organic compounds limits established in Table 1:

Table 1 Organic Hazardous Air Pollutants Content Requirements for Open Molding Resin and Gel Coat Operations (40 CFR 63, Subpart VVVV.)

Material	Application Method	Limit of Weighted-Average Monomer VOC Content (weight percent)
Production resin	Atomized (spray)	28
Production resin	Nonatomized	35
Pigmented gel coat	Any method	33
Clear gel coat	Any method	48
Tooling resin	Atomized	30
Tooling resin	Nonatomized	39
Tooling gel coat	Any method	40

The average monomer volatile organic compounds contents listed in the Table 1 shall be determined by using Equation 1:

$$\sum_{i=1}^n (M_i \text{ VOC}_i)$$

$$\text{Weighted Average Monomer VOC Content} = \frac{\sum_{i=1}^n (M_i \text{ VOC}_i)}{\sum_{i=1}^n (M_i)}$$

Where: M_i = mass of open molding resin or gel coat i used in the past 12 month in an operation, megagrams.

VOC_i = monomer volatile organic compounds content, by weight percent, of open

molding resin or gel coat i used in the past 12 month in an operation.

n = number of different open molding resins or gel coats used in the past 12 month in an operation.

(e) Molding monomer and non-monomer volatile organic compounds limits established in Paragraph (d) of this Regulation are not applicable to:

- (1) production resins (including skin coat resins) that meet specifications for use in military vessels or are approved by the U.S. Coast Guard for the use in the construction of lifeboats, rescue boats, and other life saving appliances approved under 46 CFR Subchapter Q, or the construction of small passenger vessels regulated by 46 CFR Subchapter T. Production resins that meet these criteria shall be applied with nonatomizing resin application equipment;
- (2) production and tooling resins; and pigmented, clear, and tooling gel coat used for part or mold repair and touch up. Total resin and gel coat materials that meet these criteria shall not exceed one percent by weight of all resin and gel coat used at a facility on a 12-month rolling-average basis; or
- (3) pure, 100-percent vinylester resin used for skin coats that are applied with nonatomizing resin application equipment and with the total amount of the resin materials not exceeding five percent by weight of all resin used at a factory on 12-month rolling-average basis.

(f) Any molding resin and gel coat operations listed in Paragraph (b) of this Regulation, that a facility chooses to include into average emissions among different operations to meet numerical monomer volatile organic compounds emission rate limits rather than to comply with the emission limits established in Paragraph (d) of this Regulation shall use:

- (1) Equation 2 to estimate a facility-specific monomer volatile organic compounds mass emission limit (12-month rolling average). Estimations of emissions average shall be determined on 12-month rolling average basis at the end of every month (12 times per year).

Equation 2:

$$\text{Monomer VOC Limit} = 46(M_R) + 159(M_{PG}) + 291(M_{CG}) + 54(M_{TR}) + 214(M_{TG})$$

Where:

Monomer VOC Limit = total allowable monomer volatile organic compounds that can be emitted from the open molding operations included in the average, kilograms per 12-month period.

M_R = mass of production resin used in the past 12 month excluding any materials that are exempt, megagrams.

M_{PG} = mass of pigmented gel coat used in the past 12 month, excluding any materials that are exempt, megagrams.

M_{CG} = mass of clear gel coat used in the past 12 month, excluding any materials that are exempt, megagrams

M_{TR} = mass of tooling resin coat used in the past 12 month, excluding any materials

that are exempt, megagrams

M_{TG} = mass of tooling gel coat used in the past 12 month, excluding any materials that are exempt, megagrams

The numerical coefficients associated with each term on the right hand side of Equation 2 are the allowable monomer volatile organic compounds emission rate for that particular material in units of kilograms of VOC per megagrams of material used.

- (2) Equation 3 to demonstrate that the monomer volatile organic compounds emissions from the operations included in the average do not exceed the emission limit calculated using Equation 2 from Subparagraph (f)(1) of this Regulation for the same 12-month period. This demonstration shall be conducted at the end of the first 12-month averaging period and at the end of every subsequent month for only those operations and materials that included in the average.

Equation 3:

$$\text{Monomer VOC emissions} = (PV_R)(M_R) + (PV_{PG})(M_{PG}) + (PV_{CG})(M_{CG}) + (PV_{TR})(M_{TR}) + (PV_{TG})(M_{TG})$$

Where:

Monomer VOC emissions = monomer volatile organic compounds emissions calculated using the monomer volatile organic compounds emission equation for each operation included in the average, kilograms.

PV_R = weighted-average monomer volatile organic compounds emission rate for production resin used in the past 12 month, kilograms per megagram.

M_R = Mass of production resin used in the past 12 month, megagrams.

PV_{PG} = weighted-average monomer volatile organic compounds emission rate for pigmented gel coat used in the past 12 month, kilograms per megagram.

M_{PG} = mass of pigmented gel coat used in the past 12 month, megagrams.

PV_{CG} = weighted-average monomer volatile organic compounds emission rate for clear gel coat used in the past 12 month, kilograms per megagram.

M_{CG} = Mass of clear gel coat used in the past 12 month, megagrams.

PV_{TR} = Weighted-average monomer volatile organic compounds emission rate for tooling resin used in the past 12 month, kilograms per megagram.

M_{TR} = Mass of tooling resin used in the past 12 month, megagrams.

PV_{TG} = Weighted-average monomer volatile organic compounds emission rate for tooling gel coat used in the past 12 month, kilograms per megagram.

M_{TG} = Mass of tooling gel coat used in the past 12 month, megagrams.

- (3) Equation 4 to compute the weighted-average monomer volatile organic compounds emission rate for the previous 12 month for each open molding resin and gel coat operation included in the average to apply the results in Equation 3.

Equation 4:

$$\sum_{i=1}^n (M_i PV_i)$$

$$PV_{OP} = \frac{\sum_{i=1}^n (M_i)}{\dots}$$

Where:

PV_{OP} = weighted-average monomer volatile organic compounds emission rate for each open molding operation (PV_R , PV_{PG} , PV_{CG} , PV_{TR} , and PV_{TG}) included in the average, kilograms of monomer volatile organic compounds per megagram of material applied.

M_i = mass or resin or gel coat i used within an operation in the past 12 month, megagrams.

n = number of different open molding resins and gel coats used within an operation in the past 12 month.

PV_i = the monomer volatile organic compounds emission rate for resin or gel coat i used within an operation in the past 12 month, kilograms of monomer volatile organic compounds per megagram of material applied. Equations in Table 2 shall be used to compute PV .

Table 2 Compliant Materials Monomer Volatile Organic Compounds Content for Open Molding Resin and Gel Coat.

For this material	and this application method	Use this formula to calculate the monomer VOC emission rate
1. Production resin, tooling resin	a. Atomized	$0.014 \times (\text{Resin VOC}\%)^{2.425}$
	b. Atomized, plus vacuum bagging with roll-out	$0.01185 \times (\text{Resin VOC}\%)^{2.425}$
	c. Atomized, plus vacuum bagging without roll-out	$0.00945 \times (\text{Resin VOC}\%)^{2.425}$
	d. Nonatomized	$0.014 \times (\text{Resin VOC}\%)^{2.275}$
	e. Nonatomized, plus vacuum bagging with roll-out	$0.0110 \times (\text{Resin VOC}\%)^{2.275}$
	f. Nonatomized, plus vacuum bagging without roll-out	$0.0076 \times (\text{Resin VOC}\%)^{2.275}$

2. Pigmented gel coat, clear gel coat, tooling gel coat	All methods	0.445 x (Gel coat VOC%) ^{1.675}
---	-------------	--

(g) If the owner or operator of any facility with molding resin and gel coat operations listed in Paragraph (b) of this Regulation, chooses to use of higher-monomer volatile organic compounds materials rather than to comply with the emission limits established in Paragraph (d) of this Regulation he shall:

- (1) install control equipment to meet the emission limit determined by Equation 2 in Subparagraph (f)(1) of this Regulation, applying the mass of each material used during the control device performance test in Equation 2 to determine the emission limit (in kilogram of monomer VOC) that is applicable during the test, instead of using the mass of each material as it established in Subparagraph (f)(1) of this Regulation;
- (2) monitor and record relevant control device and capture system operating parameters during the control device performance test to use the recorded values to establish operating limits for those parameters; and
- (3) monitor the operating parameters for the control device and emissions capture system and maintain the parameters within the established limits.

(h) Any molding resin and gel coat operations that use a filled production resin or filled tooling resin shall calculate the emission rate for the filled production resin or filled tooling resin on as applied basis using Equation 5. If the filled resin:

- (1) is used as a production resin then the value of PV_F calculated by Equation 5 shall not exceed 46 kilograms of monomer VOC per megagram of filled resin applied;
- (2) is used as a tooling resin then the value of PV_F calculated by Equation 5 shall not exceed 54 kilograms of monomer VOC per megagram of filled resin applied; and
- (3) is included in the emissions averaging procedure then the facility shall use the value of PV_F calculated by Equation 5 for the value PV_i in Equation 4 in Subparagraph (f)(3) of this Regulation.

Equation 5:

$$PV_F = PV_U \times \frac{(100 - \% \text{ Filler})}{100}$$

Where:

PV_F = The as-applied monomer volatile organic compounds emission rate for the filled production resin or tooling resin, kilograms monomer VOC per megagram of filled material.

PV_U = The monomer volatile organic compounds emission rate for the neat (unfilled) resin before filler is added, as calculated using the formulas in Table 2 of Subparagraph (f)(3) of this Regulation.

% Filler = The weight-percent of filler in the as-applied filled resin system.

(i) All resins and gel coats included in volatile organic compounds limits described in Paragraphs (d) through (h) shall meet non-monomer volatile organic compounds content limit of five percent.

(j) If the non-monomer volatile organic compounds content of a resin or gel coat exceeds five percent, then the excess non-monomer volatile organic compounds over five percent shall be counted toward the monomer volatile organic compounds content.

(k) SCAQMD Method 312-91, Determination of Percent Monomer in Polyester Resins, revised April 1996 shall be used to determine the monomer volatile organic compounds content of resin and gel coat materials unless the facility maintains records to document the volatile organic compounds content of resin and gel coat materials from the manufacturer.

(l) All resin and gel coat mixing containers with a capacity equal to or greater than 55 gallons, including those used for on-site mixing of putties and polyputties, shall have a cover with no visible gaps in place at all times except the following operations:

- (1) when material is being manually added to or removed from a container; or
- (2) when mixing or pumping equipment is being placed or removed from a container.

(m) Volatile organic compounds cleaning solvents for routine application equipment cleaning shall contain no more than five percent volatile organic compounds by weight, or have a composite vapor pressure of no more than 0.50 mm Hg at 68 degrees Fahrenheit.

(n) Only non-volatile organic compounds solvents shall be used to remove cured resin and gel coat from application equipment.

(o) The owner or operator of any facility subject to this Regulation shall comply with MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. September 1, 2010.*

2.0964 MISCELLANEOUS INDUSTRIAL ADHESIVES

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"Air-assisted airless spray"** means a system that consists of an airless spray gun with a compressed air jet at the gun tip to atomize the adhesive.
- (2) **"Airless spray"** means the application of an adhesive through an atomizing nozzle at high pressure (1,000 to 6,000 pounds per square inch) by a pump forces.
- (3) **"Application process"** means a process that consists of a series of one or more adhesive applicators and any associated drying area or oven where an adhesive is applied, dried and cured.
- (4) **"Dip Coating"** means application where substrates are dipped into a tank containing the adhesive. The substrates are then withdrawn from the tank and any excess adhesive is allowed to drain.

- (5) **"Electrocoating"** means a specialized form of dip coating where opposite electric charges are applied to the waterborne adhesive and the substrate.
- (6) **"Electrostatic spray"** means application where the adhesive and substrate are oppositely charged.
- (7) **"Flow coating"** means conveying the substrate over an enclosed sink where the adhesive is applied at low pressure as the item passes under a series of nozzles.
- (8) **"HVLP"** means a system with specialized nozzles that provide better air and fluid flow than conventional air atomized spray systems at low air pressure, shape spray pattern, and guide high volumes of atomized adhesive particles to the substrate using lower air pressure (10 pounds per square inch or less at the spray cap).
- (9) **"Miscellaneous industrial adhesives"** means adhesives (including adhesive primers used in conjunction with certain types of adhesives) used at industrial manufacturing and repair facilities for a wide variety of products and equipment that operate adhesives application processes.
- (10) **"Roll coating", "brush coating", and "hand application"** means application of high viscosity adhesives onto small surface area.

(b) Control of volatile organic compounds emissions from miscellaneous industrial adhesives product categories covered by MCAPCO Regulations 2.0921 – “Fabric and Vinyl Coating”, 2.0923 – “Surface Coating of Large Appliances”, 2.0935 – “Factory Surface Coating of Flat Wood Panels”, 2.0936 – “Graphic Arts”, 2.0961 – “Offset Lithographic Printing and Letterpress Printing”, 2.0962 – “Industrial Cleaning Solvents”, 2.0963 – “Fiberglass Boat Manufacturing Materials”, 2.0965 – “Flexible Package Printing”, 2.0966 – “Paper, Film and Foil Coatings”, 2.0967 – “Miscellaneous Metal and Plastic Parts Coatings”, and 2.0968 – “Automobile and Light Duty Truck Assembly Coatings” are exempted from the requirements of this Regulation.

(c) This Rule applies to miscellaneous industrial adhesive application sources whose volatile organic compounds emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability”.

(d) With the exception established in Paragraph (b) of this Regulation, all volatile organic compounds containing materials applied by each miscellaneous industrial adhesive application processes before control shall:

- (1) not exceed limits established in Table 1 of this Paragraph; and
- (2) be used in one of the following application methods in conjunction with using low volatile organic compounds adhesives or adhesive primers:
 - (A) electrostatic spray;
 - (B) HVLP spray;
 - (C) flow coat;
 - (D) roll coat or hand application, including non-spray application methods similar to hand or mechanically powered caulking gun, brush, or direct hand application;
 - (E) dip coat (including electrodesposition);
 - (F) airless spray;

- (G) air-assisted airless spray; or
- (H) other adhesive application method capable of achieving a transfer efficiency equivalent to or better than that achieved by HVLP spraying.

- (e) Emission limits established in Subparagraph (d)(1) of this Regulation shall be:
- (1) met by averaging the volatile organic compounds content of materials used on a single application unit for each day; and
 - (2) calculated as mass of volatile organic compounds per volume of adhesive primer excluding water and exempt compounds, as applied.

(f) If an adhesive is used to bond dissimilar substrates together in general adhesive application process (Table 1), then the applicable substrate category with the highest volatile organic compounds emission limit shall be established as the limit for such application.

Table 1. Volatile Organic Compounds Emission Limits for General and Specialty Adhesive Application Process.

General Adhesive Application Processes	VOC Emission Limit (lb/gal)
Reinforced Plastic Composite	1.7
Flexible vinyl	2.1
Metal	0.3
Porous Material (Except Wood)	1
Rubber	2.1
Wood	0.3
Other Substrates	2.1
Specialty Adhesive Application Processes	VOC Emission Limit (lb/gal)
Ceramic Tile Installation	1.1
Contact Adhesive	2.1
Cove Base Installation	1.3
Floor Covering Installation (Indoor)	1.3
Floor Covering Installation (Outdoor)	2.1
Floor Covering Installation (Perimeter Bonded Sheet Vinyl)	5.5
Metal to Urethane/Rubber Molding or Casting	7.1
Motor Vehicle Adhesive	2.1
Motor Vehicle Weatherstrip Adhesive	6.3
Multipurpose Construction	1.7
Plastic Solvent Welding (ABS)	3.3
Plastic Solvent Welding (Except ABS)	4.2
Sheet Rubber Lining Installation	7.1
Single-Ply Roof Membrane Installation/Repair (Except EPDM)	2.1

Structural Glazing	0.8
Thin Metal Laminating	6.5
Tire Repair	0.8
Waterproof Resorcinol Glue	1.4
Adhesive Primer Application Processes	VOC Emission Limit 1 (lb/gal)
Motor Vehicle Glass Bonding Primer	7.5
Plastic Solvent Welding Adhesive Primer	5.4
Single-Ply Roof Membrane Adhesive Primer	2.1
Other Adhesive Primer	2.1

(g) Any miscellaneous industrial adhesive application processes subject to this Regulation, which chooses to use add-on control for adhesive application processes rather than to comply with the emission limits established in Paragraph (d) of this Regulation, shall install control equipment with overall control efficiency of 85 percent or use a combination of adhesives and add-on control equipment on an application process to meet limits established in Paragraph (d) of this Regulation.

(h) EPA Method 24 or 25A (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of adhesives, other than reactive adhesives, and the procedure established in Appendix A of the NESHAP for surface coating of plastic parts (40 CFR Part 63, Subpart PPPP) shall be used to determine the volatile organic compounds content of reactive adhesives unless the facility maintains records to document the volatile organic compounds content of adhesives from the manufacturer.

(i) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143 215.3(a)(1); 143 215.107(a)(5);
Eff. September 1, 2010*

2.0965 FLEXIBLE PACKAGE PRINTING

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"First installation date"** means the actual date when the equipment or control device becomes operational. This date does not change if the equipment or control device is later moved to a new location.
- (2) **"Flexible Packaging"** means any package or part of a package the shape of which can be readily changed.
- (3) **"Flexographic printing"** means a printing process in which an image is raised above the printing plate, and the image carrier is made of rubber or other elastomeric materials.

- (4) **"Rotogravure press"** means an unwind or feed section, which may include:
 - (A) more than one unwind or feed station (such as on a laminator);
 - (B) series of individual work stations, one or more of which is a rotogravure print station;
 - (C) any dryers associated with the work stations; and
 - (D) a rewind, stack, or collection section.
- (5) **"Rotogravure printing"** means a printing process in which an image (type and art) is etched or engraved below the surface of a plate or cylinder.

(b) This Regulation applies to flexible packaging printing press sources whose emissions of volatile organic compounds exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability”.

(c) Volatile organic compounds content of materials used on any single flexible packaging printing press subject to this Regulation shall not exceed 0.8 pounds volatile organic compounds per one pound of solids applied, or 0.16 pounds volatile organic compounds per one pound of materials applied limits. These volatile organic compounds content limits are consistent with 80 percent overall emissions reduction level and reflect similar control levels as the capture and control option.

(d) Any flexible packaging printing press which has chosen to use add-on control for coating operations rather than to comply with the emission limits established in Paragraph (c) of this Regulation shall install control equipment with:

- (1) 65 percent overall control based on a capture efficiency of 75 percent and a control device efficiency of 90 percent for a press that was first installed prior to March 14, 1995 and that is controlled by an add-on control device whose first installation date prior to July 1, 2010;
- (2) 70 percent overall control based on a capture efficiency of 75 percent and a control device efficiency of 95 percent for a press that was first installed prior to March 14, 1995 and that is controlled by an add-on control device whose first installation date was on or after July 1, 2010;
- (3) 75 percent overall control based on a capture efficiency of 85 percent and a control device efficiency of 95 percent for a press that was first installed on or after March 14, 1995 and that is controlled by an add-on control device whose first installation date was prior July 1, 2010; and
- (4) 80 percent overall control based on a capture efficiency of 85 percent and a control device efficiency of 95 percent for a press that was first installed on or after March 14, 1995 and that is controlled by an add-on control device whose first installation date was on or after July 1, 2010.

(e) EPA Method 24 or 25A (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at flexible package printing facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(f) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143 215.3(a)(1); 143 215.107(a)(5);
Eff. September 1, 2010.*

2.0966 PAPER, FILM AND FOIL COATINGS

(a) For the purpose of this Regulation, the following definitions apply:

- (1) **"Paper, film, and foil coating line"** means a series of coating applicators, flash-off areas, and any associated curing/drying equipment between one or more unwind/feed stations and one or more rewind/cutting stations.
- (2) **"Flexographic coating"** means that the area to be coated is delineated by a raised surface on a flexible plate.
- (3) **"Rotary screen or flat screen coating"** means the application of a coating material to a substrate by means of masking the surface and applying a color or finish using a screen either in flat form or rotary form.
- (4) **"Rotogravure coating"** means the application of a coating material to a substrate by means of a roll coating technique in which the pattern to be applied is etched on the coating roll. The coating material is picked up in these recessed areas and is transferred to the substrate.

(b) With the exception in Paragraph (c) of this Regulation, this Regulation applies to paper, film and foil surface coating operations sources, including related cleaning activity, whose emissions of volatile organic compounds exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability”, at a facility that applies:

- (1) paper, film, or foil surfaces in the manufacturing of products for pressure sensitive tape and labels (including fabric coated for use in pressure sensitive tapes and labels; photographic film; industrial and decorative laminates; abrasive products (including fabric coated for use in abrasive products); and flexible packaging (including coating of non-woven polymer substrates for use in flexible packaging); and
- (2) coatings during coating applications for production of corrugated and solid fiber boxes; die-cut paper paperboard, and cardboard; converted paper and paperboard not elsewhere classified; folding paperboard boxes, including sanitary boxes; manifold business forms and related products; plastic aseptic packaging; and carbon paper and inked ribbons.

(c) The following types of coatings are not covered by this Regulation:

- (1) coatings performed on or in-line with any offset lithographic, screen, letterpress, flexographic, rotogravure, or digital printing press; or
- (2) size presses and on machine coaters that function as part of an in- line papermaking

system.

- (d) With the exceptions stated in Paragraph (c) of this Regulation, emissions of volatile organic compounds from:
- (1) pressure sensitive tape and label surface coating lines with the potential to emit, prior to controls, less than 25 tons per year of volatile organic compounds from coatings shall not exceed 0.20 pounds volatile organic compounds per pound of solids applied (0.067 pounds volatile organic compounds per pound of coating applied);
 - (2) paper, film, and foil surface coating lines with the potential to emit, prior to controls less than 25 tons per year of volatile organic compounds from coatings shall not exceed 0.40 pounds of volatile organic compounds per pound of solids (0.08 pounds volatile organic compounds per pound of coating applied); and
 - (3) The volatile organic compounds content limits shall be determined in accordance with Subparagraphs (c)(2) and (c)(3) of MCAPCO Regulation 2.0912 – “General Provisions on Test Methods and Procedures”.
- (e) EPA Method 24 or 25A (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at paper, film and foil coatings facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.
- (f) Any individual paper, film, and foil coating line with the potential to emit, prior to controls, at least 25 tons per year of volatile organic compounds from coatings shall apply control with overall volatile organic compounds efficiency of 90 percent rather than the emission limits established in Paragraph (d) of this Regulation or use a combination of coating and add-on control equipment on a coating unit to meet limits that are equivalent to 90 percent overall control efficiency.
- (g) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143 215.3(a)(1); 143 215.107(a)(5);
Eff. September 1, 2010*

2.0967 MISCELLANEOUS METAL AND PLASTIC PARTS COATINGS

- (a) For the purpose of this Regulation, the following definitions apply:
- (1) **"Air dried coating"** means a coating that is cured at a temperature below 90 degrees Celsius (194 degrees Fahrenheit).
 - (2) **"Baked coating"** means a coating that is cured at a temperature at or above 90 degrees Celsius (194 degrees Fahrenheit).

- (3) **"Clear coat"** means a colorless coating which contains binders, but no pigment, and is formulated to form a transparent film.
- (4) **"Coating unit"** means series one or more coating applicators and any associated drying area and oven wherein a coating is applied, dried, and cured.
- (5) **"Drum"** means any cylindrical metal shipping container larger than 12 gallons capacity but no larger than 110 gallons capacity.
- (6) **"Electric dissipating coating"** means a coating that rapidly dissipates a high voltage electric charge.
- (7) **"Electric-insulating varnish"** means a non-convertible-type coating applied to electric motors, components of electric motors, or power transformers, to provide electrical, mechanical, and environmental protection or resistance.
- (8) **"Etching filler"** means a coating that contains less than 23 percent solids by weight and at least 1/2-percent acid by weight, and is used instead of applying a pretreatment coating followed by a primer.
- (9) **"Extreme high-gloss coating"** means a coating which, when tested by the American Society for Testing Material Test Method D-523 adopted in 1980, shows a reflectance of 75 or more on a 60 degrees meter.
- (10) **"Extreme-performance coating"** means a coating used on a metal or plastic surface where the coated surface is, in its intended use, subject to the following:
 - (A) Chronic exposure to corrosive, caustic or acidic agents, chemicals, chemical fumes, chemical mixtures or solutions;
 - (B) Repeated exposure to temperatures in excess of 250 degrees Fahrenheit; or
 - (C) Repeated heavy abrasion, including mechanical wear and repeated scrubbing with industrial grade solvents, cleansers or scouring agents. Extreme performance coatings include coatings applied to locomotives, railroad cars, farm machinery, and heavy duty trucks.
- (11) **"High-performance architectural coating"** means a coating used to protect architectural subsections and which meets the requirements of the Architectural Aluminum Manufacturer Association's publication number AAMA 2604-05 (Voluntary Specification, Performance Requirements and Test Procedures for High Performance Organic Coatings on Aluminum Extrusions and Panels) or 2605-05 (Voluntary Specification, Performance Requirements and Test Procedures for Superior Performing Organic Coatings on Aluminum Extrusions and Panels).
- (12) **"Miscellaneous metal product and plastic parts surface coatings"** means the coatings that are applied to the surfaces of a varied range of metal and plastic parts and products. Such parts or products are constructed either entirely or partially from metal or plastic. These miscellaneous metal products and plastic parts include metal and plastic components of the following types of products as well as the products themselves: fabricated metal products, molded plastic parts, small and large farm machinery, commercial and industrial machinery and equipment, automotive or transportation equipment, interior or exterior automotive parts, construction equipment, motor vehicle accessories, bicycles and sporting goods, toys, recreational vehicles, pleasure craft (recreational boats), extruded aluminum structural components, railroad cars, heavier vehicles, lawn and garden equipment, business machines,

laboratory and medical equipment, electronic equipment, steel drums, metal pipes, and other industrial and household products.

- (13) **“Multi-component coating”** means a coating requiring the addition of a separate reactive resin, commonly known as a catalyst or hardener, before application to form a dry film.
- (14) **“One-component coating”** means a coating that is ready for application as it comes out of its container to form a dry film. A thinner, necessary to reduce the viscosity, is not considered a component.

(b) This Regulation applies to miscellaneous metal and plastic parts surface coating units whose volatile organic compounds emissions exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability” for coating and related cleaning activities of the following types of products:

- (1) fabricated metal products, molded plastic parts, small and large farm machinery, commercial and industrial machinery and equipment;
- (2) automotive or transportation equipment, interior or exterior automotive parts, construction equipment, motor vehicle accessories, bicycles and sporting goods;
- (3) toys, recreational vehicles, pleasure craft (recreational boats), extruded aluminum structural components, railroad cars, heavy vehicles, lawn and garden equipment;
- (4) business machines, laboratory and medical equipment; and
- (5) electronic equipment, steel drums metal pipes, and other industrial and household products.

(c) This Regulation does not apply to:

- (1) coatings that are applied to test panels and coupons as part of research and development, quality control;
- (2) performance testing activities at paint research or manufacturing facility; or
- (3) sources covered by MCAPCO Regulations 2.0921 – “Fabric and Vinyl Coating”, 2.0922 – “Metal Furniture Coating”, 2.0923 – “Surface Coating of Large Appliances”, 2.0935 – “Factory Surface Coating of Flat Wood Panels”, 2.0936 – “Graphic Arts”, 2.0961 – “Offset Lithographic Printing and Letterpress Printing”, 2.0962 – “Industrial Cleaning Solvents”, 2.0963 – “Fiberglass Boat Manufacturing Materials”, 2.0964 – “Miscellaneous Industrial Adhesives”, 2.0965 – “Flexible Package Printing”, 2.0966 – “Paper, Film and Foil Coatings”, and 2.0968 – “Automobile and Light Duty Truck Assembly Coatings”

(d) With the exception stated in Paragraph (c) of this Regulation, emissions of volatile organic compounds before control for surface coating of:

- (1) Metal parts and products shall not exceed limits as established in Table 1;

Table 1. Metal Parts and Products Volatile Organic Compounds content Limits

Coating Category	Air Dried lb VOC/gal	Baked lb VOC/gal
------------------	-------------------------	---------------------

	coating	coating
General One Component; General Multi Component; Military Specification	2.8	2.3
Camouflage; Electric-Insulating Varnish; Etching Filler; High Temperature; Metallic; Mold-Seal; Pan Backing; Pretreatment Coatings; Drum Coating, New, Interior; Drum Coating, Reconditioned, Exterior; Silicone Release; Vacuum-Metalizing	3.5	3.5
Extreme High-Gloss; Extreme Performance; Heat-Resistant; Repair and Touch Up; Solar-Absorbent	3.5	3.0
High Performance Architectural	6.2	6.2
Prefabricated Architectural Multi-Component; Prefabricated Architectural One-Component	3.5	2.3
Drum Coating, New, Exterior	2.8	2.8
Drum Coating, Reconditioned, Interior	4.2	4.2

(2) Plastic parts and products shall not exceed limits as established in Table 2;

Table 2. Plastic Parts and Products Volatile Organic Compounds content Limits

Coating Category	lbs VOC/gal coating
General One Component	2.3
General Multi Component; Metallic	3.5
Electric Dissipating Coatings and Shock-Free Coatings; Optical Coatings; Vacuum-Metalizing	6.7
Extreme Performance	3.5 (2-pack coatings)
Military Specification	2.8 (1 pack) 3.5 (2 pack)
Mold-Seal	6.3
Multi-colored Coatings	5.7

(3) automotive/transportation and business machine plastic parts shall not exceed limits as established in Table 3;

Table 3. Automotive/Transportation and Business Machine Plastic Parts Volatile Organic Compounds content Limits

Coating Category	lbs VOC/gal coating
------------------	---------------------

Automotive/Transportation Coatings	
I. High Bake Coatings – Interior and Exterior Parts	
Non-flexible Primer	3.5
Base Coats; Non-basecoat/clear coat; Flexible Primer	4.3
Clear Coat	4.0
II. Low Bake/Air Dried Coatings – Exterior Parts	
Primers; Basecoat; Non-basecoat/clearcoat	4.8
Clearcoats	4.5
III. Low Bake/Air Dried Coatings – Interior Parts	
IV. Touchup and Repair Coatings	
Business Machine Coatings	
Primers; Topcoat Texture Coat; Touchup and repair	2.9
Fog Coat	2.2

(4) pleasure craft shall not exceed limits as established in Table 4;

Table 4 Pleasure Craft Surface Coating Volatile Organic Compounds content Limits

Coating Category	lbs VOC/gal coating
Extreme High Gloss Topcoat	4.1
High Gloss Topcoat Finish; Primer/Surfacer; All other pleasure craft surface coatings for metal or plastic	3.5
Pretreatment Wash Primers	6.5
High Build Primer Surfacer; Other Substrate Antifoulant Coating	2.8
Aluminum Substrate Antifoulant Coating	4.7

(5) motor vehicle materials shall not exceed limits as established in Table 5.

Table 5 Motor Vehicle Materials Volatile Organic Compounds Content Limits

Coating Category	lbs VOC/gal coating
Motor vehicle cavity wax; Motor vehicle sealer; Motor vehicle deadener; Motor vehicle underbody coating; Motor vehicle trunk interior coating	5.4
Motor vehicle gasket/gasket sealing material; Motor vehicle bedliner	1.7
Motor vehicle lubricating wax/compound	5.8

(e) With the exception of motor vehicle materials coatings, any miscellaneous metal and plastic parts coatings operations facility may choose a combination of low volatile organic compounds coatings and add-on control equipment on a coating unit. Emissions of volatile organic

compounds before control with such combination shall not exceed limits for surface coating of:

- (1) Metal parts and products as established in Table 6;

Table 6. Metal Parts and Products Volatile Organic Compounds content Limits

Coating Category	Air Dried	Baked
	lb VOC/gal solids	lb VOC/gal solids
General One Component; General Multi Component; Military Specification;	4.52	3.35
Etching Filler; High Temperature; Metallic; Mold-Seal; Pan Backing; Pretreatment Coatings; Silicone Release; Drum Coating, New, Interior; Drum Coating, Reconditioned, Exterior; Vacuum-Metalizing	6.67	6.67
Extreme High-Gloss; Extreme Performance; Heat-Resistant; Solar-Absorbent	6.67	5.06
High Performance Architectural	38.0	38.0
Prefabricated Architectural Multi-Component	6.67	3.35
Prefabricated Architectural One-Component	6.67	3.35
Solar-Absorbent	6.67	5.06
Drum Coating, New, Exterior	4.52	4.52
Drum Coating, Reconditioned, Interior	6.67	9.78

- (2) plastic parts and products as established in Table 7;

Table 7. Plastic Parts and Products Volatile Organic Compounds content Limits

<i>Coating Category</i>	lbs VOC/gal solids
General One Component	3.35
General Multi Component; Metallic	6.67
Electric Dissipating Coatings and Shock-Free Coatings Optical Coatings; Vacuum-Metalizing	74.7
Extreme Performance	6.67(2-pack)
Military Specification	4.52 (1 pack) 6.67 (2 pack)
Mold-Seal	43.7
Multi-colored Coatings	25.3

- (3) automotive/transportation and business machine plastic parts as established in Table 8;

Table 8. Automotive/Transportation and Business Machine Plastic Parts Volatile Organic

Compounds content Limits

Coating Category	lbs VOC/gal solids
Automotive/Transportation Coatings¹	
I. High Bake Coatings – Interior and Exterior Parts	
Flexible Primer	11.58
Non-flexible Primer; Non-basecoat/clear coat	6.67
Base Coats	10.34
Clear Coat	8.76
II. Low Bake/Air Dried Coatings – Exterior Parts	
Primers	13.8
Basecoat; Non-basecoat/clearcoat	15.59
Clearcoats:	11.58
III. Low Bake/Air Dried Coatings – Interior Parts	
IV. Touchup and Repair Coatings	
Business Machine Coatings	
Primers; Topcoat; Texture Coat; Touchup and repair	4.8
Fog Coat	3.14

(4) pleasure craft surface coatings as established in Table 9;

Table 9. Pleasure Craft surface Coatings Volatile Organic Compounds content Limits

Coating Category	lbs VOC/gal solids
Extreme High Gloss Topcoat	9.2
High Gloss Topcoat; Finish Primer/Surfacer; All other pleasure craft surface coatings for metal or plastic	6.7
Pretreatment Wash Primers	55.6
Aluminum Substrate Antifoulant Coating	12.8
High Build Primer Surfacer; Other Substrate Antifoulant Coating	4.4

(f) EPA Method 24 or 25A (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coating materials used at miscellaneous metal and plastic part coating facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(g) With the exception of motor vehicle materials coatings, any miscellaneous metal and plastic parts coatings operations facility may choose to use add-on control equipment with an overall control efficiency of 90 percent in lieu of using low-VOC coatings and specified application methods.

(h) The owner or operator of any facility subject to this Regulation shall comply with the MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143-215.3(a)(1); 143 215.107(a)(5);
Eff. September 1, 2010.*

2.0968 AUTOMOBILE AND LIGHT DUTY TRUCK ASSEMBLY COATINGS

- (a) For the purpose of this Regulation, the following definitions apply:
- (1) **"Automobile"** means a motor vehicle designed to carry up to eight passengers, excluding vans, sport utility vehicles, and motor vehicles designed primarily to transport light loads of property.
 - (2) **"Automobile Topcoat Protocol"** means Protocol For Determining The Daily Volatile Organic Compound Emission Rate Of Automobile and Light-duty Truck Topcoat Operations (EPA-450/3-88-018).
 - (3) **"Electrodeposition"** means a process of applying a protective, corrosion-resistant waterborne primer on exterior and interior surfaces that provides coverage of recessed areas. It is a dip coating method that uses an electrical field to apply or deposit the conductive coating onto the part. The object being painted acts as an electrode that is oppositely charged from the particles of paint in the dip tank.
 - (4) **"Final repair"** means the operations performed and coating(s) applied to completely assembled motor vehicles or to parts that are not yet on a completely assembled vehicle to correct damage or imperfections in the coating.
 - (5) **"Light-duty truck"** means vans, sport utility vehicles, and motor vehicles designed primarily to transport light loads of property with gross vehicle weight rating of 8,500 pounds or less.
 - (6) **"Primer-surfacer"** means an intermediate protective coating applied over the electrodeposition primer (EDP) and under the topcoat. Primer-surfacer provides adhesion, protection, and appearance properties to the total finish.
 - (7) **"Solids turnover ratio (R_T)"** means the ratio of total volume of coating solids that is added to the EDP system in a calendar month divided by the total volume design capacity of the EDP system.
- (b) This Regulation applies to automobile and light-duty truck assembly coating operations and related cleaning activities whose emissions of volatile organic compounds exceed the threshold established in Paragraph (b) of MCAPCO Regulation 2.0902 – “Applicability” at:
- (1) automobile or light-duty assembly plants during the vehicle assembly processes with the following primary coating product applications:
 - (A) new automobile or new light-duty truck bodies, or body parts for new automobiles or new light-duty trucks;
 - (B) other parts that are coated along with these bodies or body parts; or
 - (C) additional coatings which include glass bonding primer, adhesives, cavity wax, sealer, deadener, gasket/gasket sealing material, underbody coating, trunk

- interior coating, bedliner, weatherstrip adhesive, and lubricating waxes/compounds; and
- (2) facilities that perform coating operations on a contractual basis other than plastic or composites molding facilities.

(c) This Regulation does not apply to:

- (1) aerosol coatings of automobile and light-truck assembly coatings;
- (2) coatings that are applied to other parts intended for use in new automobiles or new light-duty trucks (e.g., application of spray primer, color and clear coat to fascia or bumpers) on coating lines that are not related to the vehicle assembly process at automobile or light-duty assembly plants. They are covered by MCAPCO Regulations 2.0964 – “Miscellaneous Industrial Adhesives”, and 2.0967 – “Miscellaneous Metal and Plastics Parts Coating”; and
- (3) aftermarket repair or replacement parts for automobiles or light-duty trucks that are covered by MCAPCO Regulations 2.0964 and 2.0967.

(d) With the exception of materials supplied in containers with a net volume of 16 ounces or less, or a net weight of one pound or less, emissions of volatile organic compounds before control for:

- (1) automobile and light-duty truck assembly coatings shall not exceed limits established in Table 1

Table 1. Volatile Organic Compounds emission limits for automobile and light-duty truck assembly coatings.

Assembly Coating Process	Volatile Organic Compounds Emission Limit		
Electrodeposition primer (EDP) operations (including application area, spray/rinse stations, and curing oven)	When solids turnover ratio (R_T) ≥ 0.16 ;	When $0.040 \leq R_T < 0.160$;	When $R_T < 0.040$;
	0.7lb/gal coatings solids applied.	$0.084^{0.160-R_T} \times 8.34$ lb/gal coating solids applied.	No VOC emission limit.
Primer-surfacer operations (including application area, flash-off area, and oven)	12.0 lb VOC/gal deposited solids on a daily weighted average basis as determined by following the procedures in the revised Automobile Topcoat Protocol		
Topcoat operations (including application area, flash-off area, and oven)	12.0 lb VOC/gal deposited solids on a daily weighted average basis as determined by following the procedures in the revised Automobile Topcoat Protocol		

Final repair operations	4.8 lb VOC/gallon of coating less water and less exempt solvents on a daily weighted average basis or as an occurrence weighted average.
Combined primer-surfacer and topcoat operations	12.0 lb VOC/gal deposited solids on a daily weighted average basis as determined by following the procedures in the revised Automobile Topcoat Protocol

(2) materials used at automobile and light-duty truck assembly coatings facilities shall not exceed limits established in Table 2.

Table 2. Volatile Organic Compounds emission limits for miscellaneous materials used at automobile and light-duty

Material	VOC Emission Limit
Automobile and light-duty truck glass bonding primer	900
Automobile and light-duty truck adhesive	250
Automobile and light-duty truck cavity wax	650
Automobile and light-duty truck sealer	650
Automobile and light-duty truck deadener	650
Automobile and light-duty truck gasket/gasket sealing material	200
Automobile and light-duty truck underbody coating	650
Automobile and light-duty truck trunk interior coating	650
Automobile and light-duty truck bedliner	200
Automobile and light-duty truck weatherstrip adhesive	750
Automobile and light-duty truck lubricating wax/compound	700

(e) EPA Method 24 or 25A (40 CFR Part 60, Appendix A-7) shall be used to determine the volatile organic compounds content of coatings, other than reactive adhesives used at automobile and light-duty truck coating facilities unless the facility maintains records to document the volatile organic compounds content of coating materials from the manufacturer.

(f) The emission limits established in Paragraph (d) of this Regulation may be achieved with a combination of higher-solid solvent-borne coatings, efficient application equipment and bake oven exhaust control.

(g) The owner or operator of any facility subject to this Regulation shall comply with the

MCAPCO Regulations 2.0903 – “Recordkeeping:Reporting:Monitoring” and 2.0958 – “Work Practices for Sources of Volatile Organic Compounds”.

*History Note: Authority G.S. 143-215.3(a)(1); 143 215.107(a)(5);
Eff. September 1, 2010.*

